

2017-0257
2017-07-24

C-SWIFT (Blue, Red, Black)

ANTIFOULING PAINT

DOMESTIC

SUSPENSION

KEEP OUT OF REACH OF CHILDREN

IMPORTANT

READ THE LABEL BEFORE USING.

FOR USE ON BOATS ONLY.

SKIN AND EYE IRRITANT.

NOT FOR SPRAY USE.

ONLY BRUSH OR ROLLER APPLICATION.

GUARANTEE: ELEMENTAL COPPER, PRESENT AS CUPROUS OXIDE 38%

REGISTRATION NO. 22727

PEST CONTROL PRODUCTS ACT

NET CONTENTS : 4 L to 20 L

CAUTION

FLAMMABLE

DANGER

POISON

International Paint LLC, 6001 Antoine Drive, Houston, Texas 77091 USA
713-682-1711

C-SWIFT
Antifouling Paint

DIRECTIONS FOR USE:

A long life antifouling that provides up to 36 months of performance.
C-Swift releases biocide at a controlled consistent rate as it wears away.

OVERCOATING EXISTING ANTIFOULINGS: Contact International Paints regarding overcoating existing antifoulings with C-Swift.

NEW WORK:

Steel: Prepare steel by blasting to SSPC-SP10 or SA2 ½ near white metal. Apply multiple coats of C-Protac Multi-Purpose Epoxy* or C-Protac Bronze to achieve 10 mils d.f.t. Apply two coats of C-Swift observing overcoating times.

Wood: Sand wood and wipe surface clean. Thin first coat of C-Swift 20% with C-Solv Universal Thinner. Apply second coat unthinned observing overcoating times.

Fiberglass: Wipe down fiberglass with C-Solve Fiberglass Prep Solvent. Apply 1 thin coat of C-Glass Fiberglass Tie Coat. Overcoat primer within 2-3 hours, no more, no less. Apply second coat of C-Swift observing overcoating times. For osmosis repair and prevention, use the Interlux Interprotect System.

Aluminum: Light sand sweep to etch aluminum. Apply multiple coats of C-Protac Multi-Purpose Epoxy* or C-Protac Bronze to achieve 12 mils d.f.t. If aluminum cannot be prepared by sandblasting, a coat of C-Etch Vinyl Etch Primer will be required prior to either C-Protac anti-corrosive. Apply 2 coats of C-Swift observing overcoating times.

IMPORTANT: C-Swift contains copper (which reacts with aluminum). Regular inspection of primer is required to ensure film integrity.

*The first coat of C-Swift should be applied to the last coat of C-Protac MultiPurpose Epoxy while it is still tacky to the thumbprint method.

APPLICATION: STIR THOROUGHLY. Apply by brush or roller at least 2 unthinned heavy coats of C-Swift. For best results, 3 coats are recommended.

COVERAGE: 9.8 m² per litre at 50 microns d.f.t. per coat

CLEAN-UP: C-Solv Universal Thinner

DRYING: Touch dry: 4 hours

OVERCOATING TIME: Recommended minimum 6 hours, maximum 28 days

IMMERSION: Minimum 12 hours, maximum 28 days

N.B.: These are guidelines only. Temperature and humidity affect cure time.

DO NOT place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

FOR MORE DETAILED INFORMATION, REFER TO PRODUCT DATA BULLETIN.

NOTICE TO USER: This control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by spillage, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Do not re-use container for any purpose. Dispose of empty container and paint debris in accordance with provincial requirements. For information on the disposal of unused, unwanted product, and the clean-up of spills, contact the manufacturer or the Provincial Regulatory Agency.

PRECAUTIONS: Keep away from heat, sparks and flame. Vapours heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical resistant gloves, goggles and footwear, and chemical resistant clothing including hood or hat at all times during handling and application.

- KEEP OUT OF REACH OF CHILDREN - Handle with care and mix carefully - When using, do not eat, drink or smoke - Take a shower immediately after work - Wear freshly laundered clothes daily - Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet - Store and wash all protective clothing separately from household laundry - Wash protective clothing in detergent and hot water before reuse - Use only in well ventilated areas.

FIRST AID: IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice. IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice. IF SWALLOWED: Call a poison control centre or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give anything by mouth to an unconscious

person. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion. Treat symptomatically.

EPA EST. NO. 2693-NJ-1

NOT REGISTERED FOR USE IN THE UNITED STATES OF AMERICA