

2018-1824  
2018-06-06

CONTENANT : 1 L rond en métal / 3,78 L métal  
FORMAT : approx. 5 x 14 po / 7½ x 22 po  
PMS étiquette : Ocre métallique Pantone 8643  
PMS bouchon : sans objet  
Vernis : UV

Techniseal® (logo)

## Wood Preservative

IDEAL TO TREAT END CUTS

- FOR DECKS, FENCES, SIDING, ETC.
- TREATED OR BARE WOOD – NEW OR OLD
- PREVENTS MILDEW, ROT AND FUNGUS
- PENETRATING – LEAVES NO SURFACE FILM

DOMESTIC - READ LABEL BEFORE USE  
KEEP OUT OF REACH OF CHILDREN - Exterior

NOT FOR USE INSIDE DWELLINGS FOR EXTERIOR USE ONLY

GUARANTEE: zinc naphthenate: 25%  
zinc (as elemental): 2%

REG. NO. 24351 P.C.P. ACT

(Symbole : tête de mort dans un octogone)



DANGER / POISON  
WARNING EYE AND SKIN IRRITANT - POTENTIAL SKIN SENSITIZER

[OLDCASTLE BUILDING Products Canada Inc. DBA TECHNISEAL 300](#), avenue liberté, Candiac, QC J5R 6X1

144-271/273  
1 L / 3.78L  
Clear

Techniseal® Wood Preservative is a clear, penetrating fungicide designed for the protection of new or old untreated wood prior to the application of a sealant, stain, paint or varnish. It is ideal to touch up end cuts on pressure-treated wood, or to fully protect untreated wood. Equally effective on vertical or horizontal surfaces, it extends the life of decks, fences, siding, pergolas, balconies, shingles, quays, etc. Made of zinc naphthenate, Techniseal® Preservative protects wood against mildew, rot and fungus caused by water and dampness.

**Restrictions:** Do not apply by spraying or immersion. Use on exterior, aboveground surfaces only. Do not use inside houses. Do not apply to picnic tables; playground accessories or other surfaces that may be in prolonged contact with skin, vegetation, food, feed or drinking water. Do not contaminate drinking or irrigation water sources or aquatic habitats by cleaning tools or by disposing of trash.

**LIMITED WARRANTY:** Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 0.4 m<sup>2</sup> – 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 0.4 m<sup>2</sup> (4 sq. ft.). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.

## DIRECTIONS

### BEFORE YOU BEGIN

- **Do not apply to cedar wood.**
- Apply only to bare material\* or to material previously protected with this product.
- **ALWAYS TEST** on a small hidden area of approximately 0.4 m<sup>2</sup> (4 sq. ft.) to ensure that the result meets your expectations (see Warranty).
- \*Sprinkle a few drops of water on the surface prior to treatment. If water is repelled, do not apply this product.

### SURFACE PREPARATION (ESSENTIAL)

1. Cover adjacent surfaces that are not to be treated.
2. Clean the entire surface with Techniseal® Wood Cleaner (144-500), as directed on the product label.

### APPLICATION

**Application Conditions:**

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 10°C and 25°C.
- No rain forecast for the next 24 hours.
- Use a consistent application method over the entire surface.

**Tools Required:**

- Paintbrush
- Masking tape, plastic tarp and other protection accessories.

This product is ready to use. Do not dilute. Shake well or stir product thoroughly before and during application.

With the paintbrush, spread evenly and saturate wood with a coat of Preservative. Avoid product accumulation. On very porous wood or on wood that will not be covered with a coating, wait 6 to 24 hours and apply a second coat.

To better protect non pressure-treated wood, wait 48 hours and apply Techniseal Maintenance Free Protector for wood (144-3X3).

**Drying:** Wait 24 hours before walking on the treated surface. Prevent access during that period.

**Coverage:** 1 L covers 3 to 5 m<sup>2</sup> (30 to 50 sq. ft.). Coverage will depend on surface porosity.  
3.78 L covers 10 to 19 m<sup>2</sup> (110 to 200 sq. ft.). Coverage will depend on surface porosity.

**Storage:** Store in a cool, dry place. Store unused Preservative out of the reach of children and animals.

**Cleaning & Disposal:** Use a mineral spirit, then a detergent and water. Do not reuse empty container; dispose of at the local recycling center. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

#### **PRECAUTION**

##### **MAY IRRITATE EYES. MAY IRRITATE SKIN.**

Keep container closed when not in use. Keep out of reach of children. Avoid breathing vapours. Harmful if swallowed or inhaled. Flammable: keep away from flames or sparks. Causes skin and eye irritation. Potential skin sensitizer. Avoid breathing vapours, contact with skin, eyes and clothing. Wear a long-sleeved shirt, long pants, socks, shoes, and rubber gloves when applying this product. Wash with soap and water after use and before eating or smoking. Phytotoxic when wet. Toxic to fish; do not contaminate bodies of water.

**FIRST AID:** If swallowed, call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give **any** liquid to the person. Do not give anything by mouth to an unconscious person. If in eyes, hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. In case of contact with skin or clothing, take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice. If inhaled, move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

**TOXICOLOGICAL INFORMATION:** Contains petroleum distillates and zinc naphthenate; treat for ingestion of kerosene. Vomiting may cause aspiration pneumonia.

**ENVIRONMENTAL HAZARDS:** Toxic to aquatic organisms.

? : service@techniseal.com

1 800 465-7325

Monday to Thursday, 8 a.m. to 5 p.m. Friday, 8 a.m. to 4 p.m., Eastern Time.

Registered Trademark and Graphic Design owned by Techniseal®

Made in Canada  
(1114)