

2019-6368
2019-12-17

TRI-LUX II A/F Series

SUSPENSION

COMMERCIAL

IMPORTANT
READ THE LABEL BEFORE USING
FOR USE ON BOATS ONLY.

SKIN AND EYE IRRITANT.

ACTIVE INGREDIENT: Copper present as cuprous thiocyanate 11.88%

REGISTRATION NO. 25545 PEST CONTROL PRODUCTS ACT.

DANGER

POISON

FLAMMABLE

NET CONTENTS 3.78 L

International Paint LLC
6001 Antoine Drive
Houston, RX 77091
USA
1 713 682-1711

2019-6368
2019-12-17

DISCLAIMER:

The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose or application.

IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.

By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN.

Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours or spray mist.

Wear a long-sleeved shirt, long pants, shoes and socks, chemical-resistant gloves, goggles, a chemical-resistant hat that covers the neck (e.g., Sou'Wester) during mixing/loading, application, clean-up and repair, or when removing old antifouling paint coatings. In addition, wear a respirator with a NIOSH approved organic-vapour-removing cartridge with a prefilter approved for pesticides OR a NIOSH approved canister approved for pesticides during application. Wear a NIOSH-approved N95 filtering facepiece respirator (dust mask) that is properly fit tested when removing old antifouling paint coatings

Remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them.

For cleaning/maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry.

Handle with care and mix carefully – When using, do not eat, drink or smoke – Take a shower immediately after work – Wear freshly laundered clothes daily – Wash hands and face before eating, drinking, smoking and using the toilet – Store and wash all protective clothing separately from household laundry – Wash protective clothing in detergent and hot water before reuse – Use only in well ventilated areas.

2019-6368
2019-12-17

FIRST AID:

If swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

If inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

If in eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION:

Treat symptomatically. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia. Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion.

ENVIRONMENTAL PRECAUTIONS:

Toxic to aquatic organisms. This product contains petroleum distillate which is moderately to highly toxic to aquatic organisms. Avoid contamination of aquatic systems during application. Do not contaminate these systems through direct application, disposal of waste or cleaning of equipment.

STORAGE:

To prevent contamination, store this product away from food or feed.

DISPOSAL:

1. Triple – or pressure – rinse the empty container. Add the rinsings to the treatment site.
2. Follow provincial instruction for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill and for clean-up of spills.

DIRECTIONS FOR USE

TRI-LUX® II A/F Series

2019-6368
2019-12-17

PRODUCT DESCRIPTION: TRI-LUX® II A/F Series is a unique copolymer bottom paint, available in a wide range of bright colors. Although specifically formulated for aluminum crafts and related surfaces, TRI-LUX® II A/F Series is equally compatible with fiberglass, wood, steel and lead. TRI-LUX® II A/F Series is ideal for aluminum outdrive and outboard motor lower units; provided the application instructions are followed. TRI-LUX® II A/F Series can be used in fresh, salt and brackish water.

SURFACE PREPARATION: Surface must be clean and dry and properly prepared prior to painting. All sanded surfaces must be wiped clean with INTERLUX® SPECIAL THINNER 216 to remove all sanding residue.

GENERAL APPLICATION: For use on primed aluminum, fiberglass, wood, steel and lead below the true waterline. Apply at least two full coats by solvent resistant roller, natural bristle brush or by spray.

MIXING AND THINNING: Shake or mix and stir continuously while using. When brushing or rolling, do not thin this bottom paint – except for the first coat on bare wood. When spraying, thin 10% with INTERLUX® SPECIAL THINNER 216.

THEORETICAL COVERAGE: Depending on surface condition, one litre of TRI-LUX® II A/F Series will usually cover 9.80 square metres, when brushing or rolling, or 7.35 square metres when spraying.

APPLICATION DATA:

<u>Spray Equipment</u>	<u>Pressure (kPa)</u>	<u>Tip Size</u>
Airless	17,500-21,000	533 Microns
Pressure Pot 10-15 Pot	50-65	1,776-2,157 Microns
Syphon Cup	N/A	N/A

CLEAN-UP: Use INTERLUX® SPECIAL THINNER 216 for cleaning paint brushes and equipment.

ESTIMATED DRY TIMES: TRI-LUX® II A/F Series may be overcoated with itself after 12 hours. Prior to launch, allow to dry for 12 hours, but no more than 90 days.

APPLICATION SYSTEMS

BARE ALUMINUM: On small craft where sandblasting is not practical, i.e. aluminum pontoon boats, car top boats, etc., wipe bare metal with INTERLUX® SPECIAL THINNER 216 to remove oil and grease. Uniformly, sand surface to a bright finish with medium grit emery cloth. Wipe surface clean of dust with INTERLUX® SPECIAL THINNER 216. Immediately apply one thin coat of INTERLUX® VINYL-LUX® PRIMEWASH 353/354 thinned 25% with INTERLUX® VINYL-LUX® SOLVENT 355. Allow to dry a minimum of one hour but no more than twenty-four hours; then apply INTERLUX® INTERPROTECT® 2000E/2001E. Apply enough INTERLUX® INTERPROTECT® 2000E/2001E to obtain a 10 mil dry film thickness.

2019-6368
2019-12-17

This usually takes 4-5 coats to obtain this thickness, although the amount of paint is more important than the number of coats. Be sure to follow dry times on the INTERLUX® INTERPROTECT® 2000E/2001E label. When complete, apply at least 3 coats of TRI-LUX® II A/F Series. If dry times for INTERLUX® INTERPROTECT® 2000E/2001E cannot be followed, use the following alternate system. Apply four coats of INTERLUX® UNDERWATER METAL PRIMER 360R over the INTERLUX® VINYL-LUX® PRIMEWASH 353/354. On rivets and adjacent areas, apply a minimum of 5 coats of INTERLUX® UNDERWATER METAL PRIMER 360R. Finish with at least three coats of TRI-LUX® II A/F Series.

ALUMINUM – PREVIOUSLY PAINTED WITH ANTIFOULING PAINT: Remove incompatible antifouling paint (soft, tin-based copolymers or cuprous oxide based) and primer (EPOXY PRIMER MAY BE LEFT ON IF IT IS IN GOOD CONDITION) to bare aluminum and proceed with bare system above. If the surface was previously painted with TRI-LUX® II A/F Series paint and primer system is in good condition, sand with 80 grit sandpaper. Wipe off sanding residue with INTERLUX® SPECIAL THINNER 216. Any areas where the bare aluminum is exposed must be re-sanded with medium grit emery cloth and wiped clean. Immediately apply INTERLUX® UNDERWATER METAL PRIMER 360R to bare areas. Then apply at least two full coats of INTERLUX® UNDERWATER METAL PRIMER 360R to the entire underwater surface. Do not apply INTERLUX® UNDERWATER METAL PRIMER 360R or TRI-LUX® II A/F Series above the true waterline. Apply three coats of TRI-LUX® II A/F Series.

ALUMINUM – PREVIOUSLY PAINTED WITH A FACTORY FINISH: Wipe surface clean with INTERLUX® SPECIAL THINNER 216 to remove contaminants. Sand the surface with 120 grit sandpaper. Wipe the surface again with INTERLUX® SPECIAL THINNER 216, to remove sanding residue. Immediately spot prime any bare areas with INTERLUX® UNDERWATER METAL PRIMER 360R. Apply at least two full coats of INTERLUX® UNDERWATER METAL PRIMER 360R (three coats to riveted areas), to the entire bottom, allowing appropriate dry times. After an overnight dry, apply at least three coats of TRI-LUX® II A/F Series. Do not apply INTERLUX® UNDERWATER METAL PRIMER 360R or TRI-LUX® II A/F Series above the true waterline.

UNDERWATER METALS INCLUDING SHAFTS, PROPELLERS, TRIM TABS, STRUTS AND THRU-HULL FITTINGS: These areas require special attention to initial surface preparation in order to improve adhesion. Treat these areas the same as bare aluminum. The longevity of this system will probably not be equal to that of the remainder of the boat due to the R.P.M.s these parts withstand. For more details contact Interlux Technical Service at 1-800-468-7589.

BARE FIBERGLASS – NO SAND SYSTEM: Clean entire surface thoroughly with INTERLUX® FIBERGLASS SOLVENT WASH 202, changing rags frequently. Before the liquid dries, wipe clean with dry cloth. Be sure all wax and other contaminants are removed; if surface is not clean, delamination will occur. Apply one thin, continuous coat of INTERLUX® AL 200 FIBERGLASS PRIMER® with brush or roller. Do not spray or sand. Allow to dry two hours, but no more than three hours, and apply the first coat of TRI-LUX® II A/F Series. Apply

2019-6368
2019-12-17

a minimum of three coats of TRI-LUX® II A/F Series.

BARE FIBERGLASS – SANDING SYSTEM: Be sure all wax and other contaminants are removed by cleaning the surface with INTERLUX® FIBERGLASS SOLVENT WASH 202. Wash the surface thoroughly with a rag that has been soaked in INTERLUX® FIBERGLASS SOLVENT WASH 202 and, before the liquid dries, wipe off with a clean dry cloth. Change the rags frequently. After the surface has been cleaned, sand with 80 grit sandpaper until a flat, matte finish has been obtained. Wipe off the sanding residue with INTERLUX® FIBERGLASS SOLVENT WASH 202. Apply three coats of TRI-LUX® II A/F Series.

BARE WOOD: Sand entire surface thoroughly to a smooth finish with 80 grit sandpaper. Clean off the sanding residue using a rag that has been dampened with INTERLUX® SPECIAL THINNER 216. Apply the first coat of TRI-LUX® II A/F Series reduced with INTERLUX® SPECIAL THINNER 216 (10% maximum) to penetrate the porous grain. Fill seams with

INTERLUX® SEAM COMPOUND 30. Apply second and third coats of TRI-LUX® II A/F Series unreduced.

PREVIOUSLY PAINTED FIBERGLASS AND WOOD – GOOD CONDITION: Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit sandpaper. Wipe surface clean. Apply three coats of TRI-LUX® II A/F Series.

NOTE: TRI-LUX® II A/F Series white may show a green patina at the waterline, especially when applied in thin coats. This patina does not affect antifouling performance. This product has been shown to be efficacious as an antifouling coating for a period of at least two years, when proper film thickness is applied.

DO NOT apply this product in a way that will contact workers or bystanders, either directly or through drift. Only protected handlers may be in the treatment area during application.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats.

DO NOT discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified.

Prevent paint chips or dust caused by removing paint from entering water. **DO NOT** place the painted parts in water after painting until the paint is fully cured (see dry times on the label).

Interlux, for more information call 1 713 682-1711,
or write 6001 Antoine Drive, Houston TX 77091, USA

NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an

2019-6368
2019-12-17

offence under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label.

NOT REGISTERED FOR USE IN THE UNITED STATES OF AMERICA