

2017-0238
2017-07-13

ULTRA-KOTE (Red, Green, Blue, Black, Brown)

ANTIFOULING PAINT SERIES

DOMESTIC

SOLUTION

KEEP OUT OF REACH OF CHILDREN

IMPORTANT

READ THE LABEL BEFORE USING.

FOR USE ON BOATS ONLY.

SKIN AND EYE IRRITANT.

NOT FOR SPRAY USE.

ONLY BRUSH OR ROLLER APPLICATION.

GUARANTEE: CUPROUS OXIDE 65.71%

COPPER (AS ELEMENTAL) 58.36%

WARNING, CONTAINS THE ALLERGEN SOY

REGISTRATION NO. 24395

PEST CONTROL PRODUCTS ACT

3.78 L

CAUTION

FLAMMABLE

DANGER

POISON

International Paint LLC,
6001 Antoine Drive, Houston, Texas 77091 USA
713-682-1711

ULTRA-KOTE

Antifouling Bottom Paint

DIRECTIONS FOR USE:

PRODUCT DESCRIPTION: ULTRA-KOTE antifouling paint is the top of the range epoxy ester, copper antifouling. ULTRA-KOTE is tin-free. Designed for maximum antifouling performance, ULTRA-KOTE contains the highest copper loading in the INTERLUX line. ULTRA-KOTE is recommended for those areas of severe fouling or where pollution or agricultural run-off increase the rate of fouling. ULTRA-KOTE has the added benefit of excellent colour homogeneity and stability, previously unmatched by ultra high load copper antifouling.

SURFACE PREPARATION: Surface must always be clean and properly prepared prior to painting. All sanded surfaces must be wiped clean with 216 INTERLUX SPECIAL THINNER to remove sanding residue.

GENERAL APPLICATION: For use on fiberglass, wood or properly primed steel or lead. Apply at least two full coats with brush or roller.

MIXING AND THINNING: Shake or mix well. Stir continuously while using. For brush or roller use, thin if necessary with 333 INTERLUX BRUSHING LIQUID. For use on bare wood, thin 15% with 216 INTERLUX SPECIAL THINNER.

THEORETICAL COVERAGE: 8.58 square metres/litre

CLEAN-UP: 216 INTERLUX SPECIAL THINNER

ESTIMATED DRY TIMES: ULTRA-KOTE may be overcoated with itself after an overnight dry. Prior to launch, allow an overnight dry. Maximum time to launch is 60 days.

APPLICATION SYSTEMS

PREVIOUSLY PAINTED SURFACES: Copolymer, vinyl and hard epoxy antifouling are the only suitable paints for overcoating with ULTRA-KOTE. It is important that these paints be in excellent condition to allow overcoating. Wash entire surface with 216 INTERLUX SPECIAL THINNER. Repeat application. Sand entire surface well with 80 grit sandpaper to a clean firmly attached surface. If a soft conventional antifouling paint is present, it must be removed. If there are excessive coats of old vinyl or hard epoxy antifouling on the surface to be painted, or weakness between or under these old coats, the “pulling” effect of ULTRA-KOTE may cause detachment. To prevent this from occurring, the excessive paint should be removed.

BARE FIBERGLASS - NO SAND METHOD:

Wash entire surface thoroughly with INTERLUX FIBERGLASS SOLVENT WASH 202 changing rags frequently. Before liquid dries, wipe clean with a dry cloth. (Be sure all wax and other contaminants are removed.) Failure to properly clean the surface will

result in paint delamination. Sand any imperfections and repair with INTERLUX EPOXY SURFACING & FAIRING COMPOUND 417A/418B; sand and wipe clean. Apply one thin continuous coat of INTERLUX AL200 FIBERGLASS PRIMER with brush or roller. Do not spray; do not sand. Allow to cure between 2 hours but no more than 3 hours. Apply first coat of ULTRA-KOTE and allow to dry overnight. Apply at least one more coat of ULTRA-KOTE allowing proper dry times.

BARE FIBERGLASS - SANDING METHOD:

Wash entire surface thoroughly with 202 FIBERGLASS SOLVENT WASH, changing rags frequently. Repeat application to ensure wax-free and mold-free surface. Repair scratches and dents with 417A/418B EPOXY SURFACING & FAIRING COMPOUND. Sand entire surface with 80 grit production sandpaper until a dull, matte appearance is obtained, wipe clean. Apply two coats of ULTRA-KOTE, allowing sufficient drying time.

BARE WOOD:

Sand well with 80-grit production sandpaper; wipe surface clean. Apply first coat of ULTRA-KOTE after it has been thinned with 216 INTERLUX SPECIAL THINNER. Apply second coat (do not thin unless necessary) after an overnight dry.

ALUMINUM AND STEEL:

Please contact the INTERLUX Technical Sales Department at 1-800-468-7589 for full details on how to apply to steel and aluminum.

DO NOT place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

NOTICE TO USER: This control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by spillage, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Do not re-use container for any purpose. Dispose of empty container and paint debris in accordance with provincial requirements. For information on the disposal of unused, unwanted product, and the clean-up of spills, contact the manufacturer or the Provincial Regulatory Agency.

PRECAUTIONS: Keep away from heat, sparks and flame. Vapours heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical

resistant gloves, goggles and footwear, and chemical resistant clothing including hood or hat at all times during handling and application.

- KEEP OUT OF REACH OF CHILDREN - Handle with care and mix carefully - When using, do not eat, drink or smoke - Take a shower immediately after work - Wear freshly laundered clothes daily - Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet - Store and wash all protective clothing separately from household laundry - Wash protective clothing in detergent and hot water before reuse - Use only in well ventilated areas.

FIRST AID: IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice. IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice. IF SWALLOWED: Call a poison control centre or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give anything by mouth to an unconscious person. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion. Treat symptomatically.

EPA EST. NO. 2693-NJ-1

NOT REGISTERED FOR USE IN THE UNITED STATES OF AMERICA