

2024-0649
2024-02-20

ANTIFOULING
SEAFORCE 200 AV

(Various Colors)

ANTIFOULING PAINT

SUSPENSION

GUARANTEE

CUPROUS OXIDE 45.53%

COMMERCIAL

DANGER SKIN IRRITANT- EYE IRRITANT
POISON
FLAMMABLE

READ THE LABEL BEFORE USING.
ONLY FOR USE ON BOATS OR SHIPS.

REGISTRATION NO. 25788 PEST CONTROL PRODUCT ACT

JOTUN PAINTS INC.

16223 Park Row Dr., Suite 120
Houston, TX 77084
MEDICAL EMERGENCY NUMBER 1-800-424-9300

GENERAL INQUIRIES 1-504-394-3538

NET CONTENT:

NOTICE TO USER

THIS PEST CONTROL PRODUCT IS TO BE USED ONLY IN ACCORDANCE WITH THE DIRECTIONS ON THE LABEL. IT IS AN OFFENCE UNDER THE *PEST CONTROL PRODUCTS ACT* TO USE THIS PRODUCT IN A WAY THAT IS INCONSISTENT WITH THE DIRECTIONS ON THE LABEL. THE USER ASSUMES THE RISK TO PERSONS OR PROPERTY THAT ARRISES FROM ANY SUCH USE OF THIS PRODUCT.

STORAGE

DO NOT CONTAMINATE WATER, FOOD OR FEED BY STORAGE OR DISPOSAL. KEEP CONTAINER CLOSED WHEN NOT IN USE.

DISPOSAL

- 1...FOLLOW PROVINCIAL INSTRUCTIONS FOR ANY REQUIRED ADDITIONAL CLEANING OF THE CONTAINER PRIOR TO ITS DISPOSAL.
- 2...MAKE THE EMPTY CONTAINER UNSUITABLE FOR FURTHER USE.
- 3...DISPOSE OF THE CONTAINER IN ACCORDANCE WITH PROVINCIAL REQUIREMENTS.
- 4...FOR INFORMATION ON THE DISPOSAL OF UNUSED, UNWANTED PRODUCT, CONTACT THE MANUFACTURER OR THE PROVINCIAL REGULATORY AGENCY. CONTACT THE MANUFACTURER AND THE PROVINCIAL REGULATORY AGENCY IN CASE OF A SPILL, AND FOR CLEAN-UP OF SPILLS.

Health 3

Fire hazard 3

Reactivity 1

Protective Equipment X

THE VOC OF THIS PAINT IS 330 GRAMS/LITER (2.75 LBS./GAL.)

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH THE SKIN.

USE AN AIR-FED RESPIRATOR WITH A FULL FACE MASK DURING HANDLING AND APPLYING.

REMOVE PERSONAL PROTECTIVE EQUIPMENT IMMEDIATELY AFTER HANDLING THIS PRODUCT. AS SOON AS POSSIBLE WASH THOROUGHLY AND CHANGE INTO CLEAN CLOTHING.

REMOVE CLOTHING/PERSONAL PROTECTIVE EQUIPMENT IMMEDIATELY IF PESTICIDE GETS INSIDE. THEN WASH THOROUGHLY AND PUT ON CLEAN CLOTHING.

DISCARD CLOTHING AND OTHER ABSORBENT MATERIAL THAT HAVE BEEN DRENCHED OR HEAVILY CONTAMINATED WITH THE PRODUCT'S CONCENTRATE. DO NOT REUSE THEM.

FOR CLEANING/MAINTAINING PERSONAL PROTECTIVE EQUIPMENT, USE DETERGENT AND HOT WATER BEFORE RE-USE.

STORE AND WASH ALL CLOTHING SEPARATELY FROM HOUSEHOLD LAUNDRY. WHEN USING, DO NOT EAT, DRINK, OR SMOKE.

WASH HANDS AND FACE BEFORE EATING, DRINKING, CHEWING GUM USING TOBACCO OR USING THE TOILET.

WASH THE OUTSIDE OF GLOVES BEFORE REMOVING.

WEAR LONG PANTS, A LONG-SLEEVED SHIRT AND SHOES PLUS SOCKS DURING MIXING, LOADING APPLICATION, CLEAN-UP AND REPAIR.

WEAR CHEMICAL RESISTANT GLOVES AND FOOTWEAR AND CHEMICAL RESISTANT CLOTHING WITH HEAD COVERING AT ALL TIMES DURING HANDLING AND APPLYING.

USE ONLY IN WELL VENTILATED AREAS.

HANDLE WITH CARE AND MIX ONLY IN A CLOSED CONTAINER.

ENVIRONMENTAL HAZARDS

TOXIC TO AQUATIC ORGANISMS. DO NOT CONTAMINATE WATER. DO NOT APPLY DIRECTLY TO WATER BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES. DO NOT ALLOW CHIPS AND DUST GENERATED DURING PAINT REMOVAL TO ENTER WATER.

PHYSICAL OR CHEMICAL HAZARDS

FLAMMABLE. KEEP AWAY FROM HEAT AND OPEN FLAME.

FIRST AID

IF SWALLOWED: CALL A POISON CONTROL CENTRE OR DOCTOR IMMEDIATELY FOR TREATMENT ADVICE. DO NOT INDUCE VOMITING UNLESS TOLD TO DO SO BY A POISON CONTROL CENTRE OR DOCTOR. DO NOT GIVE ANY LIQUID TO THE PERSON. DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

IF ON SKIN OR CLOTHING: TAKE OFF CONTAMINATED CLOTHING. RINSE SKIN IMMEDIATELY WITH PLENTY OF WATER FOR 15-20 MINUTES. CALL A POISON CONTROL CENTRE OR DOCTOR FOR TREATMENT ADVICE.

IF INHALED: MOVE PERSON TO FRESH AIR. IF PERSON IS NOT BREATHING, CALL 911 OR AN AMBULANCE, THEN GIVE ARTIFICIAL RESPIRATION, PREFERABLY BY MOUTH-TO-MOUTH, IF POSSIBLE. CALL A POISON CONTROL CENTRE OR DOCTOR FOR TREATMENT ADVICE.

IF IN EYES: HOLD EYE OPEN AND RINSE SLOWLY AND GENTLY WITH WATER FOR 15-20 MINUTES. REMOVE CONTACT LENSES, IF PRESENT, AFTER THE FIRST 5 MINUTES, THEN CONTINUE RINSING EYE. FLUSH WITH PLENTY OF WATER. CALL A POISON CONTROL CENTRE OR DOCTOR FOR TREATMENT ADVICE.

TAKE CONTAINER, LABEL OR PRODUCT NAME AND PEST CONTROL PRODUCT REGISTRATION NUMBER WITH YOU WHEN SEEKING MEDICAL ATTENTION.

TOXICOLOGICAL INFORMATION

THIS PRODUCT CONTAINS PETROLEUM DISTILLATES. VOMITING MAY CAUSE ASPIRATION PNEUMONIA. TREAT SYMPTOMATICALLY.

DIRECTIONS FOR USE

ANTI-FOULING FOR METAL BOTTOMS

TO CONTROL THE ATTACHMENT OF MARINE FOULING, IE., BARNACLES, GRASS, ALGAE, ETC. ON SHIP BOTTOMS IN SALT AND BRACKISH WATER WHICH WOULD SUSTAIN SUCH GROWTH. NOT RECOMMENDED FOR USE ON ALUMINUM. A MINIMUM OF TWO COATS IS RECOMMENDED FOR BEST PERFORMANCE.

SURFACE PREPARATION

BEFORE APPLICATION OF ANTI-FOULING, ALL SURFACES MUST BE DRY AND CLEANED OF DIRT, DUST, OIL, RUST, LOOSE PAINT, SALT RESIDUES AND OTHER CONTAMINANTS. STEEL MUST BE COATED WITH A SUITABLE PRIMER OR ANTI-CORROSIVE BARRIER COAT.

MIXING

BEFORE USE POWER MIX OR BOX THE PAINT UNTIL THE PRODUCT IS UNIFORM. STIR THE PAINT AT INTERVALS DURING APPLICATION TO MAINTAIN UNIFORMITY.

APPLICATION

APPLY BY BRUSH, ROLL OR SPRAY. CONTENTS MAY BE APPLIED BY HOT SPRAY (TEMPERATURES NOT TO EXCEED 35 C). AIRLESS SPRAY OR REGULAR COLD SPRAY. APPLY A FULL WET COAT IN A DOUBLE CROSSHATCH PATTERN. DO NOT PAINT IN COLD OR DAMP WEATHER.

THINNING

NORMALLY NO THINNING REQUIRED. WHERE THINNING IS NECESSARY, USE THINNER 092207, XYLENE.

DRYING TIME

AT 21°C AND 50% R.H. ALLOW AT LEAST 4 HOURS DRY TIME BETWEEN COATS, AND A MINIMUM OF 8 HOURS BEFORE INTRODUCTION INTO WATER.

LARGE VESSELS (I.E. OVER 25M) MUST BE TREATED BY TRAINED APPLICATORS.

GENERAL

DO NOT APPLY THIS PRODUCT IN A WAY THAT WILL CONTACT WORKERS OR BYSTANDERS, EITHER DIRECTLY OR THROUGH DRIFT. ONLY PROTECTED HANDLERS MAY BE IN THE AREA DURING APPLICATION.

DO NOT CONTAMINATE IRRIGATION OR DRINKING WATER SUPPLIES OR AQUATIC HABITATS BY CLEANING OF EQUIPMENT OR DISPOSAL OF WASTES.

DO NOT APPLY THIS PRODUCT DIRECTLY TO FRESHWATER HABITATS (SUCH AS LAKES, RIVERS, SLOUGHS, PONDS, PRARIE POTHOLE, CREEKS, MARSHES, STREAMS, RESERVOIRS AND WETLANDS), OR ESTUARINE/MARINE HABITATS.

DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT OR THE BIOCIDES PRODUCED INTO SEWER SYSTEMS, LAKES, STREAMS, PONDS, ESTUARIES, OCEANS OR OTHER WATERS UNLESS THE EFFLUENT HAS BEEN DETOXIFIED BY SUITABLE MEANS.

DO NOT PLACE THE PAINTED PARTS IN WATER AFTER PAINTING UNTIL THE PAINT IS FULLY CURED (SEE RECOMMENDED TIMES ON THE LABEL). IT IS RECOMMENDED THAT YOU PREVENT PAINT CHIPS OR DUST CAUSED BY REMOVING PAINT FROM ENTERING THE WATER.