

2018-0706  
2018-10-10

## **Kop-Coat, Inc.**

### **Timbertreat® C**

Broad Spectrum Fungicide for Solvent and Water Based Systems

Registrant No. 27252  
Pest Control Products Act

Danger

**ACTIVE INGREDIENT:**

3-Iodo-2-Propynybutyl Carbamate.....20%

**READ THE LABEL BEFORE USING  
SOLD FOR INDUSTRIAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN**

**Manufactured for:**

Kop-Coat, Inc.

Protection Products Division  
5137 Southwest Avenue,  
St. Louis, MO 63110 USA  
1-800-548-0489

Kop-Coat Inc.  
3040 William Pitt Way  
Pittsburgh, PA 15238 USA  
412-826-3323

Net Contents

Liters

2018-0706  
2018-10-10

## DIRECTIONS FOR USE

The use level for Timbertreat<sup>®</sup> C as a fungicide may vary according to the individual composition and end-use pattern of the final system. All recommendations are in percentage by weight and refer to the product Timbertreat<sup>®</sup> C.

<u>Application</u>	<u>Wt. % of Timbertreat<sup>®</sup> C</u>
Millwork	1.5 – 2.5

### **\*Suggested concentration level of ingredient in the diluted composition**

Timbertreat<sup>®</sup> C offers broad spectrum protection against wood destroying fungi, mildew, and blue stain.

**Millwork:** Use rates up to 2.5%. Timbertreat<sup>®</sup> C is suggested for use on wood joinery products including window and door components or exterior non-structural decorative wood joinery items, which are not in, ground contact. Do not use on wood products, which may come in contact with food, feed, or drinking water. Machine, cut, glue, and sand wood as desired prior to treating. Do not apply over previously finished or stained wood. Wood must be clean and dry. Engineered ventilation systems may be required to remove solvent vapours during treatment, mixing or drying.

### **Apply this product by the following methods:**

- Double vacuum system (closed System). Wood should be dry to the touch upon removal from the treating chamber. Use a treating schedule, which achieves adequate distribution of the active to meet market standards or customer specifications.
- Bundle dipping or other immersion methods, which utilize automated technology (3 minute minimum treatment).
- Flood coating, roller coating or for coating using automated technology (15 second minimum treatment).
- Spray box automated technology (treating parameters appropriate for the specific unit substrate).

**Finishing:** Prior to top coating with paint, varnish, or other material, the wood must be free of residual solvent. Allow four to eight hours under ambient temperature, 20°C, or less drying time if accelerated drying methods are used.

Timbertreat<sup>®</sup> C may be added to either solvent or water. It should be added at the end of the formulation process at a level of 1.5 to 2.5% based on the weight of the final solution Field trials are suggested as a means of determining the appropriate level to achieve protection.

## STORAGE AND DISPOSAL

**STORAGE:** Do not store below 16°C, optimum storage temperature of 16°C to 32°C is recommended. Store drums in a tightly closed and upright position. Do not reuse empty drums. See MSDS for complete safety and handling information. Do not use, pour, spill, or store near heat or open flame.

### **DISPOSAL:**

- Triple-or pressure-rinse the empty container. Add the rinsings to the mixture in the tank
- Follow provincial instructions for any required additional cleaning of the container prior to its disposal
- Make the empty container unsuitable for further use.
- Dispose of the container in accordance with provincial requirements.
- For information on the disposal of unused, unwanted product and contact the manufacturer or provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean up of spills.

## PRECAUTIONS

### **DANGER**

Corrosive to eyes and skin. Do not get in eyes, on skin, or on clothing. In case of contact, immediately flush eyes or skin or skin with plenty of water. Get medical attention if irritation persists. May be fatal if inhaled. Do not inhale vapors or mist. When handling the concentrate, wear a full-face protection with cartridge respirator and chemical resistant gloves, apron, cap and boots. Use only in well ventilated areas. Do not wear contact lenses. Do not use, pour, spill, or store near heat or open flame.

2018-0706  
2018-10-10

Wear chemical-resistant coveralls over long-sleeved shirt and long pants, chemical-resistant gloves, goggles or face shield, socks and chemical-resistant footwear when handling the concentrate or during mixing/loading, clean-up, maintenance and repair activities.

Use a NIOSH-respirator if the area is not well ventilated or if airborne exposure levels are above the occupational exposure limit(s), as determined by air sampling.

Use a NIOSH-respirator during clean-up, maintenance and repair activities when working in/on application equipment or if airborne material (e.g. dust, mist/spray) may be generated when working in the treatment area.

When piling freshly treated lumber, handling treated lumber that has not fully dried, or if there is a potential for getting wet by the treating solution during other activities in the sawmill, wear chemical-resistant coveralls or a chemical-resistant apron over long-sleeved shirt and long pants, chemical-resistant gloves, socks and chemical-resistant footwear.

When working in the dip or spray area, wear long-sleeved shirt, long pants, chemical-resistant gloves, socks and boots. Wear goggles or face shield if there is a possibility of splashing.

Once dry, the treated wood can be handled with cotton or leather gloves.

Wash hands and face before eating, drinking, smoking and using the toilet. Change clothes daily. Wash contaminated clothing separately from household laundry. Not for use or storage in or around the home. Clean contaminated equipment thoroughly prior to making welding repairs.

#### **FIRST AID**

**IF SWALLOWED:** Call a poison centre or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison centre or doctor for treatment advice.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment.

**Medical Emergencies:** 1-800-548-0489

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

**TOXICOLOGICAL INFORMATION:** Probable mucosal damage may contraindicate the use of gastric lavage. Treat symptomatically.

#### **I. ENVIRONMENTAL PRECAUTIONS**

TOXIC to aquatic organisms.

#### **II. DIRECTIONS FOR USE:**

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

This product is TOXIC to aquatic organisms. It is not to be used in circumstances that would cause or allow it to enter lakes, streams, ponds, estuaries, oceans or other waters in contravention of federal or provincial regulatory requirements. The requirements of applicable laws should be determined before using the product.

Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of treatment solution.

Store treated lumber on a roofed drip pad until dripping has ceased. Slope lumber on the drip pad to expedite drainage and to ensure that no puddles remain on the surface of the wood. Manage drippage and other related wastes to prevent release in the environment.

DO NOT expose treated lumber to rains immediately after treatment.

2018-0706  
2018-10-10

For further information on storage, handling, and disposal of treated wood, contact the manufacturer of this product or the provincial regulatory agency.

### **III. STORAGE:**

To prevent contamination store this product away from food or feed.

### **IV. DISPOSAL:**

For recyclable containers:

DO NOT reuse this container for any other purpose. This is a recyclable container, and is to be disposed of at a container collection site. Contact your local distributor/dealer or municipality for the location of the nearest collection site. Before taking the container to the collection site:

1. Triple-or pressure-rinse the empty container. Dispose of the rinsings in accordance with provincial requirements.
2. Make the empty, rinsed container unsuitable for further use.

If there is no container collection site in your area, dispose of the container in accordance with provincial requirements.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of waters. Apply this product only as specified on this label.

**NOTICE TO USER:** This control product is to be used only in accordance with the directions of this label. It is an offense under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label.