SIGMA COATINGS

RED BROWN

5297 HS SIGMAPLANE ECOL ANTIFOULING PAINT

SUSPENSION

COMMERCIAL MARINE READ THE ENTIRE LABEL BEFORE USING

GUARANTEE: COPPER PRESENT AS CUPROUS OXIDE . . . 37.0% Warning, contains the allergens soy and tree nuts (cashew). REGISTRATION NO. 27522 PEST CONTROL PRODUCTS ACT

DANGER

Poison symbol here Corrosive symbol here

FLAMMABLE EYE IRRITANT SKIN IRRITANT

POISON CORROSIVE

KEEP OUT OF REACH OF CHILDREN

FOR SPRAY APPLICATION ONLY (ROLL OR BRUSH FOR TOUCH UP ONLY)

NET CONTENTS 18.9 LITRES

SIGMAKALON USA, LLC SUITE 255 1700 WEST LOOP SOUTH HOUSTON TX 77027UNITED STATES In case of emergency, call toll-free 1-800-424-9300.

PRECAUTIONS

Danger - Corrosive. DO NOT ingest, inhale, get in eyes or on skin. Contains crystalline silica, which can cause cancer. Risk of cancer depends on duration and level of exposure.

- Wear an air-fed respirator with a full face mask during handling and applying. Wear
 chemical resistant gloves, and footwear, and chemical resistant clothing with head
 covering at all times during handling and applying.
- Wear long pants, a long-sleeved shirt and shoes plus socks during mixing/loading, application, clean-up and repair.
- KEEP OUT OF REACH OF CHILDREN.
- Handle with care and mix only in a closed container.
- Use only in well ventilated areas.
- When using do not eat, drink, or smoke.
- Remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.
- Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them.
- For cleaning/maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry. Wash protective clothing in detergent and hot water before reuse.
- Take a shower immediately after work.
- Wear freshly laundered clothes daily.
- Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

FIRST AID

If splashed in eyes, hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. If on skin or clothing, take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice. If swallowed, call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person. If inhaled, move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

Take container, label or product name, and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION

Contains petroleum distillates. Do not induce vomiting. Treat symptomatically.

ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DIRECTIONS FOR USE

This product is offered for sale and use only to PROFESSIONALLY TRAINED INDUSTRIAL PERSONNEL.

Do not apply to aluminum hulls and outdrives.

Discolouration of the antifouling paint may occur at the waterline.

DO NOT apply this product in a way that will contact workers or bystanders, either directly or through drift. Only protected handlers may be in the area during application.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats.

For use on metal and fibreglass boat hulls to control the growth of fouling organisms. Controls common types of fouling for a period up to 3 years depending on sailing pattern, water temperature, and the system applied.

Before using, power agitate to a uniform consistency. Bare steel surfaces should be blasted before the application of the primer. Surfaces must be suitably prepared and primed before application of 5297HS Sigmaplane Ecol Antifouling Paint. Do not apply below 2°C (36°F) unless care is taken to ensure absence of frost or ice. Surfaces to be painted shall be free of dirt, oil, grease, and other surface contaminants. Product must be allowed to dry at least 8 hours before immersion. Large vessels over 25 metres must be treated by trained applicators.

Dry Dock Interval	No. of Coats	Dry Film Thickness (DFT)
		per Coat
Up to 30 months	2	125 μm (5.0 mils)
Up to 36 months	2	150 μm (6.0 mils)

Basic Data at 20°C (68°F):

Touch Dry after 1 hour

Overcoating interval minimum 6 hours
Overcoating interval maximum 6 months

Minimum interval before launching 8 hours

Shelf Life (cool and dry place) subject to reinspection after 6 months

Flash Point (T.C.C) 31°C (87°F)

DISPOSAL

Dispose of empty containers and paint debris in accordance with provincial requirements. Triple or pressure-rinse the empty container. Add the rinsings to the treatment site. Make the empty container unsuitable for further use. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill and for clean-up of spills.

NOTICE TO USER: This pest control product is to be used only in accordance with the directions on the label. It is an offence under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.