CuRAP[®]20 PAK

WOOD PRESERVATIVE WRAP

COMMERCIAL

For use ONLY as a groundline remedial treatment for exterior industrial wood products. For Exterior Industrial use only. Not for use in dwellings. Harmful or fatal if swallowed.

KEEP OUT OF REACH OF CHILDREN.

DANGER





DANGER CORROSIVE TO SKIN AND EYES

CHEMICAL BURNS AND BLINDNESS MAY RESULT FROM EYE CONTACT

POTENTIAL SKIN SENSITIZER

READ THE LABEL BEFORE USING

GUARANTEE:

Warning, contains the allergen soy.

REGISTRATION NO. 27026

PEST CONTROL PRODUCTS ACT NET

CONTENTS:

Bandages:

_ 2.88 kg (53 x 69cm) _ 4.38 kg (53 x 104 cm) __3.63 kg (53 x 86 cm) 5.12 kg (53 x 122 cm)

Genics Inc. 27717 Acheson Road Acheson, AB T7X 6B1 780-962-1000

STORAGE:

Store away from food/feed in a secure, well-ventilated area protected from extreme temperatures. Do not allow to freeze. Do not transfer to unmarked containers. Keep container closed when not in use.

DISPOSAL:

- 1. Dispose of outer cardboard box according to provincial requirements.
- 2. Follow provincial instruction for any required additional cleaning of the container prior to its disposal.
- 3. Make the empty container unsuitable for further use.
- 4. Dispose of the container in accordance with provincial requirements.
- 5. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

FOR PRODUCT EMERGENCIES: CHEMTREC - 800/424-9300

NOTICE TO USER: This pest control product is to be used only in accordance with the directions on he label. It is an offence under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

PRODUCT LIMITATIONS: For use ONLY in the exterior remedial groundline treatment of:

1. Utility Poles & Land Pilings (The owners of utility poles must be consulted before treatment can be initiated.)

2. Outdoor Wooden Structures

TREATED WOOD LIMITATIONS:

CuRap 20 Wood Preservative should be used only for treatment of wood having NO OPPORTUNITIES FOR:

- 1. Direct contact with, or becoming a deleterious component of drinking water.
- 2. Use in a) residential construction
 - b) food/feed storage/production or animal housing
 - c) playground equipment
- 3. Prolonged skin contact

DIRECTIONS FOR USE:

Post a copy of this label at the treating site, or mobile treatment vehicle.

DO NOT apply this product to wood that will be used in water.

DO NOT discharge effluent containing this product into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

PREPARATION: Clean and inspect the wood prior to treatment. This product is a pre-manufactured bandage and is intended for use as a remedial treatment for wooden utility poles, power poles and remedial treatment for wood structures susceptible to attack by decay and soft rot fungi, carpenter ants, or wood boring beetles. This product assists in controlling termite infestations.

For utility poles, pilings, posts or other wooden structures standing in the ground, excavate the soil away from the structure to a depth of about 42 centimeters. Wire brush the surfa ce to remove adhering soil and remove any damaged wood. The structure should be inspected for internal decay and insect attack by ta king increment borings. Remedial t reatment of sampling a reas prior to plugging is advisable. Measures to prevent the inoculation and spread of decay organisms from inspection instruments to pole or soil to pole via the inspection procedure are necessary.

Bandages may be applied to cover groundline areas of structures in bands typically 45 centimeters to 58 centimeters in height. This product should be applied to at least cover the wood surface 10 centimeters below the last evidence of decay and 8 centimeters above the groundlin e. More than one bandage may be u sed in special cases wh ere the structure spans a height greater than 56 centimeters, such as on hillsides. After application of the bandage, wrap top of bandage with 7.7 cm reinforced tape, allowing tape to overlap, and staple or nail into place. Backfill and tamp dirt firmly, mounding within 2.6 cm of bandage top. Do not backfill above top edge of pak.

The above ground portion of the treated area must be protected by suitable mechanical means to prevent damage to the bandage and/or access to the preservative by pets, farm animals, and people.

EFFICACY: The effectiveness of remedial treatments with this product will be dependent on a number of parameters, including condition of the wood when treated, wood species, type of decay hazard, workmanship, and previous and subsequent treatments.

Assuming poles, land pilings, posts or other w ooden structures are in undistributed condition, reapplication is only necessary every 10 - 15 years depending on soil and climatic conditions.

PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage and skin burns. Potential skin sensitizer. May be harmful or fatal if swallowed, inhaled or absorbed through the skin. Do not breathe vapour. Do not get in eyes, on skin or on clothing. Wash thoroughly with soap and water after skin contact and before eating, drinking, use of tobacco products or using restrooms. Do not carry, store or consume food or drink in areas where this product is stored or used, or where freshly treated wood is stored. Do not carry or smoke cigarettes in working areas. Do not expose cuts or abrasions to this product. Get immediate first aid if eyes contact this product. Keep work area well ventilated. Keep away frm open flames. A portable eye wash and wash up facility must be available at the use site.

OPERATORFUNCTION	PROTECTIVEREGIME
 I Operations carried on that entail opportunity for direct contact with this product, e.g. a. Application of the product b. Cleaning maintenance activities c. Transferring product to application equipment 	Coveralls over long-sleeved shirt and long pants, protective eyewear (ie: chemical goggles or face shield), chemical resistant gauntlets (long sleeve gloves), chemical resistant apron, head gear and chemical resistant boots. In addition, a respirator is required for workers applying copper products by brush.
II Operations involving storage and handling of sealed product.	Coveralls, chemical resistant gloves and chemical resistant boots.

SAFETYEQUIPMENT

USE PROTECTIVE CLOTHING MADE FROM THE FOLLOWING MATERIALS:

Viton, Neoprene, Polyvinyl chloride. Launder work clothing separately from other household clothing. Replace any defective, worn or contaminated protective equipment immediately.

TOXICOLOGICAL INFORMATION

Chemical burns and blindness may result from eye contact. Chemical burns can result from prolonged skin contact. Contains monoethanolamine.

ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms.

FIRST AID

EYE CONTACT: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

IF IN CONTACT WITH SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

INHALATION: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to mouth, if possible. Call a poison control centre or doctor for further treatment advice.

INGESTION: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centreor doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.