

Model label: Replacement cell for chlorine generating devices:

Krystal Clear Saltwater System™ model Eco7111

Replacement cell for the chlorine generating device Krystal Clear Saltwater System™ model Eco7111

REGISTRATION NUMBER 31004, *PEST CONTROL PRODUCTS ACT*.

This cell must only be used on this model of chlorine generating device.

READ THE LABEL, THE INSTALLATION MANUAL AND OPERATION MANUAL OF THE CHLORINE GENERATING DEVICE KRYSTAL CLEAR SALTWATER SYSTEM™ MODEL ECO7111 BEFORE USING.

Registrant: Intex Development Co. Ltd., 9th floor Everbright Center, 108 Gloucester Road, Wanchai, Hong Kong

Canadian Agent: INTEX RECREATION CORP., 1665 Hughes Way, Long Beach, CA 90810 Phone: 1-800-234-6839

Model label: Chlorine generating devices:

Krystal Clear Saltwater System™ model Eco7111

CHLORINE GENERATOR

CONTROLS BACTERIA AND ALGAE

In
Swimming Pool Waters

DOMESTIC

A maximum of 26 000 L of water can be treated with one
Krystal Clear Saltwater System™ model Eco7111 unit.
Maximum output of hypochlorous acid equivalent to 0.125 kg of free available
chlorine per day

For swimming pools, a range of 1-3 ppm of free available chlorine must be
maintained.

READ THE LABEL AND OPERATING MANUAL BEFORE USING
KEEP OUT OF REACH OF CHILDREN

REGISTRATION NO.31004 *PEST CONTROL PRODUCT ACT*

WARNING: operating Krystal Clear Saltwater System™ model Eco7111 without
water flow through the cell can cause a build-up of flammable gases which can result
in FIRE OR EXPLOSION.

Registrant: Intex Development Co. Ltd., 9th floor Everbright Center, 108
Gloucester Road, Wanchai, Hong Kong
Canadian Agent: INTEX RECREATION CORP., 1665 Hughes Way, Long Beach,
CA 90810 Phone: 1-800-234-6839

**KRYSTAL CLEAR SALTWATER SYSTEM™MODEL ECO7111
WITH E.C.O. (ELECTROCATALYTIC OXIDATION)**

**110 – 120 V~, 60 Hz, 2.1 A THERMALLY PROTECTED,
WEATHERPROOF ENCLOSURE, CSA ENCLOSURE 3,
FOR USE WITH SWIMMING POOLS ONLY.**

WARNING

**RISK OF ELECTRIC SHOCK.
CONNECT ONLY TO A GROUNDING TYPE RECEPTACLE
PROTECTED BY A CLASS A GROUND FAULT CIRCUIT INTERRUPTER (GFCI).**

CAUTION

**TO ENSURE CONTINUED PROTECTION AGAINST SHOCK HAZARD, USE ONLY
IDENTICAL REPLACEMENT PARTS WHEN SERVICING. THIS PRODUCT IS FOR
USE WITH STORABLE ABOVE-GROUND POOLS ONLY. DO NOT USE WITH
PERMANENTLY INSTALLED POOLS.**

**CONFORMS TO
UL STD. 1081
CERTIFIED TO
CSA STD. C22.2
No. 108-01**

**©2012 Intex Marketing Ltd. - Intex Development Co. Ltd. –
Intex Trading Ltd. - Intex Recreation Corp. All rights reserved.
®™ Trademarks used in some countries of the world under license
from Intex Marketing Ltd. to Intex Trading Ltd., Intex Development Co. Ltd.,
G.P.O Box 28829, Hong Kong, and Intex Recreation Corp., P.O. Box 1440, Long
Beach CA 90801. Intex Industries (Xiamen) Co., Ltd., Xiamen, Fujian, P.R.C.
Made in China**

**Canadian Agent: INTEX RECREATION CORP., 1665 Hughes Way, Long Beach,
CA 90810 Phone: 1-800-234-6839**

SALTWATER SYSTEM Model 7111

SIZE: 160mm x 135mm

KRYSTAL CLEAR SALTWATER SYSTEM MODEL ECO7111
WITH E.C.O. (ELECTROCATALYTIC OXIDATION)

CONTROLS BACTERIA AND ALGAE
In Storable Swimming Pool Waters

DOMESTIC

A maximum of 26 000 L of water can be treated with one KRYSTAL CLEAR
SALTWATER SYSTEM MODEL ECO7111
Maximum output of hypochlorous acid equivalent to 0.125 kg of
free available chlorine per day.

For swimming pools, a range of 1-3 ppm of free available chlorine
must be maintained.

READ THE LABEL AND OPERATING MANUAL BEFORE USING
KEEP OUT OF REACH OF CHILDREN

REGISTRATION NUMBER 31004 PEST CONTROL PRODUCTS ACT.

Warning: operating KRYSTAL CLEAR SALTWATER SYSTEM MODEL
ECO7111 without water flow through the cell can cause a build-up of flammable
gases which can result in FIRE OR EXPLOSION.

Warning: Straining of pool surfaces may occur due to deposits of copper salts.
Excessive levels of copper will increase the probability of this occurrence.

Registrant: Intex Development Co. Ltd., 9th floor Everbright Center, 108
Gloucester Road, Wanchai, Hong Kong
Canadian Agent: INTEX RECREATION CORP., 1665 Hughes Way, Long Beach,
CA 90810 Phone: 1-800-234-6839