

Middle/Center Panel page 1 of 2

**PLATINUM
ANTIFOULING
ABLATIVE ANTIFOULING PAINT
SUSPENSION**

NON-FLAMMABLE

**FUNGICIDE AND MARINE ANTIFOULANT
FOR INDUSTRIAL AND/OR COMMERCIAL USE**

Controls mildew on paint

Protects against algae and Marine Fouling Organisms on Antifouling Coatings

GUARANTEE

Copper – present as cuprous oxide and related copper compounds 23.6 %

COMMERCIAL

REGISTRATION NO. 32225 PEST CONTROL PRODUCTS ACT

READ THE LABEL BEFORE USING

KEEP OUT OF REACH OF CHILDREN



DANGER

**POISON
EYE IRRITANT SKIN IRRITANT
KEEP FROM FREEZING**

Net Contents: 0.95-3.78 litres (1 US quart-1 US Gallon)

Manufactured for
AMMA Marine Inc.
222 Roy St.
Saint-Eustache, QC J7R5R6
Téléphone : 450-983-2500
Télécopie : 450-983-2575

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS
READ "NOTICE TO USER" BEFORE BUYING OR USING.
IF SUCH ITEMS ARE NOT ACCEPTABLE, RETURN AT ONCE, UNOPENED.

DISPOSAL

Dispose of empty container and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the cleanup of spills, contact the Provincial Regulatory Agency or the manufacturer.

NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offence, under the *Pest Control Products Act*, to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

Right Panel – Page 1 of 2

DIRECTIONS FOR USE

This is a Cuprous Oxide pigmented coating, formulated especially to prevent the attachment of both plant and animal fouling on fiberglass, wood or rubber inflatable vessels immersed in both seawater and “brackish” water.

This coating requires a primer when used directly over fiberglass or wood. For optimum performance, two (2) coats are recommended. The theoretical coverage of this product is approximately 9.80 square meters per liter.

PREPARATION

Rubber inflatable boats

Wash the rubber boat surface with a mild detergent or cleaner, rinse and allow to dry before paint application.

Fiberglass or wood boats

To prepare the surface for coating, remove all loose coating and fouling residue by washing with high-pressure water and scraping or by disc sanding. Be sure to use the proper protective equipment to prevent inhalation or ingestion of the paint dust generated.

For use on New/Bare Fiberglass Hulls: For best adhesion: Wipe down surface with Aquagard 180 Fiberglass Solvent Wash. Change rags frequently to assure complete removal of wax and mold release agent and contaminants. Sand surface thoroughly with 80 or 100 grit sand paper. Wipe down surface with Aquagard 180 Fiberglass Solvent Wash to remove sanding residue. Apply one (1) coat of Aquagard 181 Solvent Base Primer with a roller or brush. Allow Primer to dry for a minimum of two (2) hours.

For previously painted surface:

To prepare the surface for coating, remove all loose coating and fouling residue by either washing with high pressure water and scraping or by disc sanding. If fiberglass surface is exposed, apply one (1) coat of Aquagard 181 Solvent Based Primer. Allow Primer to dry for a minimum of two (2) hours.

APPLICATION

A clean dry surface (free of scale corrosion, dirt, grease, oil, marine fouling or other foreign matter) will provide the optimum performance of this coating when used for either complete coating or for touch-up. Inadequate surface preparation will result in unsatisfactory performance. Prior to painting, be sure to remove all dust, debris and other surface contaminations that are generated by the cleaning process.

Mix the coating with either a high-speed mixer or paint shaker for a minimum of five (5) minutes to ensure complete pigment re-incorporation. To apply easily, thin with up to 5% water, in the event that coating is too thick. Clean up with water when finished.

Apply by either brush, roller or spray. Be sure to follow mixing instructions and apply the correct thickness (approximately 2 mils). Allow a minimum of twenty-four (24) hours before launching vessel.

Large vessels, i.e., over 25m, must be treated by trained applicators.

DO NOT apply this product in a way that will contact workers or bystanders, either directly or through drift. Only protected handlers may be in the area during application.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats.

DO NOT discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified by suitable means.

DO NOT place the painted parts in water painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

WARNING

USE PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN

DO NOT get in eyes, on skin or on clothing. Wear chemical resistant coveralls over long sleeved shirt and long pants, chemical resistant gloves, socks and chemical resistant footwear during mixing, loading, application, clean up and repair. Mixer/loaders and applicators must wear a NIOSH/MSHA/BHSE approved dust/mist filtering respirator. Wash the outside of gloves before removing.

DO NOT take internally.

Remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing. Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them.

For cleaning/maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry.

Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

Handle with care and mix only in a closed container.

Use only in a well ventilated area. When using, **do not** eat, drink or smoke.

Take shower immediately after work.

ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms. Do not contaminate water. Do not apply to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust (generated during paint removal) to enter water.

PHYSICAL OR CHEMICAL HAZARDS: Not combustible (waterbase)

FIRST AID

IF SWALLOWED: Call a poison control centre or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give anything by mouth to an unconscious person.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to mouth, if possible. Call a poison control centre or doctor for further treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

Take container, label or product name and Pest Control Product registration number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION:

This product may produce temporary allergic side effects characterized by redness to the eyes, mild bronchial irritation and redness or rash on exposed skin areas OR to persons having an allergic reaction to treatment with antihistamines or steroid creams and/or systemic steroids.

STORAGE

Storage: Keep from freezing.