

2023-5920
2024-02-07

PETTIT ULTIMA

ANTIFOULING PAINT

COMMERCIAL Suspension

- Economical Antifouling Protection
- Hard Smooth Finish
- Apply Over Most Other Antifouling Paints
- Excellent For Fiberglass, Wood & Steel Boats.

[1282 BLUE, 1682 RED, 1882 BLACK]

WARNING EYE AND SKIN IRRITANT READ THE LABEL BEFORE USING

ACTIVE INGREDIENT:

COPPER, PRESENT AS CUPROUS OXIDE AND RELATED COPPER COMPOUNDS 28.86%

Warning, contains the allergen soy.

REGISTRATION NO. 33294
PEST CONTROL PRODUCTS ACT

NET CONTENTS: 946 mL - 3.78 LITRES

FOR USE ON BOATS ONLY

Modern Recreational Technologies Inc.
2220 US Hwy 70 SE, Suite 100
Hickory, NC 28602

MADE IN THE U.S
1-800-221-4466

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

- Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion Hazards.
- Keep containers tightly closed when not in use. Causes skin irritation. May irritate eyes. DO NOT get on skin. Avoid contact with eyes.
- Handle with care and mix only in a closed container.
- .
- Wear chemical resistant coveralls with head covering over long pants, a long-sleeved shirt, chemical resistant gloves, socks and footwear, and full face respirator with a NIOSH-approved organic-vapour-removing cartridge with a prefilter approved for pesticides OR a NIOSH-approved canister approved for pesticides during mixing/loading, application, clean-up and repair.
- Use only in well ventilated areas.
- When using do not eat, drink or smoke.
- Take a shower immediately after work.
- Wear freshly laundered clothes daily.
- Wash hands and face before eating, drinking, smoking and using the toilet.
- Store and wash all protective clothing separately from household laundry.
- Wash protective clothing in detergent and hot water before reuse.
- Remove personal protective equipment immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing.
- Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them.
- Wash outside of gloves before reusing.

FIRST AID

IF SWALLOWED: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control centre or doctor for treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

2023-5920
2024-02-07

TOXICOLOGICAL INFORMATION Contains petroleum distillate. Do not induce vomiting. Vomiting may cause aspiration pneumonia.

NOTICE TO USER: This pest control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label.

ENVIRONMENTAL HAZARDS

TOXIC to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Triple or pressure rinse the empty container. Add the rinsings for thinner in future antifouling applications. Follow provincial instruction for any required additional cleaning of the container prior to its disposal. Make the container unsuitable for further use. Dispose of the container in accordance with provincial requirements. Canadian manufacturers should dispose of unwanted active ingredients and containers in accordance with municipal or provincial regulations. For additional details and clean-up of spills, contact the manufacturer or the provincial regulatory agency.

DIRECTIONS FOR USE

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats.

DO NOT discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified by suitable means.

DO NOT apply this product in a way that will contact workers or bystanders, either directly or through drift. Only protected handlers may be in the area during application.

DO NOT place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

PREPARATION: Scrape, wire brush or sandpaper old surfaces to remove scum, contaminants or loose paint. On bare (unpainted) fiberglass, prepare the surface with Petit Bio-Blue. Rinse well with fresh water and allow to dry. Sand vigorously until all sheen on gel coat has been removed. Use 80 grit production paper to sand. Sand bare wood with 80 grit paper and wipe clean with a rag dampened with Pettit 120 Brushing Thinner.

2023-5920
2024-02-07

PRIMING: On new or bare wood areas and on unpainted fiberglass prepared as directed above, apply first coat of this paint thinned 10%. On steel or cast iron keels, centerboards or other underwater fittings, prime these areas with 3 coats of 4700/4701 High Build Epoxy Primer, carefully following the label directions for this primer.

APPLICATION: Mix thoroughly to uniform consistency by pouring off some of top portion into a clean can – then stirring the remainder and gradually adding the portion removed. Apply generously and at full body with good bristle brush, using long even strokes or with a short nap roller. Stir occasionally during use to assure uniform suspension of toxicants in the vehicle.

NUMBER OF COATS: For initial applications, 2 coats are recommended.

DRY TIMES:	To recoat	To launch
30°C	2 hours	8 hours
20°C	4 hours	16 hours
10°C	5 hours	24 hours

above dry times are minimums. This product may be recoated after the minimum times shown and launched up to 60 days after painting.

THINNING: Reduce 10% with Pettit 120 Brushing Thinner, for brush use on bare surfaces-also for spray application. Otherwise apply this paint at full body, thinning sparingly if necessary.

COVERAGE: 37 square metres per 3.8 litres [400 square feet per gallon).

DO NOT USE THIS PRODUCT ON ALUMINUM HULLS AND OUTDRIVES MEDICAL EMERGENCIES: 1:800-548-0489

PRODUCT INFORMATION: 1-800-221-4466 or www.pettitpaint.com