

2022-0195
2022-01-20

LANXESS Corporation
PREVENTOL® IT 14 MV PRESERVATIVE
COMMERCIAL
SOLUTION

An Industrial Microbiocide for use in polymer latices, paints, coatings, inks, adhesives, building materials (caulks and sealants), metalworking fluids, fuels, wood, electrodeposition systems, papermill slimicide, industrial recirculating water cooling towers, oil field injection waters.

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one 11.81%
2-Methyl-4-isothiazolin-3-one 3.46%

KEEP OUT OF REACH OF CHILDREN

READ THE LABEL BEFORE USING

REGISTRATION NO. 34397

PEST CONTROL PRODUCTS ACT

DANGER



POISON

CORROSIVE TO EYES AND SKIN

POTENTIAL SKIN SENSITIZER

NET CONTENTS: 1 L – 1200 L

LANXESS Corporation
111 RIDC Park West Drive
Pittsburgh, PA 15275-1112
1-800-LANXESS

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Fatal or poisonous if swallowed or absorbed through the skin. Do not get on skin or clothing. May be fatal if inhaled. Avoid breathing vapors and spray mists. Corrosive to eyes and skin. Potential skin sensitizer. May cause allergic skin reaction.

Wash skin thoroughly with soap and water after handling. Remove contaminated clothing and wash separately from other laundry before reuse. Put on clean clothing. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product.

Users should remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. Follow manufacturer's instructions for cleaning/maintaining personal protective equipment. If no such instructions for washables exist, use detergent and hot water.

Wear chemical-resistant coveralls over a long-sleeved shirt, long pants, chemical-resistant gloves, socks, chemical-resistant footwear and a full-face respirator with a NIOSH-approved organic-vapour-removing cartridge with a prefilter approved for pesticides, or a NIOSH-approved canister approved for pesticides during mixing, loading, application, clean-up and repair.

ENVIRONMENTAL PRECAUTIONS

Toxic to aquatic organisms.

FIRST AID

IF SWALLOWED: Call a poison control center or doctor IMMEDIATELY for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control center or doctor for treatment advice.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION

Probable mucosal damage may contraindicate the use of gastric lavage. Treat symptomatically.

DIRECTIONS FOR USE

This registration is granted under the *Pest Control Products Act* and does not exempt the user from any other legislative requirements. Use of this product and management of any resulting discharge or release of any effluents or runoff containing this product must also be in accordance with the *Fisheries Act* and

with any other applicable federal or provincial legislation. Consult with provincial regulatory authorities on any authorizations or other requirements for use of this product and management of any resulting discharge or release of any effluents or runoff containing this product.

Use only as specified on this label.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of treatment solution. Store treated lumber on a roofed drip pad until dripping has ceased. Slope lumber on the drip pad to expedite drainage and to ensure that no puddles remain on the surface of the wood. Manage drippage and other related wastes to prevent release in the environment.

DO NOT expose treated lumber to rains immediately after treatment. DO NOT float treated lumber in lakes, rivers, streams or oceans.

PAINTS AND COATINGS

PREVENTOL® 14 MV PRESERVATIVE is recommended for the control of bacteria and fungi in water-based coatings and dispersed pigments, and for aqueous paints used for architectural purposes.

Add 42.6 to 163.7 grams of PREVENTOL® 14 MV PRESERVATIVE to each 1000 kg of emulsion to provide 6.5 to 25 ppm active isothiazolone ingredients. A higher dosage rate of up to 262 g per 1000 kg, providing up to 40 ppm active ingredients, may be required for storage during extremely high temperatures and humidity.

ADHESIVES, INKS, AND BUILDING MATERIALS

PREVENTOL® 14 MV PRESERVATIVE is also recommended as an in-container preservative in industrial products – caulks, joint cements, concrete additives, inks and slurries.

Add 42.6 to 262 grams of PREVENTOL® 14 MV PRESERVATIVE to each 1000 kg of product to provide 6.5 to 40 ppm active isothiazolones.

POLYMER LATEX EMULSIONS

PREVENTOL® 14 MV PRESERVATIVE is recommended for the control of bacteria in the manufacture and storage of synthetic and natural polymer latices – acrylics, styrene/butadiene, carboxylated styrene/butadiene, ethylene/vinyl acetate, starches and derived polymers.

Add 42.6 to 262 grams of PREVENTOL® 14 MV PRESERVATIVE to each 1000 kg of emulsion to provide 6.5 to 40 ppm active isothiazolones.

NOTE: The actual concentration of PREVENTOL® 14 MV PRESERVATIVE required will depend upon such factors as specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required. To ensure uniform mixing and in order to prevent localized shock to latex materials, it is advantageous to dilute PREVENTOL® 14 MV PRESERVATIVE ten fold with water before slowly adding to the latex with agitation as early as possible during the production process.

METAL WORKING FLUIDS

PREVENTOL® 14 MV PRESERVATIVE is recommended for soluble and emulsifiable type aqueous metalworking fluids, such as emulsified petroleum oils, and formulations containing alcoholic fatty acid, sulfonated red oil, or naphthalene sulfonate. These fluids are usually prepared by diluting the product concentrates 1:40 to 1:60 with water. For the maintenance of a nonfouled system, add 21.8 mL per 1000 L of emulsion or 21.8 mL – 41.6 mL every 8-12 weeks. For a noticeably fouled system use an initial dosage of 41.6 mL followed by a subsequent dosage depending upon the treatment level above. A higher dosage range and/or increased frequency of treatment may be required depending on rate of dilution of the preservative with makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

The preservative should be dispensed into the use-dilution of the metalworking fluid by a metering pump and uniformly dispersed throughout the system.

FUELS

PREVENTOL® 14 MV PRESERVATIVE is recommended for the control of bacteria and fungi in the following liquid hydrocarbon fuels and oils: liquefied petroleum gases, aviation fuels, petrochemical feedstocks, kerosene, heating oils, diesel fuels, residual fuel oils and coal slurries.

Add PREVENTOL® 14 MV PRESERVATIVE at 7.4 kilos to 22.2 kilos per 1 million kilos of total system (fuel and water) depending on degree of fouling.

FOR USE IN AVIATION FUEL, THE FEDERAL AUTHORITIES MUST BE CONSULTED AS TO THE ACCEPTABILITY OF THE ADDITIVE FOR USE IN SPECIFIC ENGINES AND/OR AIRCRAFTS.

WOOD AND WOOD PRODUCTS

PREVENTOL® 14 MV PRESERVATIVE, tank-mixed with ACQ or CCA, is recommended for the protection of wood and wood products from mould and mildew degradation.

For use with CCA solutions: Add 37.7 ml to 60.4 ml, or 49 grams to 79 grams, of PREVENTOL® 14 MV PRESERVATIVE (7.5 ppm to 12 ppm active ingredient) per 1000 litres of CCA dilute solution in the pressure treating process for mould and mildew control. Under extreme mould and mildew conditions the addition of PREVENTOL® 14 MV PRESERVATIVE may be used up to a maximum concentration of 30 ppm active ingredient (151 ml or 197 grams PREVENTOL® 14 MV PRESERVATIVE per 1000 litres).

For use with ACQ solutions: Add 25.1 ml to 101 ml, or 33 grams to 132 grams, of PREVENTOL® 14 MV PRESERVATIVE (5 ppm to 20 ppm active ingredient) per 1000 litres of ACQ dilute solution in the pressure treating process for mould and mildew control. Under extreme mould and mildew conditions the addition of PREVENTOL® 14 MV PRESERVATIVE may be used up to a maximum concentration of 30 ppm active ingredient (151 ml or 197 grams PREVENTOL® 14 MV PRESERVATIVE per 1000 litres).

Wood and/or wood product should be allowed to dry. For further information on storage, handling, use, and disposal of treated wood, contact the manufacturer of this product or the provincial regulatory agency. DO NOT apply this product to wood that will be used in water.

ELECTRODEPOSITION SYSTEMS

PREVENTOL® 14 MV PRESERVATIVE is recommended for the control of bacteria, fungi and algae in recirculating electrodeposition systems and associated rinse systems. PREVENTOL® 14 MV PRESERVATIVE should be dispensed into the circulating rinse system, ultrafilter permeate or final distilled water rinse at a point to ensure uniform mixing.

When the system is noticeably fouled, add 270 to 936 ppm PREVENTOL® 14 MV PRESERVATIVE (11.7 to 40.3 L) per 10,000 Litres of fluid in the system. Repeat until control is achieved.

When microbial control is evident, add 135 to 402 ppm PREVENTOL® 14 MV PRESERVATIVE (4.7 to 13.5 L) per 10,000 Litres of fluid in the system weekly or as needed to maintain the system. A change of frequency of treatment may be required depending upon the rate of dilution of the preservative with the makeup fluid, the nature and severity of contamination, level of control required, filtration effectiveness, system design, etc.

PAPERMILL SLIMICIDE, INDUSTRIAL RECIRCULATING WATER COOLING TOWERS AND OIL FIELD INJECTION WATERS

PULP & PAPER

PREVENTOL® 14 MV PRESERVATIVE is recommended for the control of bacterial and fungal slime in the production of paper. PREVENTOL® 14 MV PRESERVATIVE should be added at a point in the system to insure uniform mixing such as the Beater, Hydropulper Fan or Broke Storage Pump.

Add 0.02 to 0.08 kg of PREVENTOL® 14 MV PRESERVATIVE as supplied per tonne (dry basis) of pulp or paper produced, as a slug dose. If needed, repeat daily. Badly fouled systems should be cleaned before initial treatment.

COOLING TOWERS

PREVENTOL® 14 MV PRESERVATIVE is recommended for removal of slime from fouled towers. PREVENTOL® 14 MV PRESERVATIVE should be added to the basin, to the distribution boxes, or at any other point where it will be rapidly and uniformly dispersed throughout the system.

Add 0.033 to 0.92 kg of PREVENTOL® 14 MV PRESERVATIVE as supplied per 10 tonnes of water in the system. This dosage should be repeated 2 to 3 times per week until fouling has been reduced to an acceptable level.

AIR WASHER SYSTEMS

PREVENTOL® 14 MV PRESERVATIVE is recommended for the control of bacteria, fungi and algae which cause fouling in industrial air washer systems. For use only in industrial air washing systems that maintain effective mist eliminating components. Add to the air washer sump or chill water sump to ensure uniform mixing.

Add 0.42 to 1.63 kg of PREVENTOL® 14 MV PRESERVATIVE per 10,000 liters of water in the system, depending on the severity of contamination. Badly fouled systems must be cleaned before initial treatment.

OIL FIELD INJECTION WATERS

PREVENTOL® 14 MV PRESERVATIVE is recommended for the control of slime- forming bacteria and sulphate-reducing (sulphide-forming) bacteria in oil field injection waters.

Slug treat with 6 to 29 ppm of PREVENTOL® 14 MV PRESERVATIVE as supplied depending of the severity of bacterial contamination.

Add 14 to 29 ppm of PREVENTOL® 14 MV PRESERVATIVE as supplied (1.31 to 2.63 litres per 100 tonnes of water) at any point from which the material mixes uniformly throughout the system. Repeat the treatment after 3 days or as needed to achieve control.

After achieving control, add 6 to 14 ppm of PREVENTOL® 14 MV PRESERVATIVE as supplied (0.53 to 1.31 litres per 100 tonnes of water) every seven days or as needed to maintain control.

STORAGE

Store this product away from food or feed. Open dumping is prohibited. This product is corrosive to mild steel. Do not store or transport in unlined metal containers.

DISPOSAL

1. Triple- or pressure-rinse the empty container. Add the rinsings to the treatment site.
2. Follow provincial instruction for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offence under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label.