



Viny-Lux

ANTIFOULING PAINT

3.78 L

IMPORTANT
 READ THE LABEL BEFORE USING.
 FOR USE ON BOATS ONLY.
 SKIN AND EYE IRRITANT.
 NOT FOR SPRAY USE.

ONLY BRUSH OR ROLLER APPLICATION.

GUARANTEE: Cuprous Oxide 33.00%

COPPER (as elemental) 30.00%

REGISTRATION NO. 21356

PEST CONTROL PRODUCTS ACT.



DOMESTIC



340
 BLUE

International Paint Inc., 2270 Morris Avenue, Union, New Jersey 07083

INTERLUX VINY-LUX

Vinyl Based Copper Antifouling Paint

For all types of fiberglass, wood, and steel boats. Specially formulated for racing boats used extensively in areas of heavy fouling. Viny-Lux offers a hard, abrasion resistant surface and burnishes to a slick racing finish.

SURFACE PREPARATION: If previous antifouling paint is vinyl based and in good condition, wash down with fresh water, degrease with Interlux Brushing Liquid 333 if required, and use Interlux Viny-Lux as directed. Otherwise, remove all old paint mechanically and/or use Interlux Pintoff 199 or 299 as appropriate. Do not burn off. Proceed as for new work.

NEW WORK:

- **Fiberglass:** Wipe down fiberglass with Interlux Solvent Wash 202. Apply one thin coat of Interlux Fiberglass Primer AL200. Overcoat primer after an overnight cure. Apply second coat of Interlux Viny-Lux observing overcoating times. For osmosis repair and prevention, use the Interlux Interprotect System.

- **Wood:** Sand wood and wipe surface clean. Thin first coat of Interlux Viny-Lux 20% with Interlux Viny-Lux Solvent 355. Apply second coat of Interlux Viny-Lux observing overcoating times.

- **Steel, Lead:** Etch by blasting or grinding with 36 grit paper to provide a good profile. Apply 5-6 coats of Interlux Interprotect 2000E. Apply Interlux Viny-Lux after allowing InterProtect 2000E to cure for 24 hours and sanding with 80 grit production paper. Apply second coat of Interlux Viny-Lux observing overcoating times.

- **Aluminum:** Use Interlux Tri-Lux IIT.

APPLICATION: STIR THOROUGHLY. Apply by brush or roller two unthinned coats of Interlux Viny-Lux, for best results, 3 coats of Interlux Viny-Lux are recommended.

COVERAGE: 6.8 m² per litre at 50 microns d.f.t. per coat.

CLEAN-UP: Interlux Viny-Lux Solvent 355.

DRYING: Touch dry 30 minutes**.

OVERCOATING TIME: Minimum 3 hours**, recommended 8 hours**, maximum 6 months**.

IMMERSION: Minimum 4 hours**, recommended within 8 weeks**, maximum 6 months**.

**N.B.: These are guidelines only. Temperature and humidity affect cure time.

NOTICE TO USER

This control product is to be used only in accordance with the directions on the label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by spillage, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Dispose of empty containers and paint debris in accordance with provincial requirements. For information on disposal of unused or unwanted product and the cleanup of spills, contact the Provincial Regulatory Agency or the Manufacturer.

PRECAUTIONS: Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical resistant gloves, goggles and footwear, and chemical resistant clothing including hood or hat at all times during handling and application.

- Keep out of reach of children - Handle with care and mix carefully - When using, do not eat, drink or smoke - Take a shower immediately after work - Wear freshly laundered clothes daily - Wash hands and face before eating, drinking, smoking and using the toilet - Store and wash all protective clothing separately from household laundry - Wash protective clothing in detergent and hot water before reuse - Use only in well ventilated areas.

FIRST AID: EYES: Flush immediately with water for 15 minutes. See a doctor. SKIN: Wash affected areas with soap and water. If irritation persists, see a doctor. INHALATION: Remove to fresh air. Aid breathing. See a doctor at once. INGESTION: Do not induce vomiting. See a doctor at once or a poison control centre.

TOXICOLOGICAL INFORMATION: Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion.

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

Rev. 10/02

EPA EST. NO. 2693-NJ-1

NOT REGISTERED FOR USE
 IN THE UNITED STATES OF AMERICA

Interlux
 International Paint Inc.
 2270 Morris Ave., Union, NJ 07083 • 908-686-1300



This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))