

2000/2001

OSMOSE
PENTOX

CREOSOTE 50

EXTERIOR USE ONLY

WOOD PRESERVATIVE
AWPA BRUSHING GRADE

DOMESTIC - SOLUTION

GARANTEE
Creosote 49.8%

REG. NO.
17807
P.C.P. Act

READ LABEL BEFORE USING

DANGER WARNING

POISON CORROSIVE

4 1

OSMOSE PENTOX INC.
1080 PRATT AVENUE, MONTREAL, P.Q. H2V 2V2

AWPA Brushing Grade CREOSOTE is high quality creosote specially refined for brush application in accordance with Standards of the American Wood Preservers Association. It can be applied by brushing, rolling or dipping. Application in warm weather will enhance the penetration. Care must be taken to avoid inhaling the fumes. Lumber should be clean, dry and

free of bark. Treated wood has a brown colour. Not recommended for interior use because of residual odour. Not recommended for wood to be painted, but wood may usually be painted after extensive weathering. Not recommended for tents, tarpaulins, fabrics and ropes. Ready to use.

DIRECTIONS

Apply by dipping, brushing or rolling to clean dry wood free from all surface deposits such as dirt, paint, varnish, grease, etc. Dip for 1 to 3 minutes. Brush or roll 2 liberal coats. Heavy lumber requires longer dipping time. Painted, sealed or varnished wood must be stripped before application. Treat all new cuts and trims. Apply 1 litre per 6 to 8 square meters depending on the porosity of the wood. Drying time: minimum 1 hour before handling. Wood may be painted after extensive weathering. Clean equipment with mineral spirits, then with detergent and water.

PRECAUTIONS

Keep away from children, pets, livestock and foodstuffs. Do not use near open flame or spark. Protect trees, shrubs and plants during application. Creosote is toxic to plants (phytotoxic). Not recommended for greenhouses or for wood that may be in close contact with living plants. Not to be used for saunas. During application good ventilation is necessary. Avoid breathing vapour or mist. Avoid contact of solution with skin, eyes or clothing. Protective clothing is recommended. Wear gloves when applying and handling treated lumber. Harmful or fatal if swallowed. Close container or tank when not in use. Dispose of empty container safely.

FIRST AID & TOXICOLOGY

In case of skin contact, wash immediately with soap and water and remove contaminated clothing. If skin irritation occurs obtain medical attention. In case of eye contact, flush with plenty of water and obtain medical attention. If swallowed do not induce vomiting. If patient is unconscious give him air; call physician or poison control centre. Contains Creosote. Treat as for phenol poisoning.

NOTICE

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this

product and accepts the product on that condition.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))