

90.01.15

INDUSTRIAL

1.2 ECOBRITE II

(Post a copy of the label in the work area.)

ECOBRITE II:

Sapstain and mold preventative for lumber.

GUARANTEE:

Contains 10% sodium carbonate, 2% sodium borate, and 2% boric acid.

Registration No.: 21343 (Pesticides Control Products Act)

READ THIS LABEL BEFORE USING

CAUTION

SKIN & SEVERE EYE IRRITANT

KEEP OUT OF REACH OF CHILDREN

Net Content: 200 Litres

Canadian Forest Products Ltd.
2800 - 1055 Dunsmuir Street
Vancouver, B.C.
V7X 1B5

Use specified concentration in lumber production industrial dip or spray tanks in accordance with the Workers' Compensation Board of B.C.'s recommended practice -- to be used in the short term storage of spruce-pine-fir, hemlock and Douglas fir lumber.

Do not dilute this product. Apply by dip or spray thoroughly saturating lumber surfaces. Allow freshly treated lumber surface to dry in a containment area. To prevent leaching during yard storage, cover bundles with appropriate wrap.

Commercial spray box flow coater or dip tanks must be free of

leaks with provision to eliminate or contain mist overspray, drips and spillage into the surrounding environment. Not for use in drive through dip tanks.

Store away from acids and foodstuffs. Keep out of lakes, streams, and ponds. Do not contaminate water by cleaning of equipment or disposal of waste.

NOTICE TO USER: This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions. Not for use in drive-through dip tanks.

First Aid: In case of poisoning, call a physician immediately. If splashed on skin, remove contaminated clothing and wash skin thoroughly with soap and water. If splashed in eyes, flush with water for five to ten minutes and seek medical attention. If swallowed, give patient one or two glasses of water and induce vomiting by giving one dose of syrup of ipecac. Do not try to cause vomiting if the patient is unconscious or in a convulsive state.

Precautions: Use closed transfer systems and mechanical mixing and application systems. As a potential skin irritant and a severe eye irritant, avoid direct skin and eye contact and avoid inhalation of spray mist. Wear impermeable coveralls or a rain suit, eye protection, impermeable gloves and impermeable footwear when handling the concentrate or during loading, mixing or applying this product, when handling wet treated lumber or when removing chemical dust in the work place.

Disposal: Rinse the emptied container thoroughly and add the rinsings to treatment site. Follow Provincial instructions for any required additional cleaning of the container prior to its disposal or reconditioning. Dispose of the container in accordance with Provincial requirements. For information on the disposal of unused, unwanted product and the cleanup of spills, contact the regional office of the Environmental Protection Service, Environment Canada. For small spills, recover free liquid, soak up residue with solids absorbent. DO NOT FLUSH INTO SURFACE STREAMS. INFORM ENVIRONMENT CANADA. Not for use in drive-through dip tanks. Keep out of lakes, streams, and ponds. Do not contaminate water by cleaning of equipment or disposal of waste.

LIMITATION OF WARRANTY: Seller's guarantee shall be limited to the terms set out on the label and, subject thereto, the buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

Canadian Forest Products Ltd.
2800 - 1055 Dunsmuir Street
Vancouver, B.C. V7X 1B5

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))