

16-JUN-2003 Notification received of a label change. See below for this change.

1997/2002

WOLMANAC

CONCENTRATE 50%

INDUSTRIAL

WOOD PRESERVATIVE

FOR INDUSTRIAL USE ONLY

REGISTRATION NUMBER 14502 PEST CONTROL PRODUCT ACT

DANGER

POISON

CORROSIVE TO EYES AND SKIN

GUARANTEE

Active ingredients:

Chromic acid.....	23.75%
Arsenic Pentoxide.....	17.00%
Cupric Oxide.....	9.25%

NET CONTENTS: tanker truck contains less than 13,620 litres

Arsenic content as metallic is 11.1% As
 Chromium content as metallic is 12.35% Cr

READ THE LABEL BEFORE USING

Arch Wood Protection Canada Corp.

Notification Change

Registrant: ~~HICKSON BUILDING PRODUCTS LTD.~~
 2000 Argentia Road, Suite 306, Plaza 4
 Mississauga, Ont. L5N 1V9

DIRECTIONS:

Keep out of reach of children. Contents for use only in pressure-treating wood products. Cannot be used in concentrated form. DO NOT attempt to use without reading the Manual and having the necessary safety equipment. To be used only in vacuum pressure impregnation of wood products utilizing water solutions

having concentrations ranging from 1.0 percent to 5.0 percent by weight. Impregnation procedures must rigidly adhere to the current specifications of HICKSON BUILDING PRODUCTS LTD. and/or those of the Canadian Standards Association.

Pressure treatment of wood products with time-tested Wolman Preservative provides wood in all its forms with "built-in" protection against termites, ascoymycetes, white rot, brown rot and dry rot.

PRECAUTIONS:

Severe eye damage and skin burns. Rash or ulcerated skin. May be fatal if inhaled, absorbed through skin or swallowed.

Do not get on eyes, on skin, or on clothing. Wear face shield, plastic gown with long sleeves and rubber gauntlets when handling. Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g. handling freshly treated wood and manually opening cylinder doors).

In case of contact, immediately remove all contaminated clothing, including shoes and flush skin with water for at least 15 minutes.

Promptly wash skin thoroughly with soap and water after handling. For further detailed information on safety procedures, storage, handling preparation, application and disposal of CCA wood preservative refer to Environment Canada publication "CCA Wood Preservation Facilities." All plants using Wolmanac 50% CCA must have a copy of the Environment Canada Publication on site.

Individuals who enter pressure treatment cylinders and other related equipment that is contaminated with the wood treatment solution (e.g. cylinders that are in operation or are not free of the treatment solution) must wear protective clothing, including overalls, jacket, gloves and boots, impervious to the wood treatment formulation. In addition, individuals who enter pressure- treatment cylinders must wear properly fitting well maintained high efficiency filter respirators. MSHA/NIOSH approved for inorganic arsenic.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g. manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, and handling freshly treated wood).

Wash thoroughly after skin contact and before eating, drinking,

use of tobacco product or using restrooms. Protective clothing* must be changed when it shows signs of contamination. Applicators must leave protective clothing and workshoes or boots and equipment at the plant. Worn out protective clothing and workshoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with Provincial and Federal regulations.

* Example of acceptable protective clothing during application and handling of inorganic arsenicals are vinyl, polyvinyl chloride (PVC), neoprene, KBR (Buna-N) and polyethylene.

Do not store near heater or open flame, food or feed. Use with adequate ventilation. Do not contaminate water used for domestic consumption, irrigation or Fish or Wildlife.

Store concentrate in a secure area. Do not burn the treated wood. Dispose of wood by burial.

POISON

FIRST AID:

EYE CONTACT: Immediately flush with large amounts of water for at least 15 minutes. Immediately seek medical aid.

SKIN CONTACT: Immediately flush area with large amounts of water for at least 15 minutes. Remove contaminated clothing. Wash contaminated clothing before re-use. Immediately seek medical aid.

INHALATION: Remove from exposure. If breathing has stopped or is difficult, administer artificial respiration or oxygen as indicated. Seek medical aid.

INGESTION: Immediately seek medical aid. DO NOT INDUCE VOMITING. As little as 5g ingested of 50% concentrate may be fatal. Give 1 glass of milk or 30 to 60g. of activated charcoal in water to victim as tolerated. Do not attempt to give anything by mouth to an unconscious person.

SPIILLS: Limit the spread of spill and keep people away. Dike spill area with lime, cement, sand or soil. Sawdust or wood chips may be used for liquid absorption. IMPORTANT! All contaminated sawdust must be recovered and neutralized. Clean-up efforts should not begin until material is treated with lime or cement for absorption and neutralization. If feasible and without risk, repair the leaking tank to limit spill. Handle neutralized material with care. It is poisonous by skin contact or ingestion. Collect in stainless or carbon steel drums or equipment. Sweep up

or vacuum area thoroughly to remove all material. Run-off to sewers or streams may create toxic hazard; notify health and pollution control authorities. Dispose of contaminated material.

DISPOSAL:

1. Rinse the emptied container thoroughly and add the rinsings to treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal or reconditioning.
3. Dispose of the container in accordance with provincial requirements.
4. For information on the disposal of unused, unwanted product and the cleanup of spills, contact the regional office of the Environmental Protection Service, Environment Canada.
5. For small spills. Recover Free liquid. Soak up residue with solids absorbent. Do Not flush into surface streams. Inform Environment Canada as in #4.

NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

Sold by HICKSON Building Products Ltd., 2000 Argentia Rd., Ste. 306, Plaza 4, Missisauga, Ontario L5N 1V9

NOTE:

For further information on the use, and disposal of the product refer to Environment Canada Publication "CCA Wood Preservation facilities. Recommendations for Design and Operation."

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))