TIMBER SPECIALTIES K-33™(72%) WOOD PRESERVATIVE

10-OCT-2003

(For Pressure Plant Use Only)



INDUSTRIAL DANGER



POISON

CORROSIVE

READ THE LABEL BEFORE USING

REGISTRATION NO. 13707

PEST CONTROL PRODUCTS ACT

GUARANTEE:

Chromic Acid 25.40% TOTAL ARSENIC AS METALLIC 21.1%

Arsenic Pentoxide 32.50% Copper Oxide 14.10%

NET CONTENTS: 125 kg. (90 kg. Oxide Basis)

Distributed by TIMBER SPECIALTIES CO. 980 ELLICOTT STREET BUFFALO, NEW YORK 14209

DIRECTIONS FOR USE:

For use only in pressure treatment processes according to Federal standards such as CSA O80. Refer to Plant Operating Manual for specific recommendations.

TREATED WOOD USE LIMITATIONS:

Effective December 31, 2003, working solutions of this product may only be used for treatment of wood in the following categories:

- 1. Land, fresh water, foundation and marine piles as defined in CSA O80.3-97.
- 2. Poles for highway and utility uses.
- 3. Plywood.
- 4. Wood for highway construction as defined in CSA O80-14.97: lumber for bridges and structural members; lumber for cribbing, culverts and bridge parts; land, fresh water and salt water piles; structural lumber in salt water; posts (fence, guard rail, guide, sign and sight); lighting poles; bridge hand rails, guardrails and posts.
- 5. Fence posts and poles as defined in CSA O80.16-97 for use on farms, piles and posts used as structural members on farms, and plywood used on farms.
- Wood for marine construction (salt water immersion).
- Round poles and posts used in building construction.
- 8. Sawn crossarms.
- Laminations before gluing.
- 10. Shakes and shingles.
- 11. Lumber and plywood for permanent wood foundation.

Forest products treated with this product may only be sold or distributed for the uses noted above.

DO NOT BURN CCA-TREATED WOOD. DO NOT USE CCA-TREATED WOOD AS A COMPOST OR MULCH.

PRECAUTIONS:

POISONOUS IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.

Exposure may result in severe eye damage and skin burns, rash or ulcerated skin. May be fatal if inhaled, absorbed through skin or swallowed. Do not get on eyes, on skin, or on clothing. Wear face shield, plastic gown with long sleeves and rubber gauntlets when handling. Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., handling freshly treated wood and manually opening cylinder doors).

In case of contact, immediately remove all contaminated clothing, including shoes, and flush skin with water for at least 15 minutes. Promptly wash thoroughly with soap and water after handling.

Individuals who enter pressure treatment cylinders and other related equipment that is contaminated with the wood treatment solution (e.g., cylinders that are in operation or are not free of the treatment solution) must wear protective clothing, including overalls, jacket, gloves and boots, impervious to the wood treatment formulation. In addition, individuals who enter pressure-treatment cylinders must wear properly fitting well maintained high efficiency filter respirators. MSHA/NIOSH approved for inorganic arsenic.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, and handling freshly treated wood).

Wash thoroughly after skin contact and before eating, drinking, use of tobacco product or using restrooms. Protective clothing* must be changed when it shows signs of contamination. Applicators must leave protective clothing and workshoes or boots and equipment at the plant in an area free from contamination. Worn out protective clothing and workshoes or boots must be left at the plant and disposed of in a manner approved for pesticide disposal and in accordance with Provincial and Federal regulations.

*Example of acceptable protective clothing during application and handling of inorganic arsenicals are vinyl, polyvinyl chloride (PVC), neoprene, KBR (Buna-N) and polyethylene.

Do not store near heater or open flame, food or feed. Use with adequate ventilation. Do not contaminate water used for domestic consumption, irrigation or Fish or Wildlife. Store concentration in a secure area. Do not burn the treated wood. Dispose of wood by burial.

For further detailed information on safety procedures, storage, handling preparation, application and disposal of CCA wood preservative refer to Environment Canada publication "Recommendations for the design and Operation of Wood Preservation Facilities, March 1999."

DISPOSAL:

For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

FIRST AID:

In case of contact, flush skin or eyes with plenty of water. For eyes, get medical attention. If swallowed, give 1 or 2 glasses of water or 30 ml of milk of magnesia or aluminum hydroxide gel suspended in water (the whites of two or three eggs may be used). Follow with an emetic (15 ml of mustard or table salt in a glass of warm water). Then give olive oil or mucilaginous drink. Never give anything by mouth to an unconscious person. CALL A PHYSICIAN OR POISON CONTROL CENTRE IMMEDIATELY. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Treat symptomatically.

NOTICE TO USER:

This control product is to be used in accordance with the directions on this label. It is an offense under the Pest Control Products act to use a control product under unsafe conditions.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.