HEMPEL'S

ANTIFOULING ATLANTIC (R)

U7134-5000 RED

READ THE LABEL BEFORE USING

COMMERCIAL

CAUTION FLAMMABLE

DANGER POISON

EYE IRRITANT SKIN IRRITANT

GUARANTEE

WEIGHT PERCENT

CUPROUS OXIDE..... 12.00%

Copper (as elemental)

REGISTRATION No. 21660 PEST CONTROL PRODUCTS ACT

NET CONTENTS 18.93 Litres

FOR USE ON SHIPS OR BOATS ONLY

HEMPEL COATINGS (CANADA), INC. #10, 3511 VIKING WAY, RICHMOND, B.C. CANADA V6V 1W1

Keep out of reach of children. Use only in well ventilated areas.

HANDLE WITH CARE AND MIX ONLY IN A CLOSED CONTAINER.

HANDLING: Use an air-fed respirator with a full face mask during handling and applying. Wear chemical resistant gloves and footwear, and chemical resistant clothing with head covering at all times during handling and applying.

When using, do not eat, drink or smoke. Take a shower immediately after work. Wear fresh laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the clean-up of spills, contact the Provincial Regulatory Agency or the Manufacturer.

FIRST AID:

If Swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if those are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

If In Eyes: Flush immediately with plenty of water for at least 15 minutes. Get medical attention.

If on Skin: Wash with plenty of soap and water. Get medical attention.

If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

TOXICOLOGICAL INFORMATION: This product contains petroleum distillates and there is no antidote for solvent ingestion. Drinking or ingestion of this product could cause serious injury or death.

NOTICE TO USER: This control product is to be used only in accordance with the directions on this label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

HEMPEL'S ANTIFOULING U7134

is an advanced antifouling paint containing cuprous oxide for the

prevention of barnacles, algae, coral and other sessile marine fouling organisms. Recommended for the underwater surfaces of steel vessels operated in all coastal and oceanic waters.

DIRECTIONS FOR USE

APPLICATION INSTRUCTIONS: Stir thoroughly and apply 1-2 coats over HEMPEL'S PLATIN PRIMER 1000 or specified primer.

A sealer coat of PLATIN PRIMER 1000 is recommended if ATLANTIC U7134 is to be applied over HEMPADUR COAL TAR EPOXY.

Allow 5 hours at 20 deg C/68 deg F between coats of ATLANTIC U7134.

If thinning is required for brush, roller, conventional spray or airless application, use HEMPEL'S THINNER No. 0808.

The ship may be floated when the paint is dry (3-5 hours).

ATLANTIC is not suited for prolonged atmospheric exposure. If exposed to direct sunlight, undocking should not be delayed for more than 72 hours.

Equipment should be promptly cleaned with THINNER 0808 after use.

When renewing the antifouling coat, the old coat should be sealed off with PLATIN PRIMER 1000, even if it appears sound and intact.

Large vessels (i.e. over 25m) must be treated by a trained applicator.

FOR COMPLETE PROTECTION, READ:
MATERIAL SAFETY DATA SHEETS

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.