88.07.26

SAVOLITE

WT 625

LIQUID MICROBICIDE

INDUSTRIAL

CAUTION POISON

CORROSIVE

CORROSIVE TO EYES

READ THE LABEL BEFORE USING

REGISTRATION NO. 20437

PEST CONTROL PRODUCTS ACT

GUARANTEE:

2-Hydroxypropyl Methanethiolsulfonate.....10%

NET CONTENTS:

LOT NUMBER:

SAVOLITE CHEMICAL COMPANY LIMITED HEAD OFFICE: 7901 Progress Way Delta, B.C. V4G 1A3

NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

NOTICE TO BUYER:

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

DESCRIPTION: WT 625 is used to control bacteria in recirculating commercial and industrial water cooling towers.

DISPOSAL:

- 1. Rinse the emptied container thoroughly and add the rinsings to treatment site.
- 2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal or reconditioning.
- 3. Dispose of the container in accordance with provincial requirements.
- 4. For information on the disposal of unused, unwanted product and the cleanup of spills, contact the regional office of Conservation & Protection, Environment Canada.
- 5. For small spills, recover free liquid. Soak up residue with solids absorbent. DO NOT FLUSH INTO SURFACE STREAMS. INFORM ENVIRONMENT CANADA AS IN #4.

DIRECTIONS FOR USE: Prior to the use of WT 625 in water cooling towers, systems should be cleaned to remove algae growth, microbiological slime, and other deposits. Then make an initial slug addition of 80 mL of WT 625 per 1,000 Litres of water in the system. Repeat initial dosage until control is evident. Make subsequent slug additions of 30 mL WT 625 per 1,000 Litres of water three times a week or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

PRECAUTIONS: SEVERE EYE AND SKIN IRRITANT. Avoid ingestion, inhalation, and contact with skin, eyes and clothing. Where there is a risk of contact, wear protective clothing. Store away from: (a)Oxidizing materials,(b)Heat and sources of ignition,(c)Food and food containers.

FIRST AID TREATMENT: In the case of contact with skin or eyes, give prolonged irrigation with water. In the case of ingestion, wash out the mouth thoroughly with water and give water to drink,

then induce vomiting by administering 15 mL of syrup of Ipecac. In all cases obtain medical attention immediately.

FOR INDUSTRIAL & INSTITUTIONAL USE ONLY.

KEEP FROM FREEZING.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))