ECC International

METASOL® CMI-150-C

PAPERMILL SLIMICIDE

COMMERCIAL

WARNING CORROSIVE

GUARANTEE:

5-Chloro-2-methyl-4-isothiazolin-3-one 1.13% 2-Methyl-4-isothiazolin-3-one 0.37%

READ THIS LABEL BEFORE USING

REGISTRATION NO. 25380

PEST CONTROL PRODUCTS ACT

NET CONTENTS: 1116 KG. (2460 LB.)

MANUFACTURED BY: ECC INTERNATIONAL P.O. BOX 1346 PITTSBURGH, PA 15230

FOR

ECC INTERNATIONAL
7895 Tranmere Drive
Suite #213-214
Mississauga, Ontario
L5S 1V9

PRECAUTIONS

DANGER!

CORROSIVE TO EYES AND CAUSES SKIN BURNS.

MAY CAUSE ALLERGIC SKIN REACTION.

MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN.

Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Do not take internally. Wash thoroughly after handling. This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water. Apply this product only as specified on this label.

FIRST AID: IF SWALLOWED: DO NOT INDUCE VOMITING. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician or Poison Control Centre immediately.

IF INHALED: Remove immediately to fresh air. If not breathing apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

IF IN EYES: Flush with plenty of water for at least 15 minutes. Call a physician.

TOXICOLOGICAL INFORMATION: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed. Skin burns and corrosion may be delayed for several hours.

DIRECTIONS FOR USE

PULP AND PAPER

Metasol CMI-150-C is recommended for the control of bacterial and fungal slime in the production of paper.

POINT OF ADDITION: Metasol CMI-150-C should be added at a point in the system to insure uniform mixing such as the Beater, Hydropulper or Fan or Broke Storage Pumps.

DOSAGE: Apply 0.3 to 1.1 kgs. of Metasol CMI-150-C as supplied per tonne (dry basis) of pulp or paper produced, as a slug dose. If needed repeat daily. Badly fouled systems should be cleaned before initial treatment. One litre of Metasol CMI-150-C weighs 1.01 kg.

STORAGE AND DISPOSAL

DISPOSAL:

- 1) Rinse the emptied container thoroughly and add the rinsings to treatment site.
- 2) Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
- 3) Make the empty container unsuitable for further use.
- 4) Dispose of the container in accordance with provincial requirements.
- 5) For information on the disposal of unused, unwanted product and the cleanup of spills, contact the Provincial Regulatory Agency or the manufacturer.

NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

NOTICE TO BUYER:

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))