

99.03.15

SAPSTAIN CONTROL CHEMICAL

RODEWOD 200 SC

READ THE LABEL BEFORE USING

COMMERCIAL

FOR INDUSTRIAL USE ONLY

Aids in the control of blue stain, mold, and decay  
of freshly cut lumber when properly used.

KEEP OUT OF REACH OF CHILDREN

WARNING POISON

WARNING EYE IRRITANT

GUARANTEE:

Azaconazole 200 g/L

REGISTRATION NO. 25734  
PEST CONTROL PRODUCTS ACT

Note: For further information on the storage, handling, use and disposal of Rodewod 200SC contact Diacon Technologies Ltd. and refer to BC Environment and Environment Canada's publication "Antisapstain Wood Protection Recommendations for Design and Operation", May 1994.

Active ingredient is manufactured by Janssen Pharmaceutica, Beerse, Belgium. Rodewod 200SC is formulated and distributed for Janssen Pharmaceutica by Diacon Technologies Ltd.

NET CONTENTS: 205 LITRE

Registrant:  
JANSSEN PHARMACEUTICA  
Plant Protection Division  
1125 Trenton-Haliburton Rd.  
Titusville, New Jersey  
08560-0200  
(609) 730-2607

Distributed by:  
DIACON TECHNOLOGIES LTD.  
11420 Blacksmith Place  
Richmond, B.C.  
V7A 4X1  
(604) 271-8855

#### USE RESTRICTIONS

- 1) Treated wood is not to be used for construction of food handling containers, food storage facilities or food growing building (e.g., mushroom houses).
- 2) Not for use in drive-through dip tanks.

#### DILUTE BEFORE USING:

For best results, lumber should be treated immediately after it is sawn. A delay in treatment of 24 hours or more permits the start of stain, mold, and decay growth which subsequently requires a stronger treatment to achieve control of surface growth. Delayed application and log borne infection can result in internal stain often under a bright surface.

Freshly dipped or sprayed lumber should be protected from rain washing. Dip tanks and drip aprons must be roofed, paved, and drained to prevent dilution and loss of the anti-stain solution. Anti-stain treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use anti-stain solution must be adjusted to accommodate seasonal changes in the exposure and species being treated.

Dip tanks and spray equipment must be properly maintained. Spray boxes must be equipped with mechanical means of preventing the escape of droplets or entrained aerosols.

#### MIXING INSTRUCTIONS:

Mix one litre of this concentrate per 5-20 litres of water to protect lumber against sapstaining organisms during protracted periods of storage and transit. Dilution rates will be influenced by seasonal conditions, exposure during storage and transit, treating methods and wood species. The operational target deposition level of azaconazole on the surface of treated lumber is 180-200 micrograms/CM<sup>2</sup>. This should be verified periodically using available analytical quality control techniques. (Contact Diacon Technologies Ltd. for

further information).

Lumber and logs should be totally immersed or sprayed so as to ensure that all surfaces are treated. Put about **a** of the water to be used in the mixing tank. Add the correct amount of Rodewod 200SC and then rinse the container into the tank. Add the balance of water needed and mix thoroughly. In a dipping process, the agitation resulting from the movement of the wood will be sufficient to ensure a good mix. On standing unused for a period, remix thoroughly before use. When using proportioning pumps for mixing, Rodewod 200SC should be maintained at temperature above 10EC to prevent inaccurate mixing due to viscosity changes.

NOTE: With normal dip or spray application, long term control of decay cannot be achieved. This product is designed to provide blue stain, mold and decay control during storage and in transit.

#### DISPOSAL:

- 1) Rinse the emptied container thoroughly and add the rinsings to treatment site.
- 2) Follow Provincial Instructions for any required additional cleaning of the container prior to its disposal or reconditioning.
- 3) Dispose of the container in accordance with Provincial requirements.
- 4) For information on the disposal of unused, unwanted product and the cleanup of spills, contact the regional office of Environment Canada.
- 5) For small spills, recover free liquid. Soak up residue with solids absorbent. DO NOT FLUSH INTO SURFACE STREAMS. INFORM ENVIRONMENT CANADA AS IN #4.

#### STORAGE:

Store in a closed, properly labelled container in a cool place. Keep containers closed when not in use. Store above OEC (32EF).

DO NOT use, pour, spill, or store near heat or open flame.

#### NOTICE TO BUYER:

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to

persons or property arising from the use or handling of this product and accepts the product on that condition.

NOTICE TO USER:

This control product is to be used only in accordance with the directions on the label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

PRECAUTIONARY STATEMENTS:

CONCENTRATE MAY BE FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH THE SKIN. DO NOT GET IN EYES.

Do not get concentrate in eyes, on skin, or on clothing. Do not breathe concentrate spray mists, When handling the concentrate, wear full-face protection with cartridge respirator and impermeable gloves, aprons, a boots. Use only in well ventilated areas. Do not wear contact lenses. When working in the dip and spray area, or handling contaminated equipment, wear impermeable gloves. Wear impermeable aprons and boots if there is potential for getting wet by the Rodewod 200SC solution and full-face protection if there is a possibility of splashing. When handling freshly treated lumber, wear impermeable gloves. Use eye protection (goggles) if eye contact with Rodewod 200SC is possible. Once dry, the treated wood can be handled with cotton or leather gloves. Wash hands and face before eating, drinking, smoking and using the toilet. Change clothing daily. Wash contaminated clothing separately from household laundry. Not for use of storage in or around the home. Clean contaminated equipment thoroughly prior to making welding repairs.

FIRST AID:

If Swallowed: Call a physician or Poison Control Centre. Drink 1 or 2 of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person. If On Skin: Wash thoroughly with soap and water. Get medical attention if irritation persists. If In Eyes: Hold eyelids open and flush immediately with a steady gentle stream of water for at least 15 minutes. Get medical attention. If Inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

PHYSICAL OR CHEMICAL HAZARDS:

Keep from freezing. Store away from foodstuffs. Do not use or store near open flame.

TOXICOLOGICAL INFORMATION:

This product contains (4 %) ethylene glycol and nonyl phenol ethoxylate (4%).

ENVIRONMENTAL HAZARDS:

This product is toxic to fish and wildlife. Do not apply directly to any body of water. Do not contaminate water by cleaning of equipment or disposal of wastes.

This product is toxic to domestic animals. Treated sawdust, shavings, and residues of the treatment process should be disposed of properly and not come in contact with domestic animals or be used as bedding or litter.

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+) )