

TROY SOLVENT BASED WOOD PRESERVATIVE

A Ready to Use Solvent Based Wood Preservative for Treatment of Exterior Millwork Such as Door and Window Sash Components to Control Mildew and Wood Rot

COMMERCIAL
REGISTRATION NO. 25697
PEST CONTROL PRODUCTS ACT
GUARANTEE:
3-Iodo-2-Propynyl Butyl Carbamate.....0.5%

POST A COPY OF THIS LABEL IN THE TREATMENT AREA

WARNING



CORROSIVE
WARNING SKIN IRRITANT

NET CONTENTS :

READ THE LABEL BEFORE USING
KEEP OUT OF REACH OF CHILDREN

PRECAUTIONS:

May irritate eyes. Avoid contact with skin, eyes and clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Wear rubber gloves when applying and handling freshly treated wood. Wear goggles or face shield when applying as a spray.

DISPOSAL:

1. Triple – or pressure-rinse the empty container and add the rinsings to the treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product and the cleanup of spills, contact the Provincial Regulatory Agency or the Manufacturer.

Do not contaminate water, food or feed by storage or disposal.

FIRST AID:

If in eyes: Flush with plenty of water. Call a physician if irritation persists.

If on skin: Wash with plenty of soap and water. Get medical attention or contact a poison control center.

If Swallowed: Immediately drink two glasses of water. Do not give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention IMMEDIATELY or contact a poison control center. Take container, label or product name and the Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION:

Probable mucosal damage may contraindicate the use of gastric lavage.

DIRECTIONS FOR USE:

This product is not recommended for use on primed or previously painted surfaces. Do not use on wood that will be in contact with food or potable water. This product should be used for above ground applications only. Do not apply when the surface or atmospheric temperature is less than 10°C. This product can be used for all above ground wood applications including lumber, plywood, shingles, shakes, porches, railings, decks, patios, millwork and joinery. For use on wood joiner products including window and door components or exterior nonstructural decorative wood joinery items which are not in ground contact. Do not use on wood products that may come in contact with food, feed or drinking water. Machine, cut, glue and sand wood as desired prior to treating. Do not apply over previously finished or stained wood. Wood must be clean and dry. Engineered ventilation systems may be required to remove solvent vapors during treatment mixing or drying.

Apply this product by the following methods: a) Double vacuum system (closed system). Wood should be dry to the touch upon removal from the treating chamber. Use a treating schedule that achieves adequate distribution of the active to meet market standards of customer specifications. b) Bundle dipping or other immersion methods that utilize automated technology (3 minute minimum treatment). c) Flood coating, roller coating or for using automated technology (15 second minimum technology). d) Spray box automated technology treating parameters appropriate for the specific unit and substrate.

Treatment of Seasoned Wood: Surface Preparation: All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax or any other contaminants that might affect adhesion or performance. Remove existing mildew by scrubbing with a 50% solution of household bleach followed by water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Make sure all surfaces are dry. Wood should be dry, unpainted, well seasoned and bark free. Cut, machine and sand wood prior to treatment if possible. If not, liberally apply two coats of preservative to all joints, cracks, cut ends, holes or other openings. If coating, apply with a brush, sprayer or roller. For best protection, use two coats. Apply the second coat after the first coat is dry (12 hours minimum). **Coverage:** Depending upon the method of application and porosity, texture and dryness of the wood: 5-10 square metres per litre.

Equipment Cleaning: Use a solvent such as mineral spirits to remove wet wood preservative from all surfaces, brushes, sprayers, and rollers.

USE LIMITATION:

Treatment facilities shall provide appropriate industrial hygiene measures and safety equipment for all safe use of this product. The treatment site must have effective containment and pollution abatement technology to insure that the pesticide is not released into the surrounding environment under normal conditions. Freshly treated wood shall be handled and sorted in a manner, which provides no opportunity for the preservative release into the environment. Outdoor treatment facilities are prohibited.

NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

NOTICE:

This product contains Mineral Spirits at 27.22% and Methyl ethyl ketone at 0.8%, which requires further toxicological testing.

TROY CHEMICAL CORPORATION
ONE AVENUE L
NEWARK, NJ 07105
(973) 589-2500

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.