

10-MAR-2005 Notification received of a label change. See below for this change.

# PROCESS B-1005

Slimicide

**A MICROBIOCIDIC CONTROLLING SLIME, FORMING BACTERIA, SULFATE REDUCING BACTERIA, FUNGI AND YEAST IN PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS AND WATER BASED COATINGS FOR PAPER AND PAPERBOARD**

**REGISTRATION NO.: 24683**  
**PEST CONTROL PRODUCTS ACT**

**GUARANTEE**  
Glutaraldehyde.....25%

**COMMERCIAL**  
**DANGER**  
**CORROSIVE**

**READ THE LABEL BEFORE USING**

**REF # :**  
**LOT #:**

Notification Change

**NET CONTENTS    kg**

**E.Q.U.I.P. International Inc.**  
~~19400 Clark Graham~~  
~~Baie d'Urfé (Québec)~~  
~~H9X 3R8    (800) 363-7885~~

**KEMIRA CHEMICALS CANADA INC.**  
**2-1380 COUNTY RD**  
**PO BOX 615**  
**MAITLAND ON K0E 1P0**

**DIRECTIONS**

PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS:

**Point of Addition :** PROCESS B-1005 Slimicide should be added to the paper making system at a point of uniform mixing such as the head box, beaters, broke chest, save-all tank or white-water tank.

**Initial treatment:** When the system is noticeably contaminated, add 0.5 to 3 kg of PROCESS B-1005 Slimicide per metric tonne of pulp and paper (dry basis) as a slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled out prior to initial treatment.

**Subsequent dose:** When microbial control is evident, add 0.3 to 2 kg of PROCESS B-1005 Slimicide per metric tonne of pulp or paper (dry basis) as a slug dose necessary to maintain control.

WATER BASED COATINGS, PIGMENTS AND FILLER SLURRIES FOR PAPER AND PAPERBOARD:

Add sufficient quantities of PROCESS B-1005 to produce a concentration of 200 to 1200 ppm PROCESS B-1005 based on slurry solids.

**PRECAUTIONS**

**DANGER – KEEP OUT OF REACH OF CHILDREN**

Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. Harmful if swallowed. Harmful if absorbed through skin. Prolonged or frequent repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing.

Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing and rubber gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

**TOXICOLOGICAL INFORMATION**

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiration depression and convulsion may be needed.

**FIRST AID INSTRUCTIONS**

**Eye Contact:** Immediately flush with plenty of water for at least 15 minutes. Do not remove contact lenses, if worn. Get immediate medical attention.

**Skin Contact:** Wash with plenty of soap and water. Get medical attention.

**Inhalation:** Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician.

**Ingestion:** DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical advice or contact a Poison Control Centre IMMEDIATELY.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

**DISPOSAL**

1. Triple or pressure-rinse the empty container. Add the rinsings to the spray mixture in the tank.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

**STORAGE AND HANDLING**

PROCESS B-1005 solutions are incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminium, tin and zinc. These solutions can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about -10°C. Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month) temperatures of up to 38°C can be tolerated but the preferred maximum storage temperature is about 27°C.

A stainless steel centrifuge pump is suggested for transfer service. Spiral wound stainless steel with TEFLON™ is suitable for gaskets and packing.

**NOTICE TO USER**

This control product is to be used only in accordance with the directions on this label. It is an offence under the *Pest Control Products Act* to use a control product under unsafe conditions.

**NOTICE TO BUYER**

Seller's guarantee shall be limited to the terms on the label and, subject thereto, the buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

**PLEASE RETURN CONTAINER TO**

**19400 Clark Graham, Baie d'Urfé**

In case of spillage : CANUTEC 1-613-996-6666

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.