

06-JUL-1998

OUR BEST
MATCHLESS(R)

BOAT &
YACHT
COATING

325 Red Bottom 946 mL

Antifouling

DOMESTIC

IMPORTANT: READ THE LABEL BEFORE USING.

FOR USE ON BOATS ONLY. SKIN
AND EYE IRRITANT. NOT FOR
SPRAY USE.
ONLY BRUSH OR ROLLER APPLICATION.

CAUTION FLAMMABLE

DANGER POISON

GUARANTEE:

CUPROUS OXIDE	25%
COPPER AS ELEMENTAL	21%

REGISTRATION NO. 22571
PEST CONTROL PRODUCTS ACT

MATCHLESS INC.,
P.O. BOX 6090
ST. JOHN'S, NEWFOUNDLAND
A1C 5X8

Surface Preparation

Steel Surfaces: Must be clean, dry and free of rust. New steel-apply Matchless 330 Primer anticorrosive barrier system, followed by two coats of Antifouling. Previously painted surfaces should be wire brushed, scraped or sand blasted and the exposed steel immediately primed with 330 Primer before finishing with Antifouling.

Wood(New): Must be clean and dry. Apply one coat of Antifouling let dry for 24 hours, sand lightly, remove dust and apply two coats of Antifouling. Previously Painted Wood Surfaces: Old antifouling paint should be thoroughly sanded and scraped to bare wood then primed and finished using Antifouling.

Fibreglass: Wash the fibreglass with 350 Cleaner and follow with a thorough cleaning of the surface with Matchless 361 Thinner to remove all wax contaminants, change cloths frequently during this procedure. Sand thoroughly to dull the surface. Remove all sanding dust with 361 Thinner and apply two coats of Antifouling. Blistering Gelcoat(Fibreglass): Remove all old antifouling by sanding. Sand all the gelcoat and fill voids with an epoxy fairing compound. Sand areas smooth. Apply two coats of 362 Epoxy Sealer. Apply two coats of Antifouling.

Under Metal Parts and Lead Keels: Scrape, sandblast or wire brush surface to remove old paint and rust. Wash surface with 361 Thinner to remove dust and other residue. Apply two coats of 362 Epoxy Sealer. Apply two coats of Antifouling.

Do not use this product on aluminum hulls and outdrives. For best performance apply two coats.

Contact your Matchless representative for detailed surface preparations, specifications and recommendations for use of this Matchless anticorrosive barrier system.

Application: Mix well. Apply by brush or roller at a temperature between 10'C-30'C.

Thinning: If required for application use up to 10% by volume of 360 Thinner. Clean up: Use Matchless 360 Thinner. Coverage: 7 to 8 M2/946 ml. Drying Time: Allow 4 hours between coats. Immersion: Minimum time 12 hours. Recommended time 24 hours. Maximum time 60 days.

Notice to User

This control product is to be used only in accordance with the

directions on this label. It is an offence under the PEST CONTROL PRODUCTS ACT to use a control product under unsafe conditions.

PRECAUTION: Keep away from heat, sparks and flame. Vapours from this product are heavier than air and may cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical resistant clothing, with head covering or hat, gloves, goggles and footwear at all times during handling and application.

Keep out of reach of children. Handle with care and mix only in a closed container. Use only in well ventilated areas. When sanding and removing old antifouling paint, use a face mask to prevent inhalation of sanding dust. When using, do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

FIRST AID INSTRUCTIONS: Move to fresh air. If breathing is difficult, administer artificial respiration. Contact physician.
SKIN CONTACT: Remove contaminated clothing. Wash with soap and water. If irritation persists, contact a physician. **EYES:** Flush with clean water for 15 minutes. Contact a physician.
INGESTION: Do not induce vomiting. Contact a physician immediately.

TOXICOLOGICAL INFORMATION: Contains petroleum distillates. Acute overexposure may cause anaesthesia, headache, nausea, narcosis, defatting of skin or eye irritation.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Dispose of empty containers and paint debris in accordance with Provincial requirements. For information on disposal of unused product and clean up spills, contact the regional office of Environment Protection, Environment Canada.

"Sellers guarantee shall be limited to the terms set out on this label and subject thereto, the buyer assumes the risk to persons

or property arising from the use or handling of this product and accepts the product on that condition."

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))