

97.01.02

Jotun Valspar

MARINE COATINGS

60A1000 RED

HYDRO CLEAN ANTI-FOULING

GUARANTEE:

Cuprous Oxide.....	40.9%
Copper (as elemental).....	36.3%

COMMERCIAL

SKIN IRRITANT - EYE IRRITANT

READ THE LABEL BEFORE USING

ONLY FOR USE ON BOATS OR SHIPS

DANGER

POISON

FLAMMABLE

"REGISTRATION NO. 21654  
PEST CONTROL PRODUCTS ACT"

Net 18.9 Liters

The Valspar Corporation  
645 Coronation Drive  
West Hill, Ontario, Canada M1E 4R6

PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS (& DOMESTIC ANIMALS)

WARNING!

Causes Eye Irritation. Harmful If Absorbed Through Skin.

"Use an air-fed respirator with a full face mask during handling and applying. Wear chemical resistant gloves and footwear, and chemical resistant clothing with head covering at all times during handling and applying".

- Keep out of reach of children
- Handle with care and mix only in a closed container - Use only in well ventilated areas
- When using do not eat, drink or smoke
- Take a shower immediately after work
- Wear freshly laundered clothes daily
- Wash hands and face before eating, drinking, smoking and using the toilet
- Store and wash all protective clothing separately from household laundry
- Wash protective clothing in detergent and hot water before reuse

ENVIRONMENTAL HAZARDS: "Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

PHYSICAL OR CHEMICAL HAZARDS:

Flammable. Keep away from heat and open flame.

TOXICOLOGICAL INFORMATION

If swallowed, drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

If in eyes: flush with plenty of water. Get medical attention.

If on skin: wash with plenty of soap and water. Get medical attention.

If inhaled: remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

DIRECTIONS FOR USE:

ANTI-FOULING PAINT FOR METAL BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on ship bottoms in salt and brackish water which would sustain such growth. A minimum of two coats is recommended for best performance.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose

paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats.

Mixing: Before use power mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity. Application: Apply by brush, roll or spray. Contents may be applied by hot spray (temperatures not to exceed 35'C.), airless spray or regular cold spray. Apply a full wet coat in a double crosshatch pattern. Do not paint in cold or damp weather.

Thinning: Normally no thinning required. Where thinning is necessary, use thinner 7-T-33, Xylene.

Dry Time: At 21'C. and 50% R.H. allow at least 4 hours dry time between coats, and a minimum of 8 hours before refloating.

D.O.T. SHIPPING NAME: PAINT

D.O.T. HAZARD CLASS: FLAMMABLE LIQUID

D.O.T. HAZARD IDENTIFICATION NUMBER: UN 1263

Refer to Product Material Safety Data Bulletin available upon request, for further safety and handling information.

Large vessels (i.e. over 25m) must be treated by trained applicators.

NOTICE TO USER: This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

#### STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

DISPOSAL: Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the cleanup of spills contact the Provincial Regulatory Agency or the Manufacturer.

The VOC of this paint exceeds 420 grams/liter (3.5 lbs./gal.)

The Valspar Corporation  
MAINTENANCE & MARINE COATINGS DEPARTMENT  
MINNEAPOLIS, MN 55415

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+) )