

94.12.29

WOOLSEY (R)

NEPTUNE

Anti-Fouling Finish

710A Royal Red

SKIN IRRITANT

EYE IRRITANT

GUARANTEE

CUPROUS OXIDE.....66.9%

Copper (as elemental)....%

READ THE LABEL BEFORE USING

REGISTRATION NO. 21702
PEST CONTROL PRODUCTS ACT

FOR USE ON BOATS ONLY

COMMERCIAL

MARINE

DANGER

POISON

CAUTION!

KEEP OUT OF REACH OF CHILDREN

FLAMMABLE

See Other Cautions on Back Panel.

NET CONTENTS 3.8 Litres

Kop-Coat, Inc. Woolsey Division
Rockaway, NJ 07866

MADE IN U.S.A.

KEEP OUT OF REACH OF CHILDREN

Handle with care and mix only in a closed container. Use only in well ventilated areas. When using do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

NOTICE TO USER

This control product is to be used only in accordance with the directions on this label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

DIRECTIONS FOR USE

PREPARATION: Scrape, wirebrush or sandpaper old surfaces to remove scum, contaminants, or loose paint. On bare (unpainted) fiberglass, first scour and scrub with Woolsey "Shipmate" Heavy Duty Fiberglass Cleaner or other strong abrasive agent. Rinse well with fresh water and allow to dry. Sand vigorously until all sheen on gel coat has been removed. Use 1/0 or No. 80 grit production paper. Wipe with clean rag moistened with paint thinner.

PRIMING: On new or bare wood areas and on unpainted fiberglass prepared as directed above, apply first coat thinned 10% as directed below. On iron or steel keels, centerboards or other underwater fittings of wood or fiberglass boats, first remove all old coatings. Then prime these metal areas with three coats. Alternate with 3 coats Woolsey 648/649 Epoxy Primer or 2 coats 650/651 Hi Build Epoxy.

APPLICATION: Mix thoroughly to uniform consistency by pouring off some of the top portion into clean can - then stirring the remainder and gradually adding the portion removed. Apply generously and at full body with good bristly brush using long even strokes. Stir occasionally during use to assure uniform suspension of toxicants in the vehicle.

NUMBER OF COATS: For initial applications, 2 coats are

recommended.

THINNING: Reduce 10% with Woolsey 433 Paint Thinner, turpentine or mineral spirits for brush use on bare surfaces. Otherwise apply this paint at full body, thinning sparingly if necessary.

COVERAGE: 37 SQUARE METRES PER 3.8 litres.

LAUNCHING: Allow from 6 hours to a week after final coat before launching. When an "HER" Epoxy Primer is used, allow from 3 days to a week before launching.

GENERAL DESCRIPTION

NEPTUNE provides maximum protection from fouling of all kinds. Concentrated copper anti-fouling guards against attachments of barnacles, annelids, tunicates, bryozoa, hydroids, algae, and other fouling organisms.

NEPTUNE applies easily and dries quickly. May be used over anti-fouling finishes in good condition, on bare wood or bare fiberglass surfaces.

NEPTUNE is a tough epoxy-vinyl vehicle that withstands frequent trailering, beaching and launching.

NEPTUNE should not be used on aluminum hulls.

NEPTUNE IS FOR USE ON BOATS ONLY.

SELLER'S GUARANTEE SHALL BE LIMITED TO THE TERMS SET OUT ON THE LABEL AND, SUBJECT THERETO, THE BUYER ASSUMES THE RISK TO PERSONS OR PROPERTY ARISING FROM THE USE OR HANDLING OF THIS PRODUCT AID ACCEPTS THE PRODUCT ON THAT CONDITION.

CAUTION

Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breath vapors or spray mist. USE AN AIR-FED RESPIRATOR WITH FULL FACE MASK DURING HANDLING AND APPLYING. WEAR CHEMICAL RESISTANT GLOVES AND FOOT WEAR AND CHEMICAL RESISTANT CLOTHING AT ALL TIMES DURING HANDLING AND APPLYING.

FIRST AID

IF SWALLOWED: Drink promptly a large quantity of milk, egg white, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical

attention.

IF IN EYES: Flush with plenty of water. Get medical attention.

IF ON SKIN: Wash with plenty of soap and water. Get medical attention. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL

Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the cleanup of spills, contact the regional office of Environment Canada.

PHYSICAL OR CHEMICAL HAZARD:

FLAMMABLE! Do not use or store near heat or open flame.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))