

96.04.29

RULE (R)

GLOUCESTER (R)
KL-990

WATERBASED ANTIFOULING COATING

SEA JACKET (TM) II

560-C RED

COMMERCIAL

REGISTRATION NUMBER 24386

PEST CONTROL PRODUCTS ACT

GUARANTEE:

CUPROUS OXIDE 40.1%
COPPER (AS ELEMENTAL) 36.8%

SKIN IRRITANT
EYE IRRITANT

DANGER POISON

NET CONTENTS: 3.78 Litres

READ THE LABEL BEFORE USING

RULE INDUSTRIES, INC.
Cape Ann Industrial Park
Gloucester, MA
01930 U.S.A.

LIMITATION OF WARRANTY:

Seller's guarantee shall be limited to the terms set out on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

Sea Jacket II

Sea Jacket II is a waterbased modified acrylic copolymer. This ablative coating inhibits the attachment of algae, barnacles and Zebra mussels. Sea Jacket II provides effective antifouling protection for fibreglass, wood and steel hulls in fresh and salt water. Sea Jacket II is easy to apply and dries quickly. It can be used over old antifouling coatings in good condition.

DIRECTIONS FOR USE

For use on boats or ships only. For prevention of marine fouling. Application rate is 9.84 square metres per litre (400 square feet per gallon). Large vessels, i.e., over 25 m; must be treated by trained applicators.

Mixing: Mix thoroughly, preferably with a shaker or drill.

Thinning: Apply Sea Jacket II without thinning to assure proper film thickness.

Coverage: For maximum protection, apply 2 coats.

Overcoat and dry times: Allow 1 hour dry time between coats.
Allow 12 hours before launching.

Clean-up: Fresh water.

Application Information:

Apply by brush, roller, or spray. Temperature should be 10°C (50°F) or above. Surface should be clean with loose or flaking paint completely removed. Apply under good drying conditions.

Fibreglass:

New fibreglass bottoms must be dewaxed using #702 Dewaxer. Change rags frequently to remove Dewaxer and contaminants. Sand with 80 to 100 grit paper and prime with two coats of #B370 Two-Part Epoxy Primer. Sand between coats and before applying the antifouling coating to improve adhesion. To protect against gel coat blistering, apply four to five coats of #B370.

Wood:

This paint can be applied to new wood bottoms after sanding smooth with 80 grit paper. Then apply two coats of Sea Jacket II.

Steel:

Clean to bright metal and then seal with 4 coats of anti-corrosive primer such as B374 Epoxy. Apply 2 coats of Sea Jacket II by brush, roller or spray.

NOT FOR USE ON ALUMINUM:

Previously Painted Surfaces:

If the previous coating is in good condition, abrade with 80 grit sandpaper, apply 2 coats of Sea Jacket II by brush, roller or spray. Coatings that are cracked, damaged or peeling should be completely removed before painting.

PRECAUTIONS

Hazardous to Humans and Domestic Animals.

Warning

USE AIR-FED RESPIRATOR WITH A FULL FACE MASK DURING HANDLING AND APPLICATION. WEAR CHEMICAL RESISTANT CLOTHING AND HEAD COVERING AT ALL TIMES DURING HANDLING AND APPLICATION.

- Keep out of the reach of children.
- Handle with care and mix only in a closed container.
- Use only in well ventilated areas.
- When using, do not eat, drink, or smoke.
- Take a shower immediately after work.
- Wear freshly laundered clothes daily.
- Wash hands and face before eating, drinking, smoking and using the toilet.
- Store and wash all protective clothing separately from household laundry.
- Wash protective clothing in detergent and hot water before reuse.

ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to the water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL:

Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the clean up of spills, contact the Provincial Regulatory Agency or the manufacturer.

PHYSICAL OR CHEMICAL HAZARD

Severe eye irritant.

FIRST AID

If swallowed, Promptly drink a large quantity of water. Avoid alcohol and get medical attention, or contact a poison control centre.

If on skin, Wash thoroughly with soap and water.

If in eyes, Flush with plenty of water. Get medical attention.

If inhaled, Remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention immediately.

TOXICOLOGICAL INFORMATION

Contains copper compounds. Do not induce vomiting due to danger of aspiration into lungs. Exposure to vapours mist or dust can cause irritation of the respiratory tract. Ingestion may cause nausea, diarrhea, and gastrointestinal distress.

NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

(R) Rule Registered Trademark

TM Property of Rule Industries, Inc.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))

