

94.12.29

DEVOE(R) COATINGS

216-S-3873 DEVRAN 216

RED ANTIFOULING

DOMESTIC

SMALL CRAFT ANTIFOULING

GUARANTEE:

CUPROUS OXIDE .....	34.88%
COPPER (AS ELEMENTAL).....	30.92%
OXYDE CUIVREUX.....	34.88%
CUIVRE (EN TANT QU'ELEMENT).....	30.92%

REGISTRATION NO. 23175  
PEST CONTROL PRODUCTS ACT

READ THE LABEL BEFORE USING

NET CONTENTS 3.78 LITRES

DANGER

POISON  
FLAMMABLE  
EYE IRRITANT  
SKIN IRRITANT

NOT FOR SPRAY USE - ONLY BRUSH OR ROLLER APPLICATION

DEVOE COATINGS  
DIVISION OF GROW GROUP CANADA LTD.  
55A MACDONALD AVENUE  
DARTMOUTH, NOVA SCOTIA  
B3B 1T9

#### PRECAUTIONS:

WARNING! WEAR CHEMICAL RESISTANT GLOVES, GOGGLES AND FOOTWEAR, AND CHEMICAL RESISTANT CLOTHING WITH HOOD OR HAT AT ALL TIMES DURING HANDLING AND APPLYING.

Keep out of reach of children. Handle with care and mix only in a closed container. Use only in well ventilated areas. When using do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

#### FIRST AID:

If splashed in eyes or on skin, flush thoroughly with water for 15 minutes. For eye contact, get medical attention. If swallowed, drink 2 or 3 glasses of milk or water. Do not induce vomiting. Call a physician immediately.

#### TOXICOLOGICAL INFORMATION:

Contains petroleum distillates. Do not induce vomiting. Can cause stomach and/or intestinal irritation, nausea, vomiting and diarrhea if swallowed. Causes eye and skin irritation and may be harmful if absorbed through the skin. Breathing of vapours or dust can cause respiratory tract irritation, headache, nausea, dizziness, weakness and fatigue. Extreme exposure can result in unconsciousness and even respiratory arrest. Prolonged or repeated overexposure to solvents can cause permanent brain and nervous system damage.

Prolonged or repeated breathing of sanding dust over a period of years may cause dust disease of the lungs. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Product does not contain any ingredients considered carcinogens or potential carcinogens by ACGIH or IARC.

#### ENVIRONMENTAL HAZARDS:

Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

#### DISPOSAL:

Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the cleanup of spills, contact the regional office of Environment Canada.

DIRECTIONS FOR USE:

Read the label information before using product. This product is for application to underwater areas of steel, aluminum, fibreglass, or wood vessels subject to fouling by barnacles, algae, tube worms and other fouling organisms. Surface to be coated should be clean of grease, oil, dirt and moisture. Do not apply directly to metal surfaces.

A suitable barrier system should be applied to steel and aluminum surfaces, a primer is recommended for fibreglass and wood surfaces. Apply by brush or roller. Applicators should wear protective clothing. Clean up with Devoe T-10 Solvent. Launching may be accomplished when coating is dry, (minimum drying time at 25'C is 5 hours), or later if desired.

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))