

97.01.02

AKZO

SIKKENS

VINYL

ANTIFOULING 2000
TIN FREE

YACHTPAINTS

DOMESTIC

RED

GUARANTEE:

COPPER (AS ELEMENTAL.....33.5%

REGISTRATION NO. 21344
PEST CONTROL PRODUCTS ACT

READ THE LABEL BEFORE USING

FLAMMABLE DANGER POISON

SKIN IRRITANT
EYE IRRITANT

NOT FOR SPRAY USE,
ONLY ROLLER
OR BRUSH APPLICATION

NOAH'S
2246 Lakeshore Blvd. W.
Toronto, Ontario
M8V 1A5

Manufactured by:
AKZO Coatings
P.O. Box 3
2170 BA Sassenheim
The Netherlands

DIRECTIONS FOR USE:

For use on ships or boats only. Vinyl based antifouling paint containing copper-compound as a poison. Suitable for fibreglass and wooden boats when extended antifouling protection is required. Use on steel and aluminium only when an anticorrosive system of at least 200 micron dry film thickness has been applied. See our datasheet for correct application. When applying over existing coatings wash with clean water. Wet sand if necessary to remove loose paint or blisters. Stir well before use. Apply 1-2 unthinned coats by brush or roller. Dry after 3 hours at 20'C. May be left exposed to air for two months before launching. Clean equipment with Oplosser.

COVERAGE:

7m²(75 Sq.ft) per litre at a dry film thickness of 40 microns.

STORAGE:

Store containers out of sun and away from heat, sparks and open flames. Keep closures tight and containers upright to prevent leakage.

DISPOSAL:

Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused or unwanted product and the cleanup of spills, contact the Provincial Regulatory Agency or the Manufacturer.

NOTICE TO USER:

This control product is to be used in accordance with the directions on this label. It is an offence under the Pest Products Act to use a control product under unsafe conditions.

PRECAUTIONS:

Wear chemical resistant gloves, goggles and footwear, and chemical resistant clothing including hood or hat at all times during handling and applying. Keep out of reach of children. Handle with care and mix only in a closed container. Use only in well ventilated areas. When using, do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothes in detergent and hot water before reuse.

ENVIRONMENTAL HAZARDS:

Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

FIRST AID:

INHALATION: Move to fresh air, give artificial respiration if necessary.

SKIN CONTACT: Wash with water and soap.

EYE CONTACT: Flush with water for at least 15 min. Consult a physician.

INGESTION: Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Consult physician or poison control centre immediately. Treat symptomatically.

TOXICOLOGICAL INFORMATION:
Contains cuprous oxide and petroleum distillates.

ADR: 3-5C VC 28034

0,75 Le

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))