

94.12.29

ANTIFOULING PAINT

TFA-10 A

COMMERCIAL

This product contains the toxic inert ingredients,  
Tri-orthocresylphosphate (TOCP).

GUARANTEE:

Cuprous Oxide.....47.5%  
Copper (as elemental).....43.5%

REGISTRATION NO. 23046  
PEST CONTROL PRODUCTS ACT

Batch No.

18.925 Liters

DANGER

POISON FLAMMABLE

EYE IRRITANT  
SKIN IRRITANT

READ THE LABEL BEFORE USING

CMP COATINGS, INC.  
1610 ENGINEERS ROAD

BELLE CHASSE, LA 70037

PRECAUTIONS

Wear an air-fed respirator with a full mask during handling and application. Wear chemical resistant gloves and footwear and chemical resistant clothing with head covering at all times during handling and application.

Keep out of reach of children.

- Handle with care and mix only in a closed container.
- Use only in well ventilated areas.
- When using do not eat, drink or smoke.
- Take a shower immediately after work.
- Wear freshly laundered clothes daily.
- Wash hands and face before eating, drinking, smoking and using the toilet.
- Store and wash all protective clothing separately from household laundry.
- Wash protective clothing in detergent and hot water before reuse.

#### FIRST AID:

If splashed in eyes or on skin, flush thoroughly with water for 15 minutes. For eye contact, get medical attention. If swallowed, drink 2 or 3 glasses of milk or water. Do not induce vomiting. Call a physician immediately.

#### TOXICOLOGICAL INFORMATION

Contains petroleum distillates. Do not induce vomiting.

#### NOTICE TO USER

This control product is to be used only in accordance with the directions on this label. It is an offense under the Pest Control Products Act to use a control product under unsafe conditions.

#### ENVIRONMENTAL HAZARDS

Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

#### DISPOSAL

Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal on unused or unwanted product and the cleanup of spills, contact the regional office of Environmental Canada.

#### DIRECTIONS FOR USE

READ THE LABEL AND PRODUCT DATA SHEET. TFA-10 A is an antifouling paint suitable for application to wood, fiberglass, or metal vessels subject to attack by barnacles, algae, tubeworms, and other fouling marine organisms. TFA-10 A may be

used on vessels in both salt and fresh water.

Stir paint thoroughly before applying. TFA-10 A may be applied by spray, brush or roller. Airless spray is strongly recommended if spray is chosen. The surface should be clean and dry prior to paint application. A suitable anticorrosive coating should be applied to metals, and a primer is recommended for wood and fiberglass. Allow a minimum of 12 hours before returning vessel to water.

Large vessels, i.e. over 25 M, must be treated by trained applicators.

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))