FINNAN 1751

LIQUID MICROBIOCIDE

COMMERCIAL

GUARANTEE:

Glutaraldehyde.....45.0%

REGISTRATION NO. 23750

PEST CONTROL PRODUCTS ACT

DANGER

POISON

DANGER CORROSIVE

READ LABEL BEFORE USING

Net Contents: kg

FINNAN ENGINEERED PRODUCTS LIMITED 1149 BELLAMY ROAD NORTH, UNIT 22 SCARBOROUGH, ONTARIO M1H 1H7 PHONE (416) 438-6070, FAX (416) 438-8739

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS

DANGER KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin burns. Harmful if inhaled. May be fatal if swallowed. Harmful if absorbed through skin. May cause allergic skin reactions.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and rubber gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

FIRST AID INSTRUCTIONS

IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Get immediate medical attention.

IF ON SKIN: Immediately wash with plenty of soap and water. Get medical attention.

IF INHALED: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, call a physician.

IF SWALLOWED: DO NOT INDUCE VOMITING. Do not give anything to drink. Seek medical advice with urgency.

TOXICOLOGICAL INFORMATION

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

DISPOSAL:

- 1. Triple or pressure-rinse the empty container. Add the rinsings to the spray mixture in the tank.
- 2. Follow provincial instruction for any required additional cleaning of the container prior to its disposal.
- 3. Make the empty container unsuitable for further use.
- 4. Dispose of the container in accordance with provincial requirements.
- 5. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer or the provincial regulatory agency in case of a spill, and for clean-up of spills.

STORAGE AND HANDLING

FINNAN 1751 LIQUID MICROBIOCIDE solutions are incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. These solutions can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel or reinforced epoxy plastic equipment. This product freezes at about -17'C. Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to 1 month), temperatures of up to 38'C can be tolerated but the preferred maximum storage temperature is about 27'C. A stainless steel centrifugal pump is suggested for transfer service. Spiral wound stainless steel with TEFLON is suitable for gaskets and packing.

NOTICE TO USER:

This control product is to be used only in accordance with the

directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

DIRECTIONS FOR USE

FINNAN 1751 LIQUID MICROBIOCIDE is a microbiocide for use in controlling slime forming bacteria, sulfate reducing bacteria and algae in air washer systems and in recirculating cooling tower systems, including Pasteurizing cooling water systems and closed recirculating process water systems.

AIR WASHERS AND RECIRCULATING COOLING WATER SYSTEMS

This product may be used only in industrial air washers and air washer systems which have mist-eliminating components. FINNAN 1751 LIQUID MICROBIOCIDE should be added at the application rates described below, to a water treatment system at a convenient point of uniform mixing such as the basin area. Additions may be made intermittently (SLUG DOSE) or continuously. Badly fouled systems can be shock treated with FINNAN 1751 LIQUID MICROBIOCIDE. Under these conditions, blowdown should be discontinued for up to 24 hours.

INTERMITTENT (SLUG DOSE) METHOD

Initial Dose: When the system is noticeably fouled apply 500mL -1000mL of FINNAN 1751 LIQUID MICROBIOCIDE per 5000 liters of water in the system. Repeat until control is achieved. Subsequent Dose: When microbial control is evident, add 200mL -500mL of FINNAN 1751 LIQUID MICROBIOCIDE per 5000 liters of water to the system weekly, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 500mL - 1000mL of FINNAN 1751 LIQUID MICROBIOCIDE per 5000 liters of water in the system. Subsequent Dose: Maintain this treatment level by starting a continuous feed of 100mL - 500mL of FINNAN 1751 LIQUID MICROBIOCIDE per 5000 liters of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

PASTEURIZER COOLING WATER SYSTEMS

AVOID CONTAMINATION OF FOOD IN THE APPLICATION OF PRODUCT. FINNAN 1751 LIQUID MICROBIOCIDE should be used at the same application rates and in the same manner as described above. It should be added to the closed recirculating system at a convenient point of uniform mixing such as a basin area, sump area, or other reservoir or collecting area from which the treated water will be circulated uniformly throughout the pasteurizer cooling system.

NOTICE TO BUYER:

"Seller's guarantee shall be limited to the terms on the label and subject thereto, the buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on condition."

BEFORE HANDLING OR USING, READ AND UNDERSTAND THE CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT.

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))