

2017-0740  
2017-09-26

West Marine  
CPP! Plus  
Ablative Antifouling Paint

(BLACK/RED/BLUE/GREEN)

COMMERCIAL  
SUSPENSION

**GUARANTEE**

Copper, present as cuprous oxide and related copper compounds.....44.0%

REGISTRATION NO. 24097 PEST CONTROL PRODUCTS ACT



DANGER POISON  
CAUTION FLAMMABLE.

SKIN IRRITANT  
EYE IRRITANT

See Other Precautions on Back Panel.

KEEP OUT OF REACH OF CHILDREN.

READ THE LABEL BEFORE USING

NET CONTENTS 3.785 L

KOP-COAT, INC., Pettit Paint Division,  
36 Pine Street Rockaway, NJ 07866 MADE IN U.S.A.  
1-800-221-4466

An RPM Company

2017-0740  
2017-09-26

**GENERAL DESCRIPTION:** West Marine CPP! Plus Ablative Antifouling Paint is an antifouling protective coating resistant to algae, barnacles, and other marine fouling. The high loading of cuprous oxide present in the formula enables the paint to perform well, even in the most severe fouling areas. Its controlled erosion characteristics minimize coating buildup and keep underwater surfaces smooth and clean.

## **DIRECTIONS FOR USE**

**PREPARATION OF SURFACE:** The surface to be painted should be clean, dry, and free of any contamination or foreign matter. Always prepare the surface to be painted by sanding and solvent cleaning before any paints or primers are applied. When sanding old antifouling paint use a dust mask to prevent the inhalation of sanding dust. Old, soft bottom paints must be completely removed before West Marine CPP! Plus Ablative Antifouling Paint.

**COVERAGE, APPLICATION AND TEMPERATURE:** West Marine CPP! Plus Ablative Antifouling Paint can be applied by brush, roller or spray. All painting should be done between 9:00 A.M. and 4:00 P.M. in order to avoid the possibility of dew or condensation spoiling the application. The temperature range should be between 10° and 32° C. At least two, and preferably three or four coats should be applied for best performance, particularly in high wear areas such as the waterline. West Marine CPP! Plus Ablative Antifouling Paint will cover approximately 9.8 sq. meters/liter.

**PREPARATION OF PAINT:** West Marine CPP! Plus Ablative Antifouling Paint is heavily loaded with cuprous oxide. As a result of this loading there is a tendency for settling to occur especially if the paint has been on the shelf for several months. It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment; then remix the two parts together thoroughly.

**THINNING:** Use West Marine CPP! Plus Ablative Antifouling Paint Thinner for thinning West Marine CPP! Plus Ablative Antifouling Paint if needed, particularly on warm or breezy days. West Marine CPP! Plus Ablative Antifouling Paint Thinner can also be used to thin West Marine CPP! Plus Ablative Antifouling Paint or spraying and for cleaning equipment. Do not thin West Marine CPP! Plus Ablative Antifouling Paint more than 10% (83 grams/liter) or inadequate paint film thickness will occur and premature erosion of the finish will be likely.

**DRY TIMES:** The minimum recoat time is six hours. The minimum dry time between final coat and launching is 16 hours. Under adverse drying conditions such as those encountered on cool or damp days, extend the dry times by 50% in order to ensure that all the solvent is out of the paint film. There is no maximum time before launching.

**MAINTENANCE OF ANTIFOULING PAINT:** No antifouling paint can be effective under all conditions of exposure. Manmade pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, silt, dirt, oil, brackish water and even electrolysis can ruin an antifouling paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. Lightly scrub the bottom with a soft brush to remove anything from the antifouling paint surface. Scrubbing is particularly important with boats that are idle for extended periods of time. The self cleaning nature of the coating is most effective when the boat is used periodically.

2017-0740  
2017-09-26

## PAINT SYSTEMS

**FIBERGLASS:** Wash the fiberglass with Pettit 15095 Dewaxer to remove parting agents, grease and dirt. Sand thoroughly with 80 grit sandpaper to a dull, finish. Rewash the sanded surface with 15095 Dewaxer and then apply at least two coats of West Marine CPP! Plus Ablative Antifouling Paint. To skip the tedium of sanding, wash the fiberglass TWICE with 15095 Dewaxer and apply a thin coat of Pettit 6999 Sandless Primer. Let dry to a tack-free condition. After the primer has dried tack-free, apply one coat of West Marine CPP! Plus Ablative Antifouling Paint. Do not let the Sandless Primer dry longer than four hours after it reaches the tack-free state before starting and finishing the application of West Marine CPP! Plus Ablative Antifouling Paint. Apply a second coat of West Marine CPP! Plus Ablative Antifouling Paint following the recommended dry time above. Please note that acetone does not readily clean contaminated surfaces and its use as a cleaner/dewaxer is not recommended. To paint old, hard antifouling paints, sand thoroughly with 80 grit sandpaper before applying West Marine CPP! Plus Ablative Antifouling Paint

**BLISTERING GELCOAT:** Consult Technical Bulletins for detailed instructions before undertaking a blister repair program.

**WOODEN HULLS:** Old, hard antifouling paint should be thoroughly sanded. If priming is necessary on bare wood spots, apply a touch up coat of West Marine CPP! Plus Ablative Antifouling Paint to these areas. Then apply the subsequent coats of West Marine CPP! Plus Ablative Antifouling Paint

**STEEL HULLS:** To remove loose rust and scale from the metal surface, scrape, sandblast, or wire brush. Solvent clean the surface to remove grease and dirt and apply 2-3 coats of Pettit 6980 Rustlok Primer. Follow with West Marine CPP! Plus Ablative Antifouling Paint. Consult the directions for the 6980 Rustlok Primer for detailed application and recoat instructions.

**UNDERWATER METAL PARTS:** Abrade to clean bright metal by scraping, sandblasting, or wire brushing. Solvent clean and apply one thin coat Pettit 6455/044 Metal Primer. Let dry four hours and apply one coat Pettit 6462 Q.D. Zinc Chromate Primer. Let dry four hours and apply West Marine CPP! Plus Ablative Antifouling Paint or let dry overnight, sand lightly, and apply West Marine CPP! Plus Ablative Antifouling Paint. Consult individual product labels for complete, detailed instructions. Large vessels, i.e., over 25m; must be treated by trained applicators.

DO NOT apply this product in a way that will contact workers or bystanders, either directly or through drift. Only protected handlers may be in the area during application.

**DO NOT** contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes. **DO NOT** apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats. **DO NOT** discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified by suitable means. **DO NOT** place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

## PRECAUTIONS

**KEEP OUT OF REACH OF CHILDREN**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

2017-0740  
2017-09-26

Mix only in a closed container. When using do not eat, drink, or smoke. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear long pants, a long-sleeved shirt and shoes plus socks during mixing/loading, application, clean-up and repair. Remove personal protective equipment immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them. For cleaning/maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Wash the outside of gloves before removing. May be fatal if swallowed or inhaled. Do not breathe dust or vapor. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling.

#### **FIRST AID:**

**If swallowed:** Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give **any** liquid to the person. Do not give anything by mouth to an unconscious person.

**If on skin or clothing:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

**If inhaled:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

**If in eyes:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention

#### **TOXICOLOGICAL INFORMATION:**

Contains petroleum distillates. Vomiting may cause aspiration pneumonia. **ENVIRONMENTAL**

#### **HAZARDS:**

**TOXIC** to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

#### **DISPOSAL:**

Triple - or pressure - rinse the empty container. Use the rinsings for thinner in future antifouling applications. Follow provincial instruction for any required additional cleaning of the container prior to its disposal. Make the empty container unsuitable for further use. Dispose of the container in accordance with provincial requirements. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean up of spills.

#### **NOTICE TO USER:**

This pest control product is to be used only in accordance with the directions on the label. It is an offence under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

**MEDICAL EMERGENCY : 1-800-548-0489**

2017-0740  
2017-09-26

**PRODUCT INFORMATION: 1-800-221-4466 or [WWW.PETTITPAINT.COM](http://WWW.PETTITPAINT.COM)**