

26-FEB-2009

2009-3846

PRINCIPAL PANEL  
ENGLISH VERSION

PREMIUM PERFORMANCE  
ANTIFOULING FINISH  
Black

READ LABEL BEFORE USING

FOR USE ON BOATS ONLY  
COMMERCIAL  
MARINE

Economical Antifouling Protection  
Hard Smooth Finish  
Apply Over Most Other Antifouling  
Excellent For Fiberglass, Wood & Steel Boats.  
Warning, contains the allergen fish. □

**GUARANTEE:**

Elemental copper, present as cuprous oxide.....33.3%  
This product contains petroleum distillates.

NOT FOR SPRAY USE ONLY BRUSH OR ROLLER APPLICATION

**SKIN IRRITANT, EYE IRRITANT, FLAMMABLE**

REGISTRATION NUMBER 21703 PEST CONTROL PRODUCTS ACT.

DANGER POISON  
CAUTION! KEEP OUT OF REACH OF CHILDREN.

NET CONTENTS 3.785 LITRES

□□

KOP-COAT, INC.  
PETTIT PAINT BRAND  
36 PINE STREET  
ROCKAWAY, NJ 07866  
Telephone: 604-328-4985

MADE IN THE U.S.A.

An RPM Company

## DIRECTIONS FOR USE

**PREPARATION:** Scrape, wire brush or sandpaper old surfaces to remove scum, contaminants or loose paint. On bare (unpainted) fiberglass, first scour and scrub with a strong abrasive agent. Rinse well with fresh water and allow to dry. Sand vigorously until all sheen on gel coat has been removed. Use VO or 80 grit production paper to sand. Wipe clean with rag moistened with mineral spirits

**PRIMING:** On new or bare wood areas and on unpainted fiberglass prepared as directed above, apply first coat of this paint thinned 10%. On steel or cast iron keels, centerboards or other underwater fittings, prime these areas with 3 coats of 4700/4701 High Build Epoxy Primer, carefully following the label directions for this primer.

**APPLICATION:** Mix thoroughly to uniform consistency by pouring off some of top portion into a clean can – then stirring the remainder and gradually adding the portion removed. Apply generously and at full body with good bristle brush, using long even strokes. Stir occasionally during use to assure uniform suspension of toxicants in the vehicle.

**NUMBER OF COATS:** For initial applications, 2 coats are recommended. Drying time between coats 3 hours.

**THINNING:** Reduce 10% with Pettit 120 Brushing Thinner or mineral spirits, for brush use on bare surfaces-also for spray application. Otherwise apply this paint at full body, thinning sparingly if necessary.

**COVERAGE:** 46 square meters per 3.8 litres (500 square feet per gallon).

**LAUNCHING:** Ready for use in four hours. Allow 3 days when an Epoxy Primer is used before launching. This product is for use on boats only. Large vessels, i.e. over 25m must be treated by trained applicators.

## GENERAL DESCRIPTION

This product provides maximum protection from fouling of all kinds. Concentrated copper guards against attachment of barnacles, annelids, tunicates, bryozoa, hydroids, algae and other fouling organisms.

This product applies easily and dries quickly. May be used over old antifouling finishes in good condition.

This product is ideal for wood, fiberglass and properly primed metal boats.

## PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

HAZARD TO HUMANS AND DOMESTIC ANIMALS

Handle with care and mix only in a closed container. Use only in well ventilated areas. When using do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

**CAUTION** Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapors. USE AN AIR-FED RESPIRATOR WITH FULL FACE MASK DURING HANDLING AND APPLYING. WEAR CHEMICAL RESISTANT GLOVES AND FOOT WEAR AND CHEMICAL RESISTANT CLOTHING AT ALL TIMES DURING HANDLING AND APPLYING.

## FIRST AID

**IF SWALLOWED:** Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

**Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.**

## TOXICOLOGICAL INFORMATION

Contains petroleum distillate. Do not induce vomiting. Treat symptomatically

## ENVIRONMENTAL HAZARDS

This material is toxic to aquatic organisms. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

## STORAGE

Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

## DISPOSAL

Triple or pressure rinse the empty container. Follow provincial instructions for any required additional cleaning of the container prior to its disposal. Make the empty container unsuitable for further use. Dispose of the container in accordance with provincial requirements. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean up of spills.

## PHYSICAL OR CHEMICAL HAZARDS

Flammable. Do not use or store near heat or open flame.

## NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

**MEDICAL EMERGENCIES: 1-800-548-0489**

26-FEB-2009

2009-3846

PRINCIPAL PANEL  
ENGLISH VERSION

PREMIUM PERFORMANCE  
ANTIFOULING FINISH  
RED

READ LABEL BEFORE USING

FOR USE ON BOATS ONLY  
COMMERCIAL  
MARINE

Economical Antifouling Protection  
Hard Smooth Finish  
Apply Over Most Other Antifoulings  
Excellent For Fiberglass, Wood & Steel Boats.  
Warning, contains the allergen fish.

**GUARANTEE:**

Elemental copper, present as cuprous oxide.....33.3%

This product contains petroleum distillates.

NOT FOR SPRAY USE ONLY BRUSH OR ROLLER APPLICATION

**SKIN IRRITANT, EYE IRRITANT, FLAMMABLE**

REGISTRATION NUMBER 21703 PEST CONTROL PRODUCTS ACT.

DANGER POISON  
CAUTION! KEEP OUT OF REACH OF CHILDREN.

NET CONTENTS 3.785 LITRES

□□

KOP-COAT, INC.  
PETTIT PAINT BRAND  
36 PINE STREET  
ROCKAWAY, NJ 07866  
Telephone: 604-328-4985

MADE IN THE U.S.A.

An RPM Company

## DIRECTIONS FOR USE

**PREPARATION:** Scrape, wire brush or sandpaper old surfaces to remove scum, contaminants or loose paint. On bare (unpainted) fiberglass, first scour and scrub with a strong abrasive agent. Rinse well with fresh water and allow to dry. Sand vigorously until all sheen on gel coat has been removed. Use VO or 80 grit production paper to sand. Wipe clean with rag moistened with mineral spirits

**PRIMING:** On new or bare wood areas and on unpainted fiberglass prepared as directed above, apply first coat of this paint thinned 10%. On steel or cast iron keels, centerboards or other underwater fittings, prime these areas with 3 coats of 4700/4701 High Build Epoxy Primer, carefully following the label directions for this primer.

**APPLICATION:** Mix thoroughly to uniform consistency by pouring off some of top portion into a clean can – then stirring the remainder and gradually adding the portion removed. Apply generously and at full body with good bristle brush, using long even strokes. Stir occasionally during use to assure uniform suspension of toxicants in the vehicle.

**NUMBER OF COATS:** For initial applications, 2 coats are recommended. Drying time between coats 3 hours.

**THINNING:** Reduce 10% with Pettit 120 Brushing Thinner or mineral spirits, for brush use on bare surfaces-also for spray application. Otherwise apply this paint at full body, thinning sparingly if necessary.

**COVERAGE:** 46 square meters per 3.8 litres (500 square feet per gallon).

**LAUNCHING:** Ready for use in four hours. Allow 3 days when an Epoxy Primer is used before launching. This product is for use on boats only. Large vessels, i.e. over 25m must be treated by trained applicators.

## GENERAL DESCRIPTION

This product provides maximum protection from fouling of all kinds. Concentrated copper guards against attachment of barnacles, annelids, tunicates, bryozoa, hydroids, algae and other fouling organisms.

This product applies easily and dries quickly. May be used over old antifouling finishes in good condition.

This product is ideal for wood, fiberglass and properly primed metal boats.

## PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

HAZARD TO HUMANS AND DOMESTIC ANIMALS

Handle with care and mix only in a closed container. Use only in well ventilated areas. When using do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

**CAUTION** Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapors. USE AN AIR-FED RESPIRATOR WITH FULL FACE MASK DURING HANDLING AND APPLYING. WEAR CHEMICAL RESISTANT GLOVES AND FOOT WEAR AND CHEMICAL RESISTANT CLOTHING AT ALL TIMES DURING HANDLING AND APPLYING.

## FIRST AID

**IF SWALLOWED:** Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

**Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.**

## TOXICOLOGICAL INFORMATION

Contains petroleum distillate. Do not induce vomiting. Treat symptomatically

## ENVIRONMENTAL HAZARDS

This material is toxic to aquatic organisms. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

## STORAGE

Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

## DISPOSAL

Triple or pressure rinse the empty container. Follow provincial instructions for any required additional cleaning of the container prior to its disposal. Make the empty container unsuitable for further use. Dispose of the container in accordance with provincial requirements. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean up of spills.

## PHYSICAL OR CHEMICAL HAZARDS

Flammable. Do not use or store near heat or open flame.

## NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

MEDICAL EMERGENCIES: 1-800-548-0489

26-FEB-2009

2009-3846

PRINCIPAL PANEL  
ENGLISH VERSION

PREMIUM PERFORMANCE  
ANTIFOULING FINISH  
BLUE

READ LABEL BEFORE USING

FOR USE ON BOATS ONLY  
COMMERCIAL  
MARINE

Economical Antifouling Protection  
Hard Smooth Finish  
Apply Over Most Other Antifouling  
Excellent For Fiberglass, Wood & Steel Boats.  
Warning, contains the allergen fish.

**GUARANTEE:**

Elemental copper, present as cuprous oxide.....33.3%

This product contains petroleum distillates.

NOT FOR SPRAY USE ONLY BRUSH OR ROLLER APPLICATION

**SKIN IRRITANT, EYE IRRITANT, FLAMMABLE**

REGISTRATION NUMBER 21703 PEST CONTROL PRODUCTS ACT.

DANGER POISON  
CAUTION! KEEP OUT OF REACH OF CHILDREN.

NET CONTENTS 3.785 LITRES

□□

KOP-COAT, INC.  
PETTIT PAINT BRAND  
36 PINE STREET  
ROCKAWAY, NJ 07866  
Telephone: 604-328-4985

MADE IN THE U.S.A.

An RPM Company

## DIRECTIONS FOR USE

**PREPARATION:** Scrape, wire brush or sandpaper old surfaces to remove scum, contaminants or loose paint. On bare (unpainted) fiberglass, first scour and scrub with a strong abrasive agent. Rinse well with fresh water and allow to dry. Sand vigorously until all sheen on gel coat has been removed. Use VO or 80 grit production paper to sand. Wipe clean with rag moistened with mineral spirits

**PRIMING:** On new or bare wood areas and on unpainted fiberglass prepared as directed above, apply first coat of this paint thinned 10%. On steel or cast iron keels, centerboards or other underwater fittings, prime these areas with 3 coats of 4700/4701 High Build Epoxy Primer, carefully following the label directions for this primer.

**APPLICATION:** Mix thoroughly to uniform consistency by pouring off some of top portion into a clean can – then stirring the remainder and gradually adding the portion removed. Apply generously and at full body with good bristle brush, using long even strokes. Stir occasionally during use to assure uniform suspension of toxicants in the vehicle.

**NUMBER OF COATS:** For initial applications, 2 coats are recommended. Drying time between coats 3 hours.

**THINNING:** Reduce 10% with Pettit 120 Brushing Thinner or mineral spirits, for brush use on bare surfaces-also for spray application. Otherwise apply this paint at full body, thinning sparingly if necessary.

**COVERAGE:** 46 square meters per 3.8 litres (500 square feet per gallon).

**LAUNCHING:** Ready for use in four hours. Allow 3 days when an Epoxy Primer is used before launching. This product is for use on boats only. Large vessels, i.e. over 25m must be treated by trained applicators.

## GENERAL DESCRIPTION

This product provides maximum protection from fouling of all kinds. Concentrated copper guards against attachment of barnacles, annelids, tunicates, bryozoa, hydroids, algae and other fouling organisms.

This product applies easily and dries quickly. May be used over old antifouling finishes in good condition.

This product is ideal for wood, fiberglass and properly primed metal boats.

## PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

HAZARD TO HUMANS AND DOMESTIC ANIMALS

Handle with care and mix only in a closed container. Use only in well ventilated areas. When using do not eat, drink or smoke. Take a shower immediately after work. Wear freshly laundered clothes daily. Wash hands and face before eating, drinking, smoking and using the toilet. Store and wash all protective clothing separately from household laundry. Wash protective clothing in detergent and hot water before reuse.

**CAUTION** Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapors. USE AN AIR-FED RESPIRATOR WITH FULL FACE MASK DURING HANDLING AND APPLYING. WEAR CHEMICAL RESISTANT GLOVES AND FOOT WEAR AND CHEMICAL RESISTANT CLOTHING AT ALL TIMES DURING HANDLING AND APPLYING.

## FIRST AID

**IF SWALLOWED:** Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

## TOXICOLOGICAL INFORMATION

Contains petroleum distillate. Do not induce vomiting. Treat symptomatically

## ENVIRONMENTAL HAZARDS

This material is toxic to aquatic organisms. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

## STORAGE

Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

## DISPOSAL

Triple or pressure rinse the empty container. Follow provincial instructions for any required additional cleaning of the container prior to its disposal. Make the empty container unsuitable for further use. Dispose of the container in accordance with provincial requirements.

For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean up of spills.

**PHYSICAL OR CHEMICAL HAZARDS** Flammable. Do not use or store near heat or open flame.

## NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offense under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

**MEDICAL EMERGENCIES:** 1-800-548-0489

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.