

2017-0299
2017-10-16

FIBERGLASS BOTTOMKOTE®
RACING BRONZE

SOLUTION

ANTI-FOULING PAINT
DOMESTIC

999 BRONZE

INTERNATIONAL PAINT LLC
6001 Antoine Drive
Houston, Texas 77091 USA
713-682-1711

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose of application. **IMPLIED WARRANTIES OF FITNESS FOR A PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 3.78 L

IMPORTANT
READ THE LABEL BEFORE USING
FOR USE ON BOATS ONLY
SKIN AND EYE IRRITANT
NOT FOR SPRAY USE
ONLY BRUSH OR ROLLER APPLICATION

GUARANTEE: Copper 28.00%
Contains the allergen soy

REGISTRATION NO. 21372
PEST CONTROL PRODUCTS ACT

CAUTION
FLAMMABLE

DANGER
POISON
INTERLUX FIBERGLASS BOTTOMKOTE
Acrylic Antifouling Paint

For all types of fibreglass, wood, and steel boats. Specially formulated to apply over most types of antifouling paint and for boats that are frequently removed from water and subjected to rough usage. Provides extended antifouling protection and a smooth, hard finish.

DIRECTIONS FOR USE:

SURFACE PREPARATION: If previous antifouling paint is in good condition, wash down with fresh water, degrease with Interlux Brushing Liquid 333 if required, sand surface lightly and apply Interlux Fibreglass Bottomkote as directed.

Otherwise, remove all old paint mechanically and/or use Interlux Pintoff 199 or 299 as appropriate. Do not burn off. Proceed as for new work.

NEW WORK:

Fibreglass: Wipe down fibreglass with Interlux Solvent Wash 202. Apply one thin coat of Interlux Fibreglass Primer AL200. Overcoat primer within 2-3 hours, no more, no less. Apply second coat of Interlux Fibreglass Bottomkote observing overcoating times. For osmosis repair and prevention, use the Interlux Interprotect System.

Wood: Sand wood and wipe surface clean. Thin first coat of Interlux Fibreglass Bottomkote 20% with Interlux Special Thinner 216. Apply second coat of Interlux Fibreglass Bottomkote observing overcoating times.

Steel, Lead: Etch by blasting or grinding with 36 grit paper to provide a good profile. Apply 4-5 coats of Interlux Interprotect 2000E. Apply Interlux Fibreglass Bottomkote following the dry times listed below. Apply second coat of Interlux Fibreglass Bottomkote observing overcoating times.

Hours between last coat of

Temperature (°C)	INTERPROTECT 2000E and antifouling paint
10-16 °C	7-9 hours
16-27 °C	5-7 hours
27-33 °C	3-5 hours

Beyond these times, sand with 80 grit paper or apply another coat of INTERPROTECT 2000E before application of the antifouling.

Aluminum: Use Interlux Tri-Lux IIT.

APPLICATION: STIR THOROUGHLY. Apply by brush or roller 2 unthinned coats of Interlux Fibreglass Bottomkote, for best results, 3 coats of Interlux Fibreglass Bottomkote

are recommended. **DO NOT** place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

COVERAGE: 9.5 m² per litre at 50 microns d.f.t. per coat.

CLEAN-UP: Interlux Special Thinner 216.

OVERCOATING TIME: Minimum 2 hours**, recommended 8 hours**, maximum 72 hours**.

IMMERSION: Minimum 4 hours**, recommended 24 hours**, maximum 60 days**.

** N.B.: These are guidelines only. Temperature and humidity affect cure time.

NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by spillage, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill and for clean-up of spills.

PRECAUTIONS: Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical resistant gloves, goggles and footwear, and chemical resistant clothing including hood or hat at all times during handling and application.

- **KEEP OUT OF REACH OF CHILDREN** - Handle with care and mix carefully -
When using, do not eat, drink or smoke - Take a shower immediately after work -
Wear freshly laundered clothes daily - Wash hands and face before eating, drinking,
chewing gum, using tobacco or using the toilet - Store and wash all protective clothing
separately from household laundry - Wash protective clothing in detergent and hot water
before reuse - Use only in well ventilated areas.

FIRST AID: IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

IF INGESTED: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.

Treat symptomatically.

EPA EST. NO. 2693-NJ-1

NOT REGISTERED FOR USE IN THE UNITED STATES OF AMERICA