

2017-0283
2017-09-06

NAUTICAL
EPOXYCOP®

SUSPENSION

POLISHING SMOOTH FINISH

MARINE ANTI-FOULING

BOTTOM PAINT

COMMERCIAL

BLUE/RED/GREEN/BROWN/BLACK

SKIN IRRITANT
EYE IRRITANT
FLAMMABLE

READ THE LABEL BEFORE USING

DANGER

POISON

GUARANTEE: COPPER PRESENT AS CUPROUS OXIDE AND RELATED COPPER
COMPOUNDS.....37.30%

Warning, contains the allergen soy.

REGISTRATION NUMBER 21652 PEST CONTROL PRODUCTS ACT

NET CONTENTS: 1-20 Litres

International Paint LLC
6001 Antoine Drive
Houston, Texas 77091 USA
713-682-1711

PRODUCT DESCRIPTION:

Epoxycop® is performance, value and reliability all in one. Epoxycop provides excellent season long antifouling protection in high fouling areas. The fast dry formula allows the boat to be painted and launched in the same day and can be applied directly over most properly prepared antifouling paints. Epoxycop is recommended for use on the underwater areas of fiberglass, wood, and properly primed metal (except aluminum) boat hulls. It can be used in fresh, salt and brackish waters.

DIRECTIONS FOR USE:

For use on boats or ships only.

NOTE: Colors may fade or change above the waterline. Stir well before and during use, can be applied by brush, or roller. **Do not use on aluminum.**

COMPATIBILITY: Epoxycop can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper.

| | |
|--|--|
| V.O.C.: Less than 408 grams/liter (3.34 lbs. /gal) | THEORETICAL COVERAGE: 9.84 sq. metres/Litre (400 sq. feet/gal at 4.1 mils W.F.T. and 2 mils D.F.T.) |
| CLEAN UP: Acetone or Xylene THINNER: Xylene (thin only when necessary, do not exceed 10% by volume) | APPLICATION TEMPERATURE: 10° C (50° F)* and above (air and hull). |

ESTIMATED DRY TIMES:

| Temperature | Touch Dry | Overcoating Time | Immersion Time | |
|---------------|------------|------------------|----------------|---------|
| | | | Minimum | Maximum |
| °C (°F) | | Minimum | Minimum | Maximum |
| 10° C (50° F) | 3 Hours | 6 Hours | 12 Hours | 60 Days |
| 25° C (77° F) | 1 Hours | 4 Hours | 8 Hours | 60 Days |
| 35° C (95° f) | 30 Minutes | 2 Hours | 6 Hours | 60 Days |

*If the air temperature falls below 10° C (50° F) during the dry time extend the dry times by 12 hours minimum.

PREPARATION/APPLICATION

BARE FIBERGLASS: Scrub the surface thoroughly with a stiff brush using soap and water. Flush with fresh water to remove the soap residue and allow surface to dry. Remove mold release wax and surface contamination by wiping down the surface with Xylene using the two-rag method. Fill any surface imperfections with approved filler for underwater use. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Xylene using the two-rag method. Apply two coats of Epoxytop allowing for appropriate dry times.

PREVIOUSLY PAINTED SURFACE - GOOD CONDITION: Remove all traces of loose paint by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Xylene using the two-rag method before and after sanding. Apply two coats of Epoxytop allowing for appropriate dry times.

PREVIOUSLY PAINTED SURFACE - POOR CONDITION: Completely remove old antifouling paint, after all old antifouling paint has been completely removed, sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Xylene using the two-rag method before and after sanding. Apply two coats of Epoxytop allowing for appropriate dry times.

BARE WOOD: Sand the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean with Xylene using the two-rag method before and after sanding. Apply the first coat of Epoxytop thinned 10% with Xylene. Apply two finish coats of Epoxytop allowing for appropriate dry times.

UNDERWATER METALS: Apply an approved underwater metal primer as per manufacturer's instructions. Apply two coats of Epoxytop allowing for appropriate dry times. **Do not use on aluminum.**

MAINTENANCE

Antifoulings are not effective under all conditions. Pollution, usage and natural occurrences can adversely affect an antifouling paint's performance. Therefore, we strongly suggest that the antifouling paints are checked regularly to make sure it is clean and that no growth is occurring. The less a boat is used, and the longer the idle periods are the higher the chance of fouling. Properly functioning antifouling paints will repel hard growth and requires only occasional light wiping with a soft cloth or Scotch-Brite™ pad to remove slime. Aggressive cleaning of antifouling paints, using tools such as scrubbing pads and brushes, will shorten the effective life of the paint, and should only be used if necessary.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint LLC including surface preparation, proper application, and environmental conditions. Therefore, International Paint LLC cannot guarantee this product's suitability for your particular purpose of application. **IMPLIED WARRANTIES OF FITNESS FOR A PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT LLC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.** By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint LLC's option.

DO NOT place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

DO NOT apply this product in a way that will contact workers or bystanders, either directly or through drift. Only protected handlers may be in the area during application.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats.

DO NOT discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified by suitable means.

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

Hazardous to Humans and Domestic Animals

WARNING

USE AN AIR-FED RESPIRATOR WITH A FULL FACE MASK DURING HANDLING AND APPLICATION. WEAR LONG PANTS, A LONG-SLEEVED SHIRT AND SHOES PLUS SOCKS, CHEMICAL RESISTANT GLOVES, GOGGLES AND FOOTWEAR, AND CHEMICAL RESISTANT CLOTHING INCLUDING HOOD OR HAT AT ALL TIMES DURING HANDLING, APPLYING AND MIXING/LOADING.

Handle with care and mix only in a closed container.

Use only in well ventilated areas.

When using, do not eat, drink or smoke.

Take a shower immediately after work.

Wear freshly laundered clothes daily.

Wash hands and face before eating, drinking, chewing gum, using tobacco or using the toilet.

Store and wash all protective clothing separately from household laundry.

Wash protective clothing in detergent and hot water before reuse.

Remove personal protective equipment immediately after handling this product.

As soon as possible, wash thoroughly and change into clean clothing.

Remove clothing/personal protective equipment immediately if pesticide gets inside.

Then wash thoroughly and put on clean clothing.

Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them.

Wash the outside of gloves before removing.

Wear long pants, a long-sleeved shirt and shoes plus socks during clean-up and repair.

ENVIRONMENTAL HAZARDS:

Toxic to aquatic organisms. Do not contaminate water. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL:

Do not reuse empty containers for any purpose. Dispose of empty containers and paint debris in accordance with provincial requirements. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

PHYSICAL OR CHEMICAL HAZARD

COMBUSTIBLE. Do not use or store near heat or open flame.

FIRST AID:

If swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give **any** liquid to the person. Do not give anything by mouth to an unconscious person.

If in eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

If inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION:

Contains petroleum distillates and copper compounds. Do not induce vomiting due to danger of aspiration into lungs. Exposure to vapours, mist or dust can cause irritation of respiratory tract, dizziness, fatigue, copper fume fever, liver and kidney disease and blood disorders. Lung disorders (asthma-like conditions) may be aggravated by breathing vapours, mists or dusts. Avoid alcohol. Treat symptomatically.

NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offence under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.