

2017-1728
2017-10-31

➤ Center Panel

HEMPEL'S ANTIFOULING OLYMPIC
7660 - 1999 Black

ANTI-FOULING PAINT
SUSPENSION

READ THE LABEL BEFORE USING

(below symbol)
CAUTION
FLAMMABLE
EYE IRRITANT

COMMERCIAL

(below symbol)
DANGER
POISON
SKIN IRRITANT

Lot Number:
XXXXXXXX

GUARANTEE: WEIGHT PERCENT
CUPROUS OXIDE 45.31%
COPPER (ELEMENTAL) 40.24%

REGISTRATION No. 21658
PEST CONTROL PRODUCTS ACT

NET CONTENTS: 18.9 Liters (5 US Gallons)

FOR USE ON BOATS OR SHIPS ONLY

HEMPEL (CANADA) INC.
Unit 111-19097 26th Avenue,
Surrey BC V3S 3V7

Tel: (604) 536-4275
Toll Free: 1-800-661-3201

>>Left Panel

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN

Use only in well ventilated areas.

HANDLE WITH CARE AND MIX ONLY IN A CLOSED CONTAINER

HANDLING: Use an air-fed respirator with a full face mask during handling and applying. Wear chemical resistant gloves and footwear, and chemical resistant clothing with head covering at all times during handling and applying. Wear long pants, a long-sleeved shirt and shoes plus socks during mixing/loading, application, clean-up and repair. Wash the outside of gloves before removing. Remove personal protective equipment immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Take shower immediately after work. Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Wear fresh laundered clothes daily. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them. For cleaning/maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry. When using, do not eat, drink or smoke. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL:

1. Triple or pressure-rinse the empty container. Add rinsings to the spray mixture in the tank.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

FIRST AID:

If Swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

If In Eyes: Hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

If On Skin Or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: This product contains petroleum distillates and there is no antidote for solvent ingestion. Drinking or ingestion of this product could cause serious injury or death. Treatment is symptomatic. Vomiting may cause aspiration pneumonia.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

NOTICE TO USER:

This pest control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

➤ Right Panel

HEMPEL'S ANTIFOULING OLYMPIC 7660 – 1999 Black is an advanced ablative antifouling paint containing cuprous oxide for the prevention of barnacles, algae, coral and other sessile marine fouling organisms. Recommended for the underwater surfaces of fiberglass, steel or wood vessels operated in all coastal and oceanic waters. DO NOT USE on aluminum.

DIRECTIONS FOR USE:

SURFACE PREPARATION:

Existing antifouling: Hempel's Antifouling Olympic 7660 – 1999 Black is only compatible with self-polishing ablative or hard type antifouling (Consult Hempel's representative). High pressure fresh water wash to remove any marine growth and depleted antifouling. Allow to dry thoroughly before painting.

Wood: Ensure surface is oil and dust free. Apply one coat thinned 25 % with Hempel's Thinner 08080 then apply additional coats without thinning.

Steel: Grit blast to SSPC-SP 6 Commercial blast. Ensure surface is grease, oil and dust free and dry. Apply proper underwater anticorrosive primer (Consult Hempel's representative).

Fiberglass: Remove mold release agent, wax, oil or grease by solvent washing with rags soaked with Hempel's Thinner 08080. Sand lightly. Ensure surface is dust free and dry.

APPLICATION INSTRUCTIONS: Stir thoroughly and apply one, preferably two coats, over properly prepared surface. Film thickness depends upon hull condition, trading pattern, and extended service life (Consult Hempel's representative).

DO NOT apply this product in a way that will contact workers or bystanders, either directly or through drift. Only protected handlers may be in the area during application.

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats.

DO NOT discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified by suitable means.

DO NOT place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

Allow minimum 12 hours at 20°C/68°F between coats of Hempel's Antifouling Olympic 7660 – 1999 Black.

Vessel may be floated after minimum 12 hours at 20°C/68°F. Withstands atmospheric exposure up to one month.

If thinning is required for brush, roller or spray application, use Hempel's Thinner 08080.

Spray equipment should be promptly cleaned with Hempel's Thinner 08080 or Hempel's Tool Cleaner 99610 after use.

Large vessels (i.e. over 25 m / 80 ft.) must be treated by a trained applicator.

FOR COMPLETE PROTECTION, READ THE HEALTH AND MATERIAL SAFETY DATA SHEET