

2017-0292
2017-09-21

MICRON CSC (VARIOUS COLOURS)
ANTIFOULING PAINT

DOMESTIC

SUSPENSION

KEEP OUT OF REACH OF CHILDREN

IMPORTANT

READ THE LABEL BEFORE USING.

FOR USE ON BOATS ONLY.

SKIN AND EYE IRRITANT.

NOT FOR SPRAY USE.

ONLY BRUSH OR ROLLER APPLICATION.

GUARANTEE: CUPROUS OXIDE 36.00%

COPPER (AS ELEMENTAL) 33.00%

REGISTRATION NO. 21351.

PEST CONTROL PRODUCTS ACT.

3.78 L

(Blue, Green, Red, Black, Brown)

CAUTION

FLAMMABLE

DANGER

POISON

International Paint LLC, 6001 Antoine Drive, Houston, Texas 77091 USA
713-682-1711

MICRON CSC
Controlled Solubility Copolymer Antifouling Paint

DIRECTIONS FOR USE:

For all types of fiberglass, wood, and steel boats. Formulated with an innovative copper copolymer system. Performance is directly proportional to the amount of Micron CSC applied, and vessels using it regularly experience optimal performance.

SURFACE PREPARATION: If previous antifouling paint is a hard type and in good condition, wash down with fresh water, degrease with Interlux Brushing Liquid 333 if required, sand surface lightly and use Micron CSC as directed. Otherwise, remove all old paint mechanically and/or use Interlux Pintoff 199 or 299 as appropriate. Do not burn off. Proceed as for new work.

NEW WORK:

Fiberglass: Wipe down fiberglass with Interlux Solvent Wash 202. Apply one thin coat of Interlux Fiberglass Primer AL200. Overcoat primer within 2-3 hours, no more, no less. Apply second coat of Micron CSC observing overcoating times. For osmosis repair and prevention, use the Interlux Interprotect System.

Wood: Sand wood and wipe surface clean. Thin first coat of Micron CSC 20% with Interlux Thinner 433 or 216. Apply second coat of Micron CSC observing overcoating times.

Steel, Lead: Etch by blasting or grinding with 36 grit paper to provide a good profile. Apply 4-5 coats of Interlux Interprotect 2000E. Apply Micron CSC following the dry times listed below. Apply second coat of Micron CSC observing overcoating times.

Hours between last coat of

Temperature (°C)	INTERPROTECT 2000E and antifouling paint
10-16 °C	7-9 hours
16-27 °C	5-7 hours
27-33 °C	3-5 hours

Beyond these times, sand with 80 grit paper or apply another coat of INTERPROTECT 2000E before application of the antifouling paint.

Aluminum: Use Interlux Tri-Lux IIT.

APPLICATION: STIR THOROUGHLY. Apply by brush or roller at least two unthinned heavy coats of Micron CSC. Use Interlux Brush-Ease 433 only if brush pulls or roller drags. Important: Success depends on initial film thickness applied.

COVERAGE: 7.5 m² per litre at 50 microns d.f.t. per coat.

CLEAN-UP: Interlux Brush-Ease 433 or Interlux Special Thinner 216.

DRYING: Touch dry: 2 hours**.

OVERCOATING TIME: Recommended minimum 16 hours**, maximum 2 months**.

IMMERSION: Minimum 24 hours**, maximum 2 months**.

* After a long layup period, MICRON CSC should be lightly scrubbed using fresh water and a soft bristle brush.

** N.B.: These are guidelines only. Temperature and humidity affect cure time.

LIMITATION: Please be aware Shark White may change colour at the waterline.

DO NOT place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

NOTICE TO USER: This control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by spillage, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL: Do not re-use container for any purpose. Dispose of empty container and paint debris in accordance with provincial requirements. For information on the disposal of unused, unwanted product, and the clean-up of spills, contact the manufacturer or the Provincial Regulatory Agency.

PRECAUTIONS: Keep away from heat, sparks and flame. Vapours heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical resistant gloves, goggles and footwear, and chemical resistant clothing including hood or hat at all times during handling and application.

- KEEP OUT OF REACH OF CHILDREN - Handle with care and mix carefully -
When using, do not eat, drink or smoke - Take a shower immediately after work -
Wear freshly laundered clothes daily - Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet - Store and wash all protective clothing separately from household laundry - Wash protective clothing in detergent and hot water before reuse - Use only in well ventilated areas.

FIRST AID: IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice. IF SWALLOWED: Call a poison control centre or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give anything by mouth to an unconscious person. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion.

Treat symptomatically.

EPA EST. NO. 2693-NJ-1

NOT REGISTERED FOR USE IN THE UNITED STATES OF AMERICA