

2016-7915
2017-06-29

Atlantic Antifouling Paint Copper Bottom Red

GUARANTEE: Copper as elemental present as cuprous oxide...8.78%

REGISTRATION NUMBER 23511 – PEST CONTROL PRODUCTS ACT.

Warning: Contains the allergen soy.
COMMERCIAL
Suspension

READ THE LABEL BEFORE USING

DANGER



POISON

FLAMMABLE

EYE AND SKIN IRRITANT

3,78L

Société Laurentide Inc

4600 Boulevard de Shawinigan-Sud, Shawinigan-Sud, Quebec G9N 6T5
1 888 537-5925
www.laurentide.biz

Alkyd paint for boats and rowboats constructed of wood, metal or fibreglass. In saltwater, use this Antifouling Paint below the water line to prevent the growth of barnacles and marine micro-organisms on the hull.

DIRECTIONS FOR USE

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs, wetland or estuary/marine habitats. **DO NOT** apply this product in a manner that would put workers or people nearby in contact with it, either directly or indirectly. Only people wearing protective clothing and equipment should enter the painting area during application. **DO**

2016-7915

2017-06-29

NOT contaminate drinking water sources, irrigation water or wetland habitats during cleaning of the equipment or elimination of waste.

DO NOT discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified by suitable means.

DO NOT place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

SURFACE PREPARATION: The surface must be clean, dry and free from all contaminants (oil, grease, rust, etc.) and flaking paint.

RECOMMENDED PRIMERS

- New wood: Prime Time Undercoater 1242-05
- New steel: Duro-Sol Primer 8545-69 (red oxide)
- Fibreglass: Duro-Sol Fibreglass Primer 8545-05
- Painted surfaces: Clean surfaces carefully. Use a wire brush to remove rust and flaking paint. Lightly sand glossy surfaces. Wipe sanding residue. Prime bare spots like new surfaces.

APPLICATION: Mix thoroughly and apply as is with a brush or roller. For spraying application, add 250 mL of Chem-sol 545-153 at 3.78 Liters of paint. Apply thin, even coats. Temperature must be between 10°C and 32°C. Vessels over 25 metres must be treated by trained applicators.

THINNER AND CLEANER

Chem-Sol 545-153.

DRYING TIME

Allow a minimum of 16 hours between each coat and 48 hours before immersing in water.

COVERAGE

Approximately 9 m²/L (100 sq. ft./L).

Satisfaction guaranteed: If this product has been used as directed, and you are not completely satisfied with it, **Soci t  Laurentide Inc.** pledges to replace it or reimburse the buyer for the cost of this product. *Please note: This warranty does not cover any expenses other than product replacement cost.*

Made in Canada

PRECAUTIONS:

KEEP OUT OF THE REACH OF CHILDREN

Causes eye and skin irritation. **DO NOT** get in eyes or skin. Harmful or fatal if swallowed. May be fatal if inhaled. Avoid inhaling/breathing in sprays or fumes. Remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing. Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Discard

2016-7915

2017-06-29

clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them. For cleaning/maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry. Wash hands before eating, drinking, chewing gum, smoking or using the toilet. Use an air assisted respirator mask that completely covers the entire face during handling and application. Wear long pants, a long-sleeved shirt and clothing resistant to chemicals. Gloves, a cap, socks and shoes should also be worn while mixing, applying, loading, cleaning or repairing this product.

- Handle with care and mix only in a closed container.
- Use only in a well ventilated location.
- Do not eat, drink or smoke during use.
- Wear long pants, a long-sleeved shirt, shoes and socks during mixing/loading, application, clean up and repair.

FIRST AID:

In case of contact with skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice

In case of contact with eyes: Hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice..

If swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give **any** liquid to the person. Do not give anything by mouth to an unconscious person.

In case of inhalation: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

Take the container label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION:

Contains petroleum distillate - vomiting may cause aspiration pneumonia. Treat symptomatically. Pre-existing lung disease may be aggravated by regular exposure. Excessive exposure may lead to chronic respiratory disease.

NOTICE TO USER:

This pest control product is to be used only in accordance with the directions on the label. It is an offence under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

ENVIRONMENTAL HAZARD:

Toxic to aquatic organisms. Do not contaminate the water. Do not discharge directly into the water by washing equipment or disposing of waste in the water. When removing paint, do not allow flakes or dust to fall into the water.

2016-7915
2017-06-29

DISPOSAL:

1. Triple or pressure-rinse the empty container. Add the rinsing to the treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean up of spills.