

2015-0036
2015-04-16

EC6112A Biocide

SOLUTION

A MICROBIOCIDIC FOR USE IN CONTROLLING SULFATE - REDUCING BACTERIA AND SLIME- FORMING BACTERIA IN OIL WELL DRILLING, OIL FIELD PROCESSING APPLICATIONS, AND OIL FIELD WATER SYSTEMS, SUCH AS STEAM-INJECTION WATER HOLDING TANKS, FLOOD WATER, INJECTION WATER, HOLDING POND WATER, DISPOSAL - WELL WATER, AND WATER HOLDING TANKS

COMMERCIAL
DANGER

CORROSIVE

POISON

READ THE LABEL BEFORE USING

REGISTRATION NO.: 25806
PEST CONTROL PRODUCTS ACT

KEEP OUT OF REACH OF CHILDREN

GUARANTEE:
Glutaraldehyde 50.0%

Net Contents:

Nalco Canada ULC
1055 Truman St./P.O. Box 5002
Burlington, Ontario
L7R 3Y9
TEL: (905) 632-8791

**PHONE IN CASE OF EMERGENCY:
CANADA 1-800-463-3216 (24 HOURS)
CANUTEC: 1-613-996-6666 (24HOURS)**

PRECAUTIONS:

DANGER. KEEP OUT OF REACH OF CHILDREN.

Corrosive. Causes irreversible eye damage. Causes skin burns. Harmful if inhaled. Harmful or fatal if swallowed. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyperreactive individuals. Do not get in eyes, on skin, on clothing. Do not inhale fumes or vapour. Do not swallow.

Wear coveralls over long-sleeved shirt and long pants, chemical-resistant gloves, socks, chemical-resistant footwear, and eye protection during mixing, loading, application, clean-up and repair. Wash thoroughly with soap and water after handling. Use only in well ventilated area. Remove contaminated clothing and shoes and wash them before reuse.

TOXICOLOGICAL INFORMATION:

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

FIRST AID:

IF IN EYES, hold eye open and rinse slowly and gently with water for 15–20 minutes.

Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.

Call a poison control centre or doctor for treatment advice.

IF ON SKIN OR CLOTHING, take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice.

IF INHALED, move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

IF SWALLOWED, call a poison control centre or doctor immediately for treatment advice.

Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not

give any liquid to the person. Do not give anything by mouth to an unconscious person.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

DIRECTIONS FOR USE:

DO NOT open pour more than 20 L of concentrate per day. Use an automatic addition system if using more than 20 L of concentrate per day. DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes. DO NOT discharge effluent containing this product into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters.

WATER FLOODS: EC6112A Biocide should be added to a water flood system at a point of uniform mixing.

Initial treatment: When the system is noticeably contaminated, add 100 - 5000 ppm EC6112A Biocide to the system (0.1 Litres to 5 Litres EC6112A Biocide per 1000 L of flood water). Repeat until control is achieved.

Subsequent dose: When microbial control is evident, add 20 - 5000 ppm EC6112A Biocide (0.02 L to 5 L of EC6112A Biocide per 1000 L of flood water) to the system weekly, or as needed to maintain control.

DRILLING MUDS/DRILLING COMPLETION, WORKOVER FLUIDS: EC6112A Biocide should be added to a drilling fluid system at a point of uniform mixing such as the circulating mud tank. Initial Treatment: Add 50 - 1000 ppm EC6112A Biocide (0.8 L to 15.1 L EC6112A per 100 barrels of fluids) to a freshly prepared drilling fluid, depending on the severity of contamination. Maintenance Dosage: Maintain a concentration of 50 to 1000 ppm EC6112A Biocide by adding 0.8 L to 15.1 L of EC6112A Biocide per 100 barrels of fluid, as needed, depending on the severity of contamination.

PACKER FLUIDS: EC6112A Biocide should be added to a packer fluid at a point of uniform mixing such as circulating holding tank. Add 50 – 600 ppm EC6112A Biocide (0.8 L to 9.5 L EC6112A Biocide per 100 barrels of fluid) to a freshly prepared fluid, depending on the severity of contamination. Seal the treated packer fluid in the wall between the casing and production tube.

GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS: EC6112A Biocide should be added to a gas production or transmission line via direct injection. The application should be conducted to ensure maximum distribution of EC6112A Biocide through the entire internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline. Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates. To facilitate application it may be desirable to dilute the EC6112A Biocide with the appropriate solvent immediately before use. The concentration in the solvent should not fall below the 500 to 5000 ppm range. Injections to the system should be made on a weekly basis, or as needed to maintain control.

GAS STORAGE WELL AND SYSTEMS: Individual injection wells should be treated with sufficient quantity of EC6112A Biocide to produce a concentration of 500 to 5000 ppm EC6112A Biocide when diluted by the water present in the formation. Injection should take place before gas is injected (during the summer). Injections should be repeated yearly, or as needed to maintain control. Individual drips should be treated with a sufficient quantity of EC6112A Biocide to produce a concentration of 200 to 2000 ppm EC6112A Biocide when diluted by the water present in the drip. Injections should be repeated yearly, or as needed to maintain control.

HYDROTESTING: Water used to hydrotest pipelines or vessels should contain 100 to 4000 ppm EC6112A Biocide (0.1 L to 4 L EC6112A Biocide per 1000 L water), depending on water quality and length of time the equipment will remain idle.

PIPELINE PIGGING AND SCRAPING OPERATION: Add EC6112A Biocide to a slug of water immediately following the scraper (ideally this water volume can be kept to a minimum and contained between the scraper

and a trailing pig). Sufficient EC6112A Biocide should be added to produce a concentration of 0.1% to 1% (0.1 L to 1 L EC6112A Biocide per 100 L water), depending on the length of the pipeline and the severity of biofouling.

ENVIRONMENTAL HAZARDS:

Toxic to aquatic organisms.

STORAGE:

To prevent contamination store this product away from food or feed.

DISPOSAL:

For Porta-Feed System: 1. Close valve. 2. The Porta-Feed System may be returned to the point of purchase (distributor/dealer). It must be refilled by the distributor/dealer with the same product. Do not reuse the Porta-Feed System for any other purpose.

For Other Containers: 1. Triple – or pressure – rinse the empty container. Add the rinsings to the treatment site. 2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal. 3. Make the empty container unsuitable for further use. 4. Dispose of the container in accordance with provincial requirements. 5.

For information on the disposal of unused, unwanted product, contact the manufacturer or the Provincial Regulatory Agency. Contact the Manufacturer and the Provincial Regulatory Agency in case of spill and for cleanup of spills.

NOTICE TO USER:

This pest control product is to be used only in accordance with the directions on the label. It is an offence under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

Lot No.:

TDG Shipping Name: CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S (GLUTARALDEHYDE), UN3265, CLASS: 8, PKG GRP: II

01/10

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.