

2017-0251  
2017-09-20

INTERCLENE 140 BWA 360 ANTIFOULING RED

SOLUTION

READ THE LABEL BEFORE USING

FOR COMMERCIAL USE ONLY

SKIN AND EYE IRRITANT

NOT REGISTERED FOR USE IN THE UNITED STATES OF AMERICA

EPA EST. NO. 2693-NJ-1

PIN NO. 1263 Paint

FLASH POINT 32°C

US463018 5

DANGER

POISON

CAUTION

FLAMMABLE

NET CONTENTS : 18.93 L

GUARANTEE

Cuprous Oxide (present as elemental copper) 33.93%

FOR USE ON BOATS ONLY

REGISTRATION NO. 24390 PEST CONTROL PRODUCTS ACT

BE RESPONSIBLE...PROTECT OUR ENVIRONMENT

International Paint LLC, 6001 Antoine Drive, Houston, Texas 77091 USA 713-682-1711

International Paints (Canada) Limited

1405 55<sup>th</sup> Avenue, Dorval, Québec H9P 2W3 (514) 631-8686

2017-0251  
2017-09-20

**NOTICE TO USER:**

This pest control product is to be used only in accordance with the directions on the label. It is an offence under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

**ENVIRONMENTAL HAZARDS:**

Toxic to aquatic organisms. Do not contaminate water by spillage, overspray, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

**DISPOSAL :** 1. Triple- or pressure-rinse the empty container. Add the rinsings to the spray mixture in the tank. 2. Follow provincial instruction for any required additional cleaning of the container prior to its disposal. 3. Make the empty container unsuitable for further use. 4. Dispose of the container in accordance with provincial requirements. 5. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

**PRECAUTIONS :** KEEP OUT OF REACH OF CHILDREN. This product contains xylene at 7.61% which requires further toxicological testing. Keep away from heat, sparks and flame. Vapors heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours or spray mist. Use an air-fed respirator with a full face mask during handling and applying. Wear long pants, a long-sleeved shirt and shoes plus socks, chemical resistant gloves, goggles, and chemical resistant clothing including hood or hat at all times during handling, applying and mixing/loading.

Handle with care and mix only in a closed container. Use only in well ventilated areas. Remove personal protective equipment immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Take a shower immediately after work. Wear freshly laundered clothes daily. Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them. For cleaning/maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry. When using, do not eat, drink or smoke. Wash hands and face before eating, drinking, chewing gum, using tobacco or using the toilet. Wash the outside of gloves before removing. Wear long pants, a long-sleeved shirt and shoes plus socks during clean-up and repair.

**FIRST AID**

**IF SWALLOWED:** Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give **any** liquid to the person. Do not give anything by mouth to an unconscious person.

2017-0251  
2017-09-20

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

### **TOXICOLOGICAL INFORMATION**

Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia. Treat symptomatically.

### **DIRECTIONS FOR USE**

#### **GENERAL DESCRIPTION**

This product is an antifouling protective coating resistant to algae, barnacles and other marine fouling in fresh, sea and brackish water on steel boat hulls. This product is for commercial use.

#### **SURFACE PREPARATION AND COMPATIBILITY**

Surface preparation directions must be followed exactly in order to ensure adhesion. The surface must always be clean and dry prior to painting.

#### **GENERAL APPLICATION PROCEDURES**

Airless spray is recommended : tip size 533-660 microns. Pump ration of 30 :1 or greater. For small areas, brush or roller may be used. But multiple coats may be required to achieve the required film thickness. It is recommended to apply by airless spray one (1) or two (2) full coats of this product.

#### **MIXING AND THINNING INSTRUCTIONS**

Mix thoroughly with power prior to application. This coating is designed to be applied without thinning. Should thinning be necessary, consult your International representative prior to altering this coating.

#### **CLEAN-UP**

For tools, equipment, etc. use INTERNATIONAL GTA007.

#### **MINIMUM DRY AND LAUNCHING TIMES**

Minimum drying time between coats is 8 hours, and before launching is 24 hours depending on the paint thickness at a temperature of 23°C.

#### **THEORETICAL COVERAGE**

12.4m<sup>2</sup>/litre, per coat at 2.0 mils D.F.T. Consult your International representative for practical application coverage.

2017-0251  
2017-09-20

## **APPLICATIONS SYSTEMS EXISTING**

### **ANTIFOULING SYSTEMS**

#### **GOOD CONDITION**

High pressure fresh water wash with a minimum of 17,500kPa and/or scrape to remove all marine growth, slime, salts etc. Spot blast all areas of corrosion to a Near White Metal Standard SSPC-SP10-85. Blow down with clean dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

#### **POOR HULL CONDITIONS**

For « optimum » results, blast entire area to Near White Metal Standard SSPC-SP-10-85. Apply an approved underwater anticorrosive system.

#### **NEW SHIP CONSTRUCTION**

Blast entire area to a Near White Metal Standard SSPC-SP-10-85. Blow down with clean and dry pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

**DO NOT** place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

**DO NOT** apply this product in a way that will contact worker or bystanders, either directly or through drift. Only protected handlers may be in the area during application.

**DO NOT** contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

**DO NOT** apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs and wetlands), or estuarine/marine habitats.

**DO NOT** discharge effluent containing this product or the biocide produced into sewer systems, lakes, streams, ponds, estuaries, oceans or other waters unless the effluent has been detoxified by suitable means