

2018-0703
2018-10-10

Kop-Coat, Inc.

NP-2[®] SAPSTAIN CONTROL CHEMICAL

READ THE LABEL BEFORE USING
COMMERCIAL
SOLUTION

Aids in the control of blue stain, mould and decay of freshly cut lumber when properly used. Effective on softwoods including Douglas fir, White fir, Spruce, Hemlock, Pines (including Southern and Western Yellow and Eastern and Western White species), as well as many hardwoods.

DANGER POISON

DANGER CORROSIVE TO EYES AND SKIN

KEEP OUT OF THE REACH OF CHILDREN

ACTIVE INGREDIENT:

DIDECYL DIMETHYL AMMONIUM CHLORIDE ...70.48%
3-iodo-2-propynyl butyl carbamate.....4.76%

REGISTRATION NUMBER 26985

For product Emergencies: 1-800-548-0489

Kop-Coat, Inc.
Protection Products Division
5137 Southwest Avenue,
St. Louis, MO 63110 USA
(314)772-2200

Kop-Coat Inc.
3040 William Pitt Way
Pittsburgh, PA 15238 USA
412-826-3323

NET CONTENTS LITERS

2018-0703
2018-10-10

Note: For Further information on the storage, handling, use and disposal of NP-2, contact Kop-Coat and refer to BC Environment and Environment Canada's publication "Antisapstain Wood Protection- Recommendations for Design and Operation", May 1994.

For Industrial Use Only

DIRECTIONS FOR USE:

Use Limitations:

1. Treated wood is not to be used for construction of food handling containers, food storage facilities or food growing buildings (e.g. mushroom houses).
2. Do not use in drive-through dip tanks.
3. This product can only be applied by spraybox application technology (i.e. linear, transverse or car wash spray boxes) or diptank application technology.

Dilute Before Using

For the best results lumber should be treated immediately after it is sawn. A delay in treatment of 24 hours or more permits the start of stain, mould and decay growth which subsequently requires a stronger treatment to achieve control of surface growth. Delayed application and log borne infection can result in internal stain often under a bright surface. Freshly dipped or sprayed lumber should be protected from rain washing. Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of the antistain solution. Antistain treatment concentrations must be geared to achieve protection of the thickest or most valuable item being treated. The concentration of the ready-to-use anti-stain solution must be adjusted to accommodate seasonal changes in the exposure and species being treated. Dip tanks and spray equipment must be properly maintained. Spray boxes must be equipped with mechanical means of preventing the escape of droplets or entrained aerosols.

Mixing Instructions

Mix this concentrate with water, as per dilution below, to protect lumber against sapstaining organisms during protracted periods of storage and transit. Dilution rates will be influenced by seasonal conditions, exposure during storage and transit, treating methods and wood species. The operational target deposition level of NP-2[®] Sapstain Control Chemical on the surface of treated lumber is 80-100 micrograms/cm² of active ingredients. This should be verified periodically using available analytical quality control techniques. (Contact Kop-Coat, Inc. for further information).

Dilution rates:

For spray applications, mix one litre of this concentrate per 15-100 litres of water.

For dip applications, mix one litre of this concentrate per 55-100 litres of water.

Lumber and logs should be totally immersed or sprayed so as to ensure that all surfaces are treated. Put about 1/3 of the water to be used in the mixing tank. Add the correct amount of this product and then rinse the container into the tank. Add the balance of water needed and mix thoroughly. In a dipping process, the agitation resulting from the movement of the wood will be sufficient to ensure a good mix. On standing unused for a period, mix thoroughly before use. When using proportioning pumps for mixing, this product should be maintained at temperatures above 10 degrees C to prevent inaccurate mixing due to viscosity changes. Minor proportioning rate changes can be affected by changing the setting of the pump dial.

NOTE: With normal dip or spray application long term control of decay cannot be achieved. This product is designed to provide blue stain, mould and decay control during storage and in transit.

NOTICE TO USER: This pest control product is to be used only in accordance with the directions of the label. It is an offence under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label.

PRECAUTIONS

CONCENTRATE IS FATAL IF SWALLOWED, INHALED OR ABSORBED THROUGH THE SKIN. CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE AND SEVERE SKIN BURNS. PROLONGED OR FREQUENTLY REPEATED SKIN CONTACT MAY CAUSE ALLERGIC REACTIONS IN SOME INDIVIDUALS. KEEP OUT OF REACH OF CHILDREN.

2018-0703
2018-10-10

- Wear chemical-resistant coveralls over long-sleeved and long pants, chemical-resistant gloves, goggles or face shield, socks, and chemical-resistant footwear when handling the concentrate or during mixing/loading, clean-up, maintenance and repair activities.
- Use a NIOSH-respirator if the area is not well ventilated or if airborne exposure levels are above the occupational exposure limit(s), as determined by air sampling.
- Use a NIOSH-respirator during clean-up, maintenance and repair activities when working in/on application equipment or if airborne material (e.g. dust, mist/spray) may be generated when working in the treatment area.
- When piling freshly treated lumber, handling treated lumber that has not fully dried, or if there is a potential for getting wet by the treating solution during other activities in the sawmill, wear chemical-resistant coveralls or chemical-resistant apron over long-sleeved shirt and long pants, chemical-resistant globes, socks and chemical-resistant footwear.
- When working in the dip or spray area, wear long sleeved shirt, long pants, chemical-resistant gloves, socks and boots. Wear goggles or face shield if there is a possibility of splashing. Once dry, the treated wood can be handled with cotton or leather gloves.
- Wash hands and face before eating, drinking, smoking and using the toilet. Change clothes daily. Was contaminated clothing separately from household laundry. Not for use or storage in or around the house. Clean contaminated equipment thoroughly prior to making welding repairs.

FIRST AID

If Swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

If In Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

If On Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice.

If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia. Treat symptomatically.

PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE. Do NOT use, pour, spill or store near heat or open flame.

IN CASE OF FIRE: Use dry chemicals, foam, water fog or CO₂. Cool closed containers with water.

ENVIRONMENTAL PRECAUTIONS:

I. TOXIC to aquatic organisms.

II. DIRECTIONS FOR USE:

DO NOT contaminate irrigation or drinking water supplies or aquatic habitats by cleaning of equipment or disposal of wastes.

This product is TOXIC to aquatic organisms. It is not to be used in circumstances that would cause or allow it to enter lakes, streams, ponds, estuaries, oceans or other waters in contravention of federal or provincial regulatory requirements. The requirements of applicable laws should be determined before using this product.

Dip tanks and drip aprons must be roofed, paved and drained to prevent dilution and loss of treatment solution.

2018-0703
2018-10-10

Store treated lumber on a roofed drip pad until dripping has ceased. Slope lumber on the drip pad to expedite drainage and to ensure that no puddles remain on the surface of the wood. Manage drippage and other related wastes to prevent release in the environment.

DO NOT expose treated lumber to rains immediately after treatment.

For further information on storage, handling, and disposal of treated wood, contact the manufacturer of this product or the provincial regulatory agency.

III. STORAGE:

To prevent contamination store this product away from food or feed.

IV. DISPOSAL:

For recyclable containers:

DO NOT reuse this container for any other purpose. This is a recyclable container, and is to be disposed of at a container collection site. Contact your local distributor or municipality for the location of the nearest collection site. Before taking the container to the collection site:

1. Triple-or pressure-rinse the empty container. Dispose of the rinsings in accordance with provincial requirements.
2. Make the empty, rinsed container unsuitable for further use.

If there is no container collection site in your area, dispose of the container in accordance with provincial requirements.

For information or disposal of unused, unwanted product, or in the case of a spill or spill clean-up, contact the manufacturer or the provincial regulatory agency.

This product is toxic to domestic animals. Treated sawdust, shavings and residues of the treatment process should be disposed of properly and should not come in contact with domestic animals or be used as bedding or litter.