

2017-0247  
2017-07-26

VINY-LUX (Black, Green, Blue)

VINYL ANTIFOULING PAINT

DOMESTIC

SUSPENSION

KEEP OUT OF REACH OF CHILDREN

**IMPORTANT**

READ THE LABEL BEFORE USING.

FOR USE ON BOATS ONLY.

SKIN AND EYE IRRITANT.

NOT FOR SPRAY USE.

ONLY BRUSH OR ROLLER APPLICATION.

GUARANTEE: CUPROUS OXIDE 33.78%

COPPER (AS ELEMENTAL) 30.00%

REGISTRATION NO. 27574

PEST CONTROL PRODUCTS ACT

CAUTION

FLAMMABLE

DANGER

POISON

NET CONTENTS:

International Paint LLC, 6001 Antoine Drive, Houston, Texas 77091, USA  
713-682-1711

VINY-LUX  
Vinyl Based Copper Antifouling Paint

DIRECTIONS FOR USE:

For all types of fiberglass, wood, and steel boats. Specially formulated for racing boats used extensively in areas of heavy fouling. VINY-LUX offers a hard, abrasion resistant surface and burnishes to a slick racing finish.

**SURFACE PREPARATION:** If previous antifouling paint is vinyl based and in good condition, wash down with fresh water, degrease with INTERLUX BRUSHING LIQUID 333 if required, and use VINY-LUX as directed. Otherwise, remove all old paint mechanically and/or use INTERLUX PINTOFF 199 or 299 as appropriate. Do not burn off. Proceed as for new work.

**NEW WORK:**

Fiberglass: Wipe down fiberglass with INTERLUX SOLVENT WASH 202. Apply one thin coat of INTERLUX FIBERGLASS PRIMER AL200. Overcoat primer after an overnight cure. Apply second coat of VINY-LUX observing overcoating times. For osmosis repair and prevention, use the Interlux Interprotect System.

Wood: Sand wood and wipe surface clean. Thin first coat of VINY-LUX 20% with INTERLUX VINY-LUX SOLVENT 355. Apply second coat of VINY-LUX observing overcoating times.

Steel, Lead: Etch by blasting or grinding with 36 grit paper to provide a good profile. Apply 5-6 coats of INTERLUX INTERPROTECT 2000E. Apply VINY-LUX after allowing INTERPROTECT 2000E to cure for 24 hours and sanding with 80 grit production paper. Apply second coat of VINY-LUX observing overcoating times.

Aluminum: Use Interlux Tri-Lux II.

**APPLICATION:** STIR THOROUGHLY. Apply by brush or roller two unthinned coats of VINY-LUX. For best results, 3 coats of VINY-LUX are recommended.

**COVERAGE:** 6.8 m<sup>2</sup> per litre at 50 microns d.f.t. per coat.

**CLEAN-UP:** INTERLUX VINY-LUX SOLVENT 355.

**DRYING:** Touch dry 30 minutes\*\*.

**OVERCOATING TIME:** Minimum 3 hours\*\*, recommended 8 hours\*\*, maximum 6 months\*\*.

**IMMERSION:** Minimum 4 hours\*\*, recommended within 8 weeks\*\*, maximum 6 months\*\*.

\*\* N.B.: These are guidelines only. Temperature and humidity affect cure time.

**DO NOT** place the painted parts in water after painting until the paint is fully cured (see recommended times on the label). It is recommended that you prevent paint chips or dust caused by removing paint from entering water.

**NOTICE TO USER:** This control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

**ENVIRONMENTAL HAZARDS:** Toxic to aquatic organisms. Do not contaminate water by spillage, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

**DISPOSAL:** Do not re-use container for any purpose. Dispose of empty container and paint debris in accordance with provincial requirements. For information on the disposal of unused, unwanted product, and the clean-up of spills, contact the manufacturer or the Provincial Regulatory Agency.

**PRECAUTIONS:** Keep away from heat, sparks and flame. Vapours heavier than air cause health and explosion hazards. Keep containers tightly closed when not in use. Avoid contact with eyes, skin and clothing. Do not breathe vapours. Wear chemical resistant gloves, goggles and footwear, and chemical resistant clothing including hood or hat at all times during handling and application.

- KEEP OUT OF REACH OF CHILDREN - Handle with care and mix carefully -  
When using, do not eat, drink or smoke - Take a shower immediately after work -  
Wear freshly laundered clothes daily - Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet - Store and wash all protective clothing separately from household laundry - Wash protective clothing in detergent and hot water before reuse - Use only in well ventilated areas.

**FIRST AID:** **IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. **IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control centre or doctor for treatment advice. **IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice. **IF SWALLOWED:** Call a poison control centre or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give anything by mouth to an unconscious person. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

**TOXICOLOGICAL INFORMATION:** Ingestion (drinking) of this product could cause serious injury or death. There is no antidote for solvent ingestion. Treat symptomatically.

EPA Est. No. 2693-NJ-1

NOT REGISTERED FOR USE IN THE UNITED STATES OF AMERICA