

# UNEPOXY

## ANTIFOULING FINISH RED

- Economical Antifouling Protection
- Hard Smooth Finish
- Apply Over Most Other Antifouling
- Excellent For Fiberglass, Wood & Steel Boats.

**SKIN IRRITANT  
EYE IRRITANT  
FLAMMABLE**

**READ THE LABEL  
BEFORE USING**

**DANGER POISON**

**CAUTION!** KEEP OUT OF REACH OF CHILDREN.  
See Other Precautions on Back Panel

**NET CONTENTS**

**3.785 LITERS**

### **GUARANTEE**

Copper Present as Cuprous Oxide.....33.3%  
(elemental copper)

REGISTRATION NO. 27443  
PEST CONTROL PRODUCTS ACT

This product contains petroleum distillates.

**FOR USE ON BOATS ONLY  
COMMERCIAL  
MARINE**

Not For Spray Use Only Brush Or Roller  
Application

KOP-COAT, INC.  
PETTIT PAINT BRAND  
36 PINE STREET  
ROCKAWAY, NJ 07866  
MADE IN THE U.S.A.

An **RPM** Company

# UNEPOXY ANTIFOULING FINISH

PRECAUTIONS  
KEEP OUT OF REACH OF CHILDREN  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

## WARNING

Mix only in a closed container. When using do not eat, drink, or smoke. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe dust or vapor. Wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

## FIRST AID

**IF SWALLOWED:** Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

**IF IN EYES:** Hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

**IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice.

**IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice.

**Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.**

## TOXICOLOGICAL INFORMATION

Contains petroleum distillate. Do not induce vomiting.

## ENVIRONMENTAL HAZARDS

This material is toxic to aquatic organisms. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

## PHYSICAL OR CHEMICAL HAZARDS

Flammable. Do not use or store near heat or open flame.

## NOTICE TO USER

This pest control product is to be used only in accordance with the directions on the label. It is an offense under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label. The user assumes the risk to persons or property that arises from any such use of this product.

## DIRECTIONS FOR USE

**PREPARATION:** Scrape, wirebrush or sandpaper old surfaces to remove scum, contaminants or loose paint. On bare (unpainted) fiberglass, first scour and scrub with a strong abrasive agent. Rinse well with fresh water and allow to dry. Sand vigorously until all sheen on gel coat has been removed. Use 80 grit production paper to sand.

**PRIMING:** On new or bare wood areas and on unpainted fiberglass prepared as directed above, apply first coat of this paint thinned 10%. On steel or cast iron keels, centerboards or other underwater fittings, prime these areas with 3 coats of 4700/4701 High Build Epoxy Primer, carefully following the label directions for this primer.

**APPLICATION:** Mix thoroughly to uniform consistency by pouring off some of top portion into a clean can – then stirring the remainder and gradually adding the portion removed. Apply generously and at full body with good bristle brush, using long even strokes. Stir occasionally during use to assure uniform suspension of toxicants in the vehicle.

**NUMBER OF COATS:** For initial applications, 2 coats are recommended. Drying time between coats 3 hours.

**THINNING:** Reduce 10% with Pettit 120 Brushing Thinner, for brush use on bare surfaces-also for spray application. Otherwise apply this paint at full body, thinning sparingly if necessary.

**COVERAGE:** 46 square metres per 3.8 litres [ 500 square feet per gallon.]

**LAUNCHING:** Ready for use in four hours. Allow 3 days when an Epoxy Primer is used before launching. Maximum dry time before launching is 2 weeks.

## GENERAL DESCRIPTION

This product provides maximum protection from fouling of all kinds. Concentrated copper guards against attachment of barnacles, annelids, tunicates, bryozoa, hydroids, algae and other fouling organisms.

This product applies easily and dries quickly. May be used over old antifouling finishes in good condition.

This product is ideal for wood, fiberglass and properly primed metal boats.

## STORAGE

Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

## DISPOSAL

Triple or pressure rinse the empty container. Use the rinsings for thinner in future antifouling applications. Follow provincial instruction for any required additional cleaning of the container prior to its disposal. **Make the empty container unsuitable for further use.** Dispose of the container in accordance with provincial requirements. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency or the manufacturer in case of a spill, and for clean up of spills.

## DO NOT USE THIS PRODUCT ON ALUMINUM HULLS AND OUTDRIVES

MEDICAL EMERGENCIES: 1-800-548-0489

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.