Doktor Doom Wasp & Hornet Nest Annihilator II

Pressurized Product

Kills Wasps, Yellowjackets, and Hornets on contact

Reaches nests more than 15 feet above ground

DOMESTIC

REG. NO. 32170 P.C.P. ACT

READ THE LABEL BEFORE USING

ACTIVE INGREDIENT:

Tetramethrin0.200% d□phenothrin (SumithrinTM)... 0.125%

NET CONTENTS: ____ grams

DANGER

EXTREMELY FLAMMABLE

EXPLOSIVE

KEEP OUT OF REACH OF CHILDREN

READ THE LABEL BEFORE USING

753146 AB LTD O/A ULTRASOL 10755 - 69 Ave Edmonton, Alberta T6H 2C9 905 - 792 - 6571

DIRECTIONS FOR USE:

Do not treat when food is present. Clean treated surfaces before being used to prepare food. TOXIC to bees. This product is intended for use on yellow jackets, hornets and wasps only. NOT FOR USE INSIDE DWELLINGS. Shake well before using. Hold can upright before spraying. For Control of Nests of Wasps, Yellow jackets, and Hornets (in trees or attached to buildings): The best time to spray the nest is in the early morning or early evening, when air temperature is cooler and most insects are in the nest and little activity is observed around the nest opening. Spray only if the air is still. Stand at a safe distance from the nest, not directly under it. Hold container upright at arms length, point the actuator at the nest and spray into the opening of the nest first. Then spray the rest of the nest until it is saturated. Treated insects may fall out of the nest and die. Any insects returning to the nest after treatment will be killed. After 48 hours, wear gloves to remove the treated nest. Foliage of desirable plants that were contacted with spray should be hosed off.

PRECAUTIONS:

KEEP OUT OF REACH OF CHILDREN AND PETS. Harmful if swallowed or absorbed through skin. Do not breathe vapors or spray mist. Causes moderate eye irritation. May irritate skin. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Do not contaminate food, feedstuffs, food containers, utensils, and food preparation areas. This pesticide is toxic to fish and other aquatic invertebrates. Do not apply directly to water. Do not contaminate water during cleaning, or by disposal of wastes. Contents under pressure. Do not use or store near heat or open flame. Do not puncture or incinerate container. Exposure to temperatures above 50° may cause bursting. Do not apply this product around equipment due to possibility of shock hazard.

FIRST AID:

If swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person. If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 \square 20 minutes. Call a poison control centre or doctor for treatment advice. If inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth \square to \square mouth, if possible. Call a poison control centre or doctor for further treatment advice. If in eyes: Hold eye open and rinse slowly and gently with water for 15 \square 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. Take container, label or product name and PCP Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Contains petroleum distillate. Vomiting may cause aspiration pneumonia. Treat symptomatically.

DISPOSAL: Do not reuse empty container. When container is empty, press valve to release all remaining pressure. Wrap container in several layers of newspaper and discard in garbage.

STORAGE: Store in a cool dry area away from heat or open flame.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Toxic to bees. Do not spray bees.

Optional Marketing Statements;

- Gives rapid contact kill and residual kill of wasps and hornets returning to the treated nest
- Dielectric Breakdown Voltage: 41.0 KV by ASTM Test Method D□877□87