

2018-5758
2018-12-05

CHEMTREAT CL-206C

Controls bacteria, fungi and yeasts in paper mills, metalworking fluids containing water, and enhanced oil recovery systems; controls bacteria and algae in industrial recirculating water cooling towers.

INDUSTRIAL

DANGER

{Corrosive Hand symbol}
CORROSIVE

WARNING

{Skull & Crossbones symbol}
POISON

POTENTIAL SKIN SENSITIZER

READ THE LABEL BEFORE USING

ACTIVE INGREDIENT: 2,2-dibromo-3-nitrilopropionamide...20%

REGISTRATION No. 33077
PEST CONTROL PRODUCTS ACT

Chemtreat, Inc.
5640 Cox Road
Glen Allen, VA USA 23060
804-935-2000

HOT LINE NUMBER

In case of an emergency endangering life or property involving this product, call 519-339-3711. Have the product container or label with you when calling a poison control center or doctor or going for treatment.

NET CONTENTS: L

PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN

DANGER: CAUSES SEVERE BURNS OF EYES; MAY BURN THE SKIN; MAY BE HARMFUL OR FATAL IF SWALLOWED; POTENTIAL SKIN SENSITIZER

Do not get in eyes, on skin, or on clothing • Wear Chemical Workers' goggles when handling • Wear a long-sleeved shirt, long pants and shoes plus socks when handling • Wash thoroughly after handling • Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet • Users should remove clothing immediately if pesticide comes in contact with skin through soaked clothing or spills • Then wash skin thoroughly and put on clean clothing • Wash contaminated clothing separate from other laundry prior to reuse • Users should remove protective clothing immediately after handling this product • Wash the outside of gloves before removing • As soon as possible, wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and other aquatic organisms. It is not to be used in circumstances that would cause or allow it to enter lakes, streams, ponds, estuaries, oceans or other waters in contravention of federal or provincial regulatory requirements. The requirements of applicable laws should be determined before using the product. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority.

FIRST AID

If In Eyes

Hold eye open and rinse slowly and gently with water for 30 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice.

If On Skin Or Clothing

Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice.

If Swallowed

Call a poison control centre or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give anything by mouth to an unconscious person.

Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Treat symptomatically.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

DIRECTIONS FOR USE

NOTE: Add CHEMTREAT CL-206C separately to the system. Do not mix with other additives in order to avoid decomposition of CHEMTREAT CL-206C due to the high pH of many additive formulations.

PAPER MILLS

For the control of bacterial, fungal and yeast growth in pulp, paper and paper-board mills, add CHEMTREAT CL-206C at the rate of 60-210 mL/tonne of pulp or paper (dry basis). Addition may be continuous or intermittent, depending upon the type of system and the severity of contamination. It should be made with a metering pump at a location that will insure uniform distribution of CHEMTREAT CL-206C in the mass of fiber and water such as the beaters, jordan inlet or discharge, broke chest, furnish chests, save-alls and white-water tanks.

Heavily fouled systems should be boiled out, then treated with 60-140 mL CHEMTREAT CL-206C /tonne of paper (dry basis), as necessary for control.

Moderately fouled systems should be treated continuously with 140-210 mL CHEMTREAT CL-206C /tonne of paper (dry basis) until the slime accumulation is controlled. Addition rates can then be reduced to 60-140 mL CHEMTREAT CL-206C /tonne of paper on a continuous or intermittent basis, as needed for control. Dislodged slime may cause breaks in the paper and a cleanup of the paper machine may be advisable.

Slightly fouled systems should be treated continuously with 60-140 mL CHEMTREAT CL-206C /tonne of paper (dry basis) until the slime is controlled, then added on an intermittent basis to maintain control.

INDUSTRIAL RECIRCULATING WATER COOLING TOWERS

This product is for recirculating water systems only

Add CHEMTREAT CL-206C to the basin (or any other point of uniform mixing). Addition should be made with a metering pump. It may be continuous or intermittent, depending on the severity of the contamination when treatment is begun, and the retention time in the system.

Optimum performance with this product is attained by continuous or intermittent treatment. If “shock” treatment is used, the blowdown should be discontinued for 24-48 hours.

FOR CONTROL OF BACTERIA

Add 1.0-10 mL CHEMTREAT CL-206C /1000 L of water in the system, depending on the severity of contamination.

Intermittent or Slug Method – Initial Dose: When the system is noticeably fouled, add 5.0-10 mL CHEMTREAT CL-206C /1000 L of water in the system. Repeat until control is achieved.

Subsequent dose: When microbial control is evident, add 3.0-10 mL CHEMTREAT CL-206C /1000 L of water in the system every 4 days or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

Continuous Feed Method – Initial Dose: When the system is noticeably fouled, add 5.0-10 mL CHEMTREAT CL-206C /1000 L water to the system. Subsequently maintain this level by pumping a continuous feed of 0.5-5.0 mL CHEMTREAT CL-206C /1000 L of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

FOR CONTROL OF ALGAE Add 30-95 mL CHEMTREAT CL-206C /1000 L of water in the system, depending on the severity of contamination.

Intermittent or Slug Method – Initial Dose: When the system is noticeably fouled, add 50-95 mL CHEMTREAT CL-206C /1000 L of water in the system. Repeat until control is achieved.

Subsequent Dose: When algal control is evident, add 30-95 mL CHEMTREAT CL-206C /1000 L of water in the system daily, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

Continuous Feed Method – Initial Dose: When the system is noticeably fouled, add 50-95 mL CHEMTREAT CL-206C /1000 L of water to the system.

Subsequent Dose: Maintain this treatment level by pumping a continuous feed of 30-95 mL CHEMTREAT CL-206C /1000 L of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

MEMBRANE SYSTEMS FOR INDUSTRIAL WATER

CHEMTREAT CL-206C may be used to control bacteria and reduce biofouling in various membrane system types (reverse osmosis, ultrafiltration, nanofiltration, and microfiltration) used for industrial water processing. Acceptable applications include reverse osmosis for the production of boiler make-up water, electronic component rinsing, and industrial wastewater treatment.

NOTE: Reverse Osmosis (RO) concentrate streams must not be allowed to enter lakes, streams, ponds, estuaries, oceans or other waters in contravention of federal or provincial regulatory requirements. The requirements of applicable laws should be determined before using the product. Discharge of RO concentrate streams to sewer systems may require approval of the local sewer treatment plant authority.

CHEMTREAT CL-206C may be added to the RO feed water at a rate of 1 to 100 ppm based on the feed water flow rate (0.8 to 80 ml/min per cubic meter/min of feed water or 0.1 to 10 fl. oz./min per 1000 gallons/min). Apply product to the service cycle feed water on a regular basis using an addition cycle of at least 30 minutes. The frequency of addition may be daily or as necessary in order to maintain RO productivity performance. For highly fouled systems, a 100 ppm dosage should be applied each day for several hours until the system performance has recovered.

NOTE: Do not add CHEMTREAT CL-206C in the presence of sodium bisulfite or other reducing agents which are being added to the feed water of the membrane system. In some situations the addition of any reducing agents must be suspended at least 15 minutes prior to the addition of CHEMTREAT CL-206C in order to avoid neutralization and deactivation of the active ingredient.

CHEMTREAT CL-206C may be added to the feed tank used for an off-line chemical cleaning procedure. Addition should be at a rate of 20 to 200 ppm based on the total amount of solution in the feed tank (2 to 20 fl. oz. per 1000 gallons, or 16 to 160 mls. per cubic meter). Following the complete transfer of feed solution, re-circulate or soak for 1 to 3 hours to ensure sufficient contact for all RO membrane modules with the DBNPA solution. Frequency of addition should be every 5 days or as needed. NOTE: Add CHEMTREAT CL-206C separately to the feed tank system. Do not mix with other chemical additives as this may result in rapid decomposition of CHEMTREAT CL-206C due to the high pH of many additive formulas. It is important to thoroughly rinse the feed tank system so it is free of any high pH chemicals prior to introducing the CHEMTREAT CL-206C product.

METALWORKING FLUIDS CONTAINING WATER

This product is effective in metalworking concentrates which have been diluted in water at ratios of 1:100 to 1:4.

For controlling (or inhibiting) growth of bacteria, fungi and yeast that may deteriorate metalworking fluids containing water, add CHEMTREAT CL-206C to the fluid in the collection tank. Additions should be made with a metering pump.

Initial or Slug Dose: When the system is just noticeably fouled, add 250 mL CHEMTREAT CL-206C /1000 L of metalworking fluid to the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 100-200 mL CHEMTREAT CL-206C /1000 L of metalworking fluid per day or as needed to maintain control. Additions can be made continuously or intermittently. Slug the system as required.

OIL FIELD APPLICATIONS

For reduction of bacterial contamination and degradation in oil recovery operations, add product to the system at a rate of 24 to 216 mL per 1000 L water (30 to 270ppm product) depending on the severity of contamination. Add at a point of uniform mixing, at the concentration within the stated dosing range for the relevant product application. Subsequent treatments can be applied, as needed, to maintain an effective microbial control concentration, within the described dosage range. The stated concentration ranges provide microbial control of microorganisms at differing levels of contamination.

FRACTURING FLUIDS

The product reduces bacterial contamination and degradation of fracturing fluids and gels used in oil and gas well stimulations. The product must be added to the water storage tanks before

gelling and circulated to ensure mixing. The product can be added at the well head for “on-the-fly” fracturing jobs.

Dose: The product must be added at a rate of 72 to 216 mL per 1000 L water (90 to 270 ppm product) depending on water quality.

Retreat after 48 hours if the frac job is delayed.

ENHANCED OIL RECOVERY (EOR) FLUIDS

The product reduces bacterial contamination and degradation of EOR polymers and gels. The product must be added to injection water before polymer addition.

Dose: The product must be added at a rate of 24 to 216 mL per 1000 L water (30 to 270 ppm product). Product must be added at a point to ensure proper mixing.

WATER FLOOD

The product can be used to control slime and corrosion causing bacteria in waters used for secondary oil and gas recovery. If the system is heavily fouled, slug treat at the higher rate to remove biofilm. For maintenance, batch treat two to three times per week.

Dose: The product must be added at a rate of 24 mL to 216 mL per 1000 L water (30 to 270 ppm product). Product must be added at a point to ensure uniform mixing.

NOTICE TO USER: This pest control product is to be used only in accordance with the directions on the label. It is an offence under the *Pest Control Products Act* to use this product in a way that is inconsistent with the directions on the label.

STORAGE

To maintain product quality, store at temperatures below 35°C. Keep package tightly closed when not in use. Do not contaminate water, food or feed by storage or disposal.

DISPOSAL

1. Triple- or pressure rinse the empty container. Add the rinsings to the spray mixture in the tank.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

Made in USA