

2016-3907
2017-01-06

MATCHLESS SUPER MARINE

COMMERCIAL

FLAMMABLE

**DANGER
EYE AND SKIN
IRRITANT**

POISON

Guarantee: Copper as elemental present as cuprous oxide 8.78 % -

Warning: Contains the allergen "soya" present as soya lecithin.

REGISTRATION NUMBER 23511.01 - PEST CONTROL PRODUCTS ACT

READ THE LABEL BEFORE USING

Société Laurentide Inc.

4600 Boulevard de Shawinigan-Sud, Shawinigan-Sud Qc G9N 6T5 Canada

1 800 567-9481

3,78 L

PRECAUTIONS: KEEP OUT OF THE REACH OF CHILDREN . Remove personal protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing. Remove clothing/personal protective equipment immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them. For cleaning/ maintaining personal protective equipment, use detergent and hot water. Keep and wash personal protective equipment separately from other laundry. Wash hands before eating, drinking, chewing gum, smoking or using the toilet. Use an air assisted respirator mask that completely covers the entire face during handling and application. Wear long pants, a long-sleeved shirt and clothing resistant to chemicals. Gloves, a cap, socks and shoes should also be worn while mixing, applying, loading, cleaning or repairing this product. Handle with care and mix only in a closed container. • Use only in a well ventilated location. • Do not eat, drink or smoke during use. • Wear long pants, a long-sleeved shirt, shoes and socks during mixing/loading, application, clean up and repair.

FIRST AID: If on skin or clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control centre or doctor for treatment advice. If in eyes: Hold eye open and rinse slowly and gently with water for 15–20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control centre or doctor for treatment advice. If swallowed: Call a poison control centre or doctor immediately for treatment advice. Do not induce vomiting unless told to do so by a poison control centre or doctor. Do not give **any** liquid to the person. Do not give anything by mouth to an unconscious person. If inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control centre or doctor for further treatment advice. In case of inhalation: move the person towards a source of fresh air. If the person is not breathing, call 911 or an ambulance then practice artificial respiration, preferably mouth to mouth resuscitation, if possible. Call a poison control center or a doctor to get advise how to treat patient. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention. Pre-existing lung disease may be aggravated by regular exposure. Excessive exposure may lead to chronic respiratory disease.

TOXICOLOGICAL INFORMATION: Signs, symptoms and effects of excessive exposure: nausea, shivering, diarrhea. May cause irritation and congestion of upper respiratory organs, skin irritation, fever, eye irritation, conjunctivitis. This product contains petroleum distillates. Vomiting can cause aspiration pneumonia. Administer a symptomatic treatment. **MAIN TOXIC PATHWAYS:** Inhalation and/or ingestion.

NOTICE TO USER: This pest control product is to be used only in accordance with the directions on the label. It is an offence under the Pest Control Products Act to use this product in a way that is inconsistent with the directions on the label. The user assumes the risks to person or property that arises from any such use of this product.

ENVIRONMENTAL HAZARD: Toxic to aquatic organisms. Do not contaminate the water. Do not discharge directly into the water by washing equipment or disposing of waste in the water. When removing paint, do not allow flakes or dust to fall into the water.

DISPOSAL: 1. Triple or pressure-rinse the empty container. Add the rinsings to the treatment site. 2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal. 3. Make the empty container unsuitable for further use. 4. Dispose of the container in accordance with provincial requirements. 5. For information on the disposal of unused, unwanted product, contact the

manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill, and for clean-up of spills.

Alkyd paint for boats and rowboats constructed of wood, metal or fibreglass. In saltwater, use this Antifouling Paint below the water line to prevent the growth of barnacles and marine micro-organisms on the hull.

DIRECTIONS FOR USE:

DO NOT apply this product directly to freshwater habitats (such as lakes, rivers, sloughs, ponds, prairie potholes, creeks, marshes, streams, reservoirs, wetland or estuary/marine habitats. **DO NOT** apply this product in a manner that would put workers or people nearby in contact with it, either directly or indirectly. Only people wearing protective clothing and equipment should enter the painting area during application. **DO NOT** contaminate drinking water sources, irrigation water or wetland habitats during cleaning of the equipment or elimination of waste.

SURFACE PREPARATION

Surface must be clean, dry and free of contaminants (oil, grease, rust, etc.).

Recommended primers

- New wood: Matchless Primer 709
- New steel: Matchless Anticorrosive Primer 713
- Fiberglass: Duro-Sol Fiberglass Primer 8545-05
- Painted surface: Clean surfaces carefully. Use a wire brush to remove rust and flaked paint. Lightly sand glossy surfaces. Wipe sanding residue. Prime bare spots like a new surface.

APPLICATION

Mix thoroughly and apply as is with brush or roller. When spraying, add 250 ml of Chem-Sol 545-153 reducer to 3.78 litres of paint. Apply thin and uniform coats, only when temperature is above 10°C (maximum 32°C). Vessels over 25 metres must be treated by trained applicators.

THINNER AND CLEANER

Chem-Sol 545-153.

DRYING TIME

Allow a minimum of 16 hours between each coat and 48 hours before immersing in water.

COVERAGE

Approximately 9 m²/L (100 sq. ft./L)

Satisfaction guaranteed: If this product has been used as directed, and you are not completely satisfied with it, **Société Laurentide Inc.** pledges to replace it or reimburse the buyer for the cost of this product. *Please note: This warranty does not cover any expenses other than product replacement cost.*

Made in Canada

Société Laurentide Inc.

Shawinigan Richibucto

G9N 6T5 E4W 4C7