

87.02.06

Pittsburgh Paints

Exterior Stain & Wood Preservative

Semi-Transparent-Oil

Dark Walnut 77-953

GUARANTEE: Bis (tributyltin) oxide (TBTO) 0.50%

Do not apply this product by spray methods.

4 LITRES

DANGER IRRITANT

POISON

READ THE LABEL BEFORE USING.

For exterior use only.

Keep out of the reach of children.

Warning Eye Irritant.

DOMESTIC

REGISTRATION NO. 19591 PEST CONTROL PRODUCTS ACT

Also - See attached back panel warning and directions.

Stain - Semi-Transparent Oil

This semi-transparent stain helps to preserve wood and repels water. It exceeds the U.S. Federal Specification for water repellency. TT-W-572B Paragraph 3.7.

This stain enhances the natural beauty of wood and resists cracking, peeling and the fading caused by the effects of the sun's harmful rays. It will also guard against wood rot and mildew growth on the stain film.

Where to Use: Decks, porches, sawn siding, beams, shakes, fencing, shingles, wood trim and previously stained wood surfaces. Do not use below ground, or on abraded plywood.

Directions for Use: Do not apply this product where the preservative may become a component of food, feed, or drinking water. Do not apply this product to insitu waterfront structures such as docks, wharfs, or piers.

Coverage: Approx. 7.4 to 14.7 m²/L depending on wood texture.

Surface Preparation: Surface must be dry and free from dirt, sawdust, loose fibers, mildew, flaking or peeling paint or stain, grease, and other surface contamination. Countersink and spot prime all ferrous nails and fill voids with putty. Sand surface smooth, always with the grain. For woods prone to bleeding, such as redwood or red cedar, white or light coloured stains are not recommended.

Application: Stir thoroughly. Apply a full, even coat by brush, or roller. Apply thoroughly to ends, cuts and edges. Avoid applying in direct sunlight or when surface temperature is below 10°C. No thinning is usually required. Stain effects may vary slightly in colour on different species of wood. Test in a unseen area before proceeding.

Drying: Normally dries in 2 to 4 hours at 25°C and 50% relative humidity. May be recoated in 24 hours.

Clean-up: LEPTYNE(R) Paint Thinner, 21-263.

PRECAUTIONS TOXICOLOGICAL INFORMATION: CONTAINS PETROLEUM DISTILLATE AND Bis (tributyltin) oxide. KEEP OUT OF THE REACH OF CHILDREN.

Harmful if swallowed; may be absorbed through skin. Causes skin irritation. Avoid breathing of vapor. Do not get in eyes, on skin, or on clothing. Remove contaminated clothing immediately.

Wear eye protection, rubber gloves, and protective clothing when applying or when handling freshly treated lumber.

Combustible. Keep away from heat, sparks, or flame. Use with forced ventilation. Do not take internally. Close container after each use.

FIRST AID STATEMENT: If swallowed, do not induce vomiting. Call

a physician immediately. In case of contact, immediately flush eyes or skin with plenty of water. Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS: Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

STORAGE AND DISPOSAL: Securely wrap original container in several layers of newspaper and discard in trash. Do not reuse container. Store unused product in a safe place out of the reach of children. For Emergency Medical and Spill Control Information, (514) 645-1320.

YOUR SATISFACTION IS GUARANTEED: PPG guarantees your satisfaction with this product. If you're not satisfied, simply return the unused portion of the product to the store where you bought it, with proof of purchase, and the dealer will refund your purchase price or furnish you with replacement product, whichever you prefer.

Tint with Section 9

Tint with Section 5

Colour Formulas.

IMPORTED BY:

PPG CANADA, INC.
5546 TIMBERLEA BLVD.
MISSISSAUGA, ONTARIO
CANADA
L4W 2T7

PRINTED IN CANADA

(10990)

REGISTERED BY:

PPG INDUSTRIES, INC.
151 COLFAX STREET
SPRINGDALE, PA
U.S.A. 15144

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))