

07-FEB-2002

Interlux®
Tri-Lux IIT

Copolymer Antifouling Paint

Low TBT Release

**CORROSIVE
SKIN IRRITANT
EYE IRRITANT
DANGER
POISON
FLAMMABLE**

**NET CONTENTS
3.78 L**

COMMERCIAL

**IMPORTANT
READ THE LABEL BEFORE USING**

**GUARANTEE: Tributyltin Fluoride 3.5%
Tributyltin Methacrylate 6.8%**

**REGISTRATION NO. 23281
PEST CONTROL PRODUCTS ACT**

International Paint Inc.

2270 Morris Ave., Union, NJ 07083 • 908-686-1300

4850 Bois-Franc Road, Ville St. Laurent, Quebec H4S 1A7

TRI-LUX IIT

Copolymer Antifouling Paint

TRI-LUX IIT Antifouling Paint is a unique copolymer bottom paint available in a wide range of bright colours. TRI-LUX IIT is specifically formulated for aluminum crafts. TRI-LUX IIT dries very quickly to a tough abrasion resistant finish. TRI-LUX IIT coated boats can be trailered without mechanical damage or loss of antifouling performance.

SURFACE PREPARATION: If previous antifouling paint is a hard vinyl or epoxy type and in good condition, wash down with fresh water, degrease with INTERLUX Brushing Liquid 333 if required, sand surface lightly and use INTERLUX TRI-LUX IIT as directed. Otherwise, remove all old paint mechanically and/or use INTERLUX Pintoff 199 or 299 as appropriate. Do not burn

off. Proceed as for new work. Do not apply TRI-LUX IIT over graphite or soft antifouling. If there are excessive coats of old vinyl or hard epoxy antifouling on the surface to be painted, or weakness between or under those old coats, the “pulling” effect of TRI-LUX IIT may cause detachment. To prevent this from occurring, the excessive paint should be removed.

-Aluminum: Wipe bare metal with INTERLUX Thinner 216 to remove oil and grease. Etch by grinding with 36 grit paper to provide a good profile. Apply one thin coat of 353/354 INTERLUX Viny-Lux Primewash thinned with INTERLUX Thinner 355. Allow at least one hour but no more than 4 hours of drying time before overcoating. Apply at least 3 coats of 360R Underwater Metal Primer followed by 2-3 coats of INTERLUX TRI-LUX IIT observing overcoating times.

NOTE: Copolymer antifouling paints such as TRI-LUX IIT are non-porous coatings and may experience small pin head bubbles on a limited number TRI-LUX IIT boats. The bubbles are not the fault of the paint and do not affect the antifouling properties.

Certain areas of the hull experience faster erosion than other areas. These areas include the leading edge of the keel and rudder, the waterline and the bow. On these areas, we suggest an additional coat of paint to insure that the TRI-LUX IIT does not wash away before the other areas of the bottom.

HAUL OUTS AND WINTER STORAGE: Immediately after hauling, use a high pressure fresh water hose and a soft scrub brush to remove all trace of salt and slime. Failure to wash off slime will cause TRI-LUX IIT to lose antifouling properties. TRI-LUX IIT does not lose toxicity or antifouling properties during out of water storage. If after winter storage recoating is required, wash and clean surface again and allow thorough dry before applying fresh coat of TRI-LUX IIT.

DIRECTIONS FOR USE:

APPLICATION: STIR THOROUGHLY. Apply by brush or roller at least three unthinned heavy coats of INTERLUX TRI-LUX IIT. Use INTERLUX Brush-Ease 433 only if brush pulls or roller drags. For spray application, thin with INTERLUX Special Thinner 216.

Important: Success depends on initial film thickness applied.

COVERAGE: 7.2 m² per litre at 50 microns d.f.t. per coat.

CLEAN-UP: INTERLUX Brush-Ease 433 or INTERLUX Special Thinner 216.

DRYING: Touch dry: 3 hours**.

OVERCOATING TIME: Recommended minimum 16 hours**, maximum 6 months**.

IMMERSION: Minimum 16 hours**, maximum indefinite.

**N.B.: These are guidelines only. Temperature and humidity affect cure time.

NOTE: Large vessels, i.e.: over 25 m. : must be treated by trained applicators.

LIMITATION OF USE:

This product is for marine vessels only. This product is for use on aluminum hulled vessels only.

FOR MORE DETAILED INFORMATION, REFER TO PRODUCT DATA BULLETIN.

NOTICE TO USER

This control product is to be used only in accordance with the directions on this label. It is an

offense under the Pest Control Products Act to use a control product under unsafe conditions.

ENVIRONMENTAL HAZARDS: Toxic to aquatic organisms. Do not contaminate water by spillage, cleaning of equipment or disposal of wastes. Do not allow chips or dust generated during paint removal to enter water.

DISPOSAL

1. Triple or pressure-rinse the empty container. Add the rinsings to the treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal.
3. Make the empty container unsuitable for further use.
4. Dispose of the container in accordance with provincial requirements.
5. For information on the disposal of unused, unwanted product, contact the manufacturer or the provincial regulatory agency. Contact the manufacturer and the provincial regulatory agency in case of a spill.

PRECAUTIONS: KEEP OUT OF REACH OF CHILDREN. Wear an air-fed respirator with a full face mask during handling and applying. Wear chemical resistant gloves, and footwear, and chemical resistant clothing with head covering at all times during handling and applying. -Handle with care and mix carefully in a closed container - When using, do not eat, drink or smoke- Take a shower immediately after work- Wear freshly laundered clothes daily-Wash hands and face before eating, drinking, smoking and using the toilet-Store and wash all protective clothing separately from household laundry-Wash protective clothing in detergent and hot water before reuse-Use only in well ventilated areas- It is usually not necessary or desirable to sand TRI-LUX IIT.

FIRST AID: If splashed in eyes or on skin, flush thoroughly with water for 15 minutes. For eye contact, get medical attention. If swallowed, drink 2 or 3 glasses of milk or water. Do not induce vomiting. Call a physician or poison control centre immediately. Take container, label or product name and Pest Control Product Registration Number with you when seeking medical attention.

TOXICOLOGICAL INFORMATION: Contains petroleum distillates. Do not induce vomiting.

NOTICE TO BUYER: "Seller's guarantee shall be limited to the terms set out on the label and, subject thereto, the buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition".

DISCLAIMER:

The performance of any marine paint or coating depends on many factors outside the control of International Paint Inc. including surface preparation, proper application, and environmental conditions. Therefore, International Paint Inc. cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT INC. SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL

DAMAGES. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc.'s option.

Interlux

International Paint Inc.

2270 Morris Ave., Union, NJ 07083 • 908-686-1300

AKZO NOBEL

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.