1996/2001

MEGANTIC-12

SODIUM HYPOCHLORITE

READ THE LABEL BEFORE USING

CHLORINATING LIQUID

CONTROLS BACTERIA & ALGAE in Swimming Pool Waters

GUARANTEE: SODIUM HYPOCHLORITE 10.8% WHEN PACKED (10.3% AVAILABLE CHLORINE CONTENT)

> REGISTRATION NUMBER 21948 PEST CONTROL PRODUCTS ACT

WARNING CORROSIVE

NET CONTENTS 20 L

PRODUITS SANITAIRES J.P.L. INC. 4689 Laval, Lac Mégantic (Québec) G6B 1C4 Tél.: (819) 583-1510

PRECAUTIONS:

Keep out of reach of children. Dangerous gas formed when mixed with acid. Do not mix with any other chemical. Avoid contact with skin and eyes. Harmful if swallowed. Keep container tightly capped and store upright in a cool location. Rinse container thoroughly before discarding. To dispose of chemical, flush into sewer with large quantities of water. Use only as directed.

FIRST AID TREATMENT:

Contains Sodium Hypochlorite. If splashed in eyes or on skin, flush thoroughly with water for 15 minutes. For eye contact, get

medical attention. If swallowed, drink one glass of milk or water. Do not induce vomiting. Keep patient warm. Call a physician or Poison Control Center IMMEDIATELY.

NOTICE TO USER:

This control product is to be used only in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

USES: For general sanitation, disinfecting, bleaching - use 30 mL of this product per 5 L of water.

For specific uses... In water treatment, sewage and waste treatment... ask your distributor for technical assistance.

FOR SANITARY SWIMMING & WADING POOL WATER: Use this product daily for maintaining sanitary pool water. Also use for SHOCK TREATMENT, and OPENING/CLOSING your pool. This product is recommended for all types of pools.

- Does not damage or clog filters
- Effective in hard or soft water
- Ready to use NO PREMIXING

DIRECTIONS FOR USE: REGULAR TREATMENT Maintain recommended daily levels as determined by testing kit:

Free Available Chlorine:	1.0	-	3.0	ppm
pH:	7.2	-	7.8	
Total Alkalinity:	100	-	120	ppm
Calcium Hardness:	200	-	300	ppm

- 1. Before adding this product test the pH and adjust to within the 7.2 to 7.8 range. Add acid if pH is high. Add soda ash if pH is low.
- 2. Chlorinate daily to maintain proper chlorine residual with 250 mL of this product per 10,000 litres of pool water, or as needed.

NOTE: Hot weather, heavy pool usage and rain, may require higher dosage rates to maintain proper chlorine residuals.

OPENING NEW POOL: Superchlorinate (SHOCK) pool water by adding to the pool 1 L of this product per 10,000 L of pool water. For best results superchlorinate (SHOCK) at dusk.

OPENING/CLOSING POOL: For opening/closing pool, superchlorinate (SHOCK) pool water by adding 3 L of this product per 10,000 L of pool water. For best results superchlorinate (SHOCK) at dusk.

SHOCK TREATMENT: Superchlorinate (SHOCK) weekly with 1 L of this

product per 10,000 litres of pool water when average temperature is 25'C - 32'C. Otherwise, superchlorinate (SHOCK) every other week.

ALGAE CONTROL: For visible algae, superchlorinate (SHOCK) using 2 L of this product per 10,000 L of pool water. Heavy algae infestation may require dosages up to 3 L per 10,000 L. Vacuum pool when dead algae settles.

WADING POOLS: Chlorinate daily to maintain a chlorine residual of 3-5 ppm by adding 45 mL of this product per 1,000 L of pool water, or as needed.

NOTE: For outdoor pools, chlorine residuals can be protected from destruction by sun's rays by adding a stabilizer (cyanuric acid).

Store upright in a cool dark place Product not affected by freezing

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+))