

95/2000

WOODSTAT 30WB

LIQUID MICROBICIDE CONCENTRATE

READ THE LABEL BEFORE USING

INDUSTRIAL

GUARANTEE:

2-(thiocyanomethylthio) benzothiazole.....30% by weight

REGISTRATION NO. 20347

PEST CONTROL PRODUCTS ACT

NET CONTENTS: 1150 Litres (1275 kg)

WARNING

POISON                      CORROSIVE

SKIN IRRITANT

DANGER: CORROSIVE TO EYES

Diachem Industries Ltd.  
11420 Blacksmith Place  
Richmond, B.C.  
V7A 4X1  
(604)271-8855

POST A COPY OF THIS LABEL IN THE WORK AREA

NOTICE TO USER: This control product is to be used in accordance with the directions on this label. It is an offence under the Pest Control Products Act to use a control product under unsafe conditions.

NOTICE TO BUYER: Seller's guarantee shall be limited to the terms set out on the label and subject thereto, the buyer assumes all risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

DIRECTIONS FOR USE

Woodstat 30WB is an emulsifiable liquid microbicide concentrate,

is used to control sapstain and mold on freshly cut softwood and hardwood lumber, logs, poles, posts, and timbers.

LUMBER: Freshly cut lumber 5 cm or less in thickness should be dipped or sprayed until complete surface wetting is accomplished using a dispersion prepared by mixing 2.0 to 4.0 litres of Woodstat 30WB in 100 litres of water. Spray systems require special safeguards to isolate the Woodstat 30WB spray. All spray boxes must use flexible isolation brushes, curtains and other mechanisms on entrance or exit openings to contain the spray droplets. The spray box must be maintained under negative pressure to prevent the escape of entrained aerosols through the spraybox openings. Any misting is evidence of a faulty system, and workers should notify their supervisor immediately.

LOGS: Spray the ends and barkless areas of the freshly cut logs with a dispersion of 2.0 to 4.0 litres of Woodstat 30WB in 100 litres of water.

POLES, POSTS, AND TIMBERS: Dip or spray until all surfaces are wetted in a dispersion of 2.0 to 4.0 litres of Woodstat 30WB in 100 litres of water.

Logs should be bright and free of infection when converted into lumber. For best protection during warm weather, lumber should be treated within 24 hours after being sawed. Woodstat 30WB should be thoroughly dispersed in water using a mixing tank or container of known capacity prior to being added to the dipping vat. The dipping vat should be protected from rain to prevent dilution of dispersion.

Treated lumber should not be exposed to heavy rains immediately after treatment. Lumber piles should be as narrow as practicable, properly elevated, well-spaced, and adequately roofed. Treated logs, poles, posts, and timbers are not to be floated in lakes, rivers, streams or ocean.

Not for use in drive-through dip tanks.

#### PRECAUTIONS

##### KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. May be harmful if absorbed through the skin. Workers handling the product should wear impervious gloves and goggles and should avoid contact of the product with clothing and skin. After exposure, wash promptly and thoroughly with an abrasive soap and cool water and finally with glycerin. Avoid contact with skin and eyes. Repeated skin contact may cause skin sensitization to this product. Causes eye damage. Keep containers closed when not in use. Do not reuse other containers for other purposes.

Any treated wood is not to be used for constructing food holding

containers, food storage facilities, or food growing buildings (eg. mushroom houses).

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of wastes.

FIRST AID: If swallowed, call a physician immediately. Give patient doses of powdered charcoal immediately or all he can swallow of raw egg whites, gruel, or flour and water; then induce vomiting in conscious patient with soap or mustard in warm water, by gently tickling back of throat or by administering 15 mL of syrup of ipecac. Repeat until vomit is clear. In case of contact with the eyes, flood eyes immediately and thoroughly with cool water for 15 to 30 minutes. See a physician if any irritation persists. In case of persistent irritation of the skin, obtain medical attention.

#### DISPOSAL

1. Rinse the emptied container thoroughly and add the rinsings to treatment site.
2. Follow provincial instructions for any required additional cleaning of the container prior to its disposal or reconditioning.
3. Dispose of the container in accordance with provincial requirements.
4. For information on the disposal of unused, unwanted product and the cleanup of spills contact the regional office of the Environmental Protection Service, Environment Canada.
5. For small spills, recover free liquid; soak up residue with solid absorbent. DO NOT FLUSH INTO SURFACE STREAMS. INFORM ENVIRONMENT CANADA AS IN #4.

For further information on the storage, handling, preparation, application, and disposal of Woodstat wood preservative, refer to the "Guidelines for the Safe Use of TCMTB in Wood Protection" available from Diachem Industries Ltd.

\*\*\*\*\*

This label transcript service is offered by the Pest Management Regulatory Agency to provide efficient searching for label information. This service and this information do not replace the official hard-copy label. The PMRA does not provide any guarantee or assurance that the information obtained through this service is accurate, current or correct, and is therefore not liable for any loss resulting, directly or indirectly, from reliance upon this service.

+ ) )